

# K10B011UCH

cam changeover switch - 1 pole - 60° - 10 A -  
for Ø 16 or 22 mm



## Main

Range of product	Harmony K
Product or component type	Complete cam switch
Component name	K10
[I <sub>th</sub> ] conventional free air thermal current	10 A
Product mounting	Front mounting
Fixing mode	Ø 16 or 22 mm hole
Type of operator	Black handle
Rotary handle padlocking	Without
Presentation of legend	With metallic legend, 1 - 2 black marking
Cam switch function	Changeover switch
Return	Without
Off position	Without Off position
Poles description	1P
Switching positions	Left: 330° Right: 30°
IP degree of protection	IP20 (contact block) IP65 (operating head) conforming to IEC 60529

## Complementary

Cam switch head type	With front plate 30 x 30 mm
Switching angle	60 °
[U <sub>i</sub> ] rated insulation voltage	440 V , degree of pollution: 3 conforming to IEC 60947-1
Rated operational power in W	370 W AC-23A , 110/120 V 1 phase 750 W AC-23A , 220/240 V 1 phase 1800 W AC-23A , 220/240 V 3 phases
Rated power in hp	0.33 hp at 110/120 V AC , 1 phase 0.75 hp at 110/120 V AC , 3 phases 0.75 hp at 220/240 V AC , 1 phase 1 hp at 220/240 V AC , 3 phases
[I <sub>e</sub> ] rated operational current AC	3 A at 240 V AC-15 6 A at 120 V AC-15 10 A at 400 V AC-21A 10 A at 400 V AC-1
[I <sub>e</sub> ] rated operational current DC	0.3 A at 220 V resistive load 0.7 A at 110 V resistive load 10 A at 24 V resistive load
Electrical durability	100000000 cycles
Short circuit protection	10 A by cartridge fuse , type gG
[U <sub>imp</sub> ] rated impulse withstand voltage	4 kV conforming to IEC 60947-1
Contacts operation	Slow-break
Electrical connection	Captive screw clamp terminals , clamping capacity: 2 x 1.5 mm <sup>2</sup>
Mechanical durability	1000000 cycles
Product weight	0.035 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Environment

Standards	CENELEC EN 50013 EN/IEC 60947-3 EN/IEC 60947-5-1
Product certifications	CULus
Protective treatment	TC
Ambient air temperature for operation	-20...55 °C
Ambient air temperature for storage	-40...70 °C
Class of protection against electric shock	Class II conforming to IEC 60536
RoHS EUR conformity date	0627
RoHS EUR status	Compliant