

31174

visible break switch-disconnector Interpact INV630 - 630 A - 3 poles



Main

Device short name	Interpact INV630
Switch-disconnector name	Interpact INV630
Poles description	3P
Network type	AC DC
Network frequency	50/60 Hz
[Ie] rated operational current	AC-21A: 630 A AC 50/60 Hz 220/240 V AC-21A: 630 A AC 50/60 Hz 380/415 V AC-21A: 630 A AC 50/60 Hz 440/480 V AC-21A: 630 A AC 50/60 Hz 500/525 V AC-21A: 630 A AC 50/60 Hz 660/690 V AC-21A: 630 A AC 50/60 Hz 480 V NEMA AC-22A: 630 A AC 50/60 Hz 220/240 V AC-22A: 630 A AC 50/60 Hz 380/415 V AC-22A: 630 A AC 50/60 Hz 440/480 V AC-22A: 630 A AC 50/60 Hz 500/525 V AC-22A: 550 A AC 50/60 Hz 660/690 V AC-22A: 630 A AC 50/60 Hz 480 V NEMA AC-23A: 630 A AC 50/60 Hz 220/240 V AC-23A: 630 A AC 50/60 Hz 380/415 V AC-23A: 630 A AC 50/60 Hz 440/480 V AC-23A: 500 A AC 50/60 Hz 500/525 V AC-23A: 500 A AC 50/60 Hz 660/690 V AC-23A: 630 A AC 50/60 Hz 480 V NEMA AC-23B: 630 A AC 50/60 Hz 220/240 V AC-23B: 630 A AC 50/60 Hz 380/415 V AC-23B: 630 A AC 50/60 Hz 440/480 V AC-23B: 630 A AC 50/60 Hz 500/525 V AC-23B: 630 A AC 50/60 Hz 660/690 V AC-23B: 630 A AC 50/60 Hz 480 V NEMA DC-21A: 550 A DC 125 V 2 poles in series DC-22A: 550 A DC 125 V 2 poles in series DC-23A: 550 A DC 125 V 2 poles in series DC-23B: 630 A DC 125 V 2 poles in series
[Ui] rated insulation voltage	750 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	8 kV
[Ith] conventional free air thermal current	630 A (60 °C)
[Icm] rated short-circuit making capacity	50 kA 690 V AC 50/60 Hz switch-disconnector alone 330 kA 690 V AC 50/60 Hz with upstream protection circuit breaker
[Ue] rated operational voltage	125 V DC 690 V AC 50/60 Hz
Suitability for isolation	Yes
Contact position indicator	Yes
Visible break	Yes
Pollution degree	3

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Complementary

Control type	Direct front rotary handle
Mounting mode	Fixed
Mounting support	Plate Rail
Upside connection	Front
Downside connection	Front
Maximum power	AC-23: 200 kW 220/240 V AC 50/60 Hz AC-23: 315 kW 380/415 V AC 50/60 Hz AC-23: 400 kW 440 V AC 50/60 Hz AC-23: 400 kW 500/525 V AC 50/60 Hz AC-23: 560 kW 660/690 V AC 50/60 Hz AC-23: 200 kW 230 V NEMA AC 50/60 Hz AC-23: 375 kW 480 V NEMA AC 50/60 Hz
Rated duty	Uninterrupted
[I _{lcw}] rated short-time withstand current	4 kA (30 s) conforming to IEC 60947-3 4.9 kA (20 s) conforming to IEC 60947-3 11.5 kA (3 s) conforming to IEC 60947-3 20 kA (1 s) conforming to IEC 60947-3
Mechanical durability	10000 cycles
Electrical durability	AC-21A: 1000 cycles 440 V AC 50/60 Hz AC-21A: 1000 cycles 500 V AC 50/60 Hz AC-21A: 1000 cycles 690 V AC 50/60 Hz AC-22A: 1000 cycles 440 V AC 50/60 Hz AC-22A: 1000 cycles 500 V AC 50/60 Hz AC-22A: 1000 cycles 690 V AC 50/60 Hz AC-23A: 1000 cycles 440 V AC 50/60 Hz AC-23A: 1000 cycles 500 V AC 50/60 Hz AC-23A: 1000 cycles 690 V AC 50/60 Hz AC-23B: 200 cycles 500 V AC 50/60 Hz AC-23B: 200 cycles 690 V AC 50/60 Hz DC-21A: 1000 cycles 125 V DC DC-22A: 1000 cycles 125 V DC DC-23A: 1000 cycles 125 V DC DC-23B: 200 cycles 125 V DC
Connection pitch	45 mm
Height	205 mm
Width	185 mm
Depth	130 mm
Product weight	4.6 kg

Environment

Standards	IEC 60947-1 IEC 60947-3
Product certifications	CCC KEMA-KEUR
IP degree of protection	IP40 conforming to IEC 60529
IK degree of protection	IK07 conforming to EN 50102
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-50...85 °C
RoHS EUR conformity date	0826
RoHS EUR status	Compliant