



Main

Range of product	PowerLogic AMP
Device short name	AMP
[In] rated current	0...30 A
Technology type	Ferromagnetic
Scale type	Pseudo-linear scale over 90°
Mounting support	DIN rail

Complementary

Type of measurement	Current
Accuracy class	Class 1.5
Power consumption	1.1 VA
Overload withstand	1.2 In permanently 10 In 5 s
9 mm pitches	8
Temperature drift	+/- 0.03 %/°C
Auxiliary connection terminal	Tunnel type terminal rigid 1.5...6 mm ²

Environment

Standards	IEC 60051-1 IEC 61000-4 IEC 61010-1
Climatic withstand	Operating temperature : - 25...55 °C
Reference temperature	23 °C
RoHS EUR conformity date	0610
RoHS EUR status	Compliant

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.