



SETRON, cylindrical fuse link, 10 x 38 mm, 6 A, gG, Un AC: 500 V

Model			
product brand name	SETRON		
product designation	Cylindrical fuse link		
General technical data			
operating class of the fuse link	gG		
size of the fuse link	10x38 mm		
type of voltage / of the operating voltage	AC		
operating voltage / at AC / rated value	500 V		
Dissipation			
power loss [W] / for rated value of the current / at AC / in hot operating state / per pole	0.95 W		
operational current / at AC / rated value	6 A		
Main circuit			
operational current / rated value	6 A		
Product details			
product component / striker	No		
Mechanical Design			
mounting position	Any, preferably vertical		
net weight	7 g		
General Product Approval	Declaration of Conformity	Test Certificates	other



[UK Declaration of Conformity](#)



[Miscellaneous](#)

[Miscellaneous](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NW6001-1>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3NW6001-1>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NW6001-1

CAx-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



