



Connecting terminal, 50 mm<sup>2</sup> according to UL 489, 480Y/277V for LS 5SJ4...-HG Infeed busbar

Model	
product brand name	SENTRON
product designation	Connecting terminal
design of the product	50 mm <sup>2</sup> , acc. to UL 489, 480Y/277 V for MCBs 5SJ4...-HG infeed busbar
operating voltage / at AC / rated value	1 000 V
operational current / at AC / rated value	160 A
Accessories	
accessories	connection terminal
Connections	
tightening torque	
• minimum	2 N·m
• maximum	3.5 N·m
type of connectable conductor cross-sections / for copper conductor / stranded	2.5 - 50 mm <sup>2</sup>
Mechanical Design	
height	51 mm
width	17.75 mm
length	31.2 mm
net weight	33 g
General Product Approval	
Declaration of Conformity	
other	



[Miscellaneous](#)



[Miscellaneous](#)

### Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mfb=5ST3666-2HG>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5ST3666-2HG>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mfb=5ST3666-2HG](http://www.automation.siemens.com/bilddb/cax_en.aspx?mfb=5ST3666-2HG)

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



