



### Product features and key data

|                                |                         |
|--------------------------------|-------------------------|
| Luminaire colour               | RAL9006 White aluminium |
| Wiring                         | 7LV                     |
| Ingress Protection (IP) rating | IP20                    |
| Protection class               | I                       |
| Net length                     | 4.425 mm                |
| Net width                      | 63 mm                   |
| Net height                     | 41,40 mm                |
| Weight                         | 5,4 kg                  |

### Available accessories

| Material                                                                                                                                | Description                                                                                                                |
|-----------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------|
|  <b>07690TL Luminaire Support Bracket</b><br>2196600 | Luminaire support bracket (1 pair), sheet steel, galvanised.                                                               |
|  <b>E04 Kette glzvz (20m)</b><br>2343400             | Chain bright zinc-plated (20 m).                                                                                           |
|  <b>A01SX/1500</b><br>2230700                        | Wire suspension with fixing clip.                                                                                          |
|  <b>A01KX/1500</b><br>2230100                        | Chain suspension consisting of link chain, bright zinc-plated, length 1500 mm, with turnbuckle and suspension clamp E03KX. |
|  <b>A01DSX/1500</b><br>2229600                       | Decorative wire suspension with suspension clip.                                                                           |
|  <b>E03KX</b><br>2342800                             | Suspension clamp for chain mounting.                                                                                       |
|  <b>E03SX</b><br>2343200                             | Suspension clamp for fixing to steel wire.                                                                                 |
|  <b>07690LHI Cable Holder 10pcs</b><br>2195300       | Cable restraint for cable routing in trunking with through-wiring.                                                         |
|  <b>D01X</b><br>2321200                              | Fixing clip for direct ceiling surface-mounting.                                                                           |
|  <b>07690LHA Cable Holder</b><br>2195200             | Outer cable restraint.                                                                                                     |

|                                                                                     |                                            |                                                                                                                                                                                        |
|-------------------------------------------------------------------------------------|--------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|    | <b>07690SK Female Connector</b><br>2195900 | Female connector for ribbon cable wiring. 7-pole, for electrical contact of ribbon cables 07690/5LV/46m and 07690/7LV/46m.                                                             |
|    | <b>07690VV Wiring Connector</b><br>2197300 | Wiring connector, 7-pole plug socket pair                                                                                                                                              |
|    | <b>07690TO</b><br>2196700                  | Female connectors, for electrical contact of single wires. 5-pole, for tool-free electrical connection between single-core cables subsequently integrated into trunking and gear trays |
|    | <b>E03SKX</b><br>6188900                   | Suspension clamp for chain mounting. Height-adjustable, flexible version.                                                                                                              |
|    | <b>A01SXVA</b><br>6817000                  | 1 piece. Wire suspension with fixing clip                                                                                                                                              |
|    | <b>07650 Flex con-cab 3pol</b><br>6912100  | Flexible connection cable for E-Line LED gear tray.                                                                                                                                    |
|    | <b>07650 Flex con-cab 5pol</b><br>6912200  | Flexible connection cable for E-Line LED gear tray.                                                                                                                                    |
|    | <b>07650 Ks 03</b><br>7260600              | End cap for terminating an E-Line 7651 continuous line application IP20.                                                                                                               |
|   | <b>A01DSX/3000</b><br>7234300              | 1 piece. Decorative wire suspension with suspension clip. 3000 mm                                                                                                                      |
|  | <b>A01DSX/5000</b><br>7234400              | 1 piece. Decorative wire suspension with suspension clip, 5000 mm                                                                                                                      |
|  | <b>A01SKX/1500</b><br>7234500              | 1 piece. {Reference (Object) not found: tb1848822583891}                                                                                                                               |
|  | <b>A01SX/5000</b><br>7234600               | 1 piece. Wire suspension with fixing clip, 5000 mm                                                                                                                                     |
|  | <b>07650 BL L225 03</b><br>7259300         | Blank cover for E-Line 7651 continuous line system. PVC. Colour silver gray (similar to RAL 9006). Length 2211,5 mm.                                                                   |
|  | <b>07650 BL L187 03</b><br>7259400         | Blank cover for E-Line 7651 continuous line system. PVC. Colour silver gray (similar to RAL 9006). Length 1843 mm.                                                                     |
|  | <b>07650 BL L150 03</b><br>7259500         | Blank cover for E-Line 7651 continuous line system. PVC. Colour silver gray (similar to RAL 9006). Length 1474 mm.                                                                     |
|  | <b>07650 BL L112 03</b><br>7259600         | Blank cover for E-Line 7651 continuous line system. PVC. Colour silver gray (similar to RAL 9006). Length 1105,5 mm.                                                                   |
|  | <b>07650 BL L75 03</b><br>7259700          | Blank cover for E-Line 7651 continuous line system. PVC. Colour silver gray (similar to RAL 9006). Length 736,5 mm.                                                                    |
|  | <b>07650 BL L37 03</b><br>7259800          | Blank cover for E-Line 7651 continuous line system. PVC. Colour silver gray (similar to RAL 9006). Length 368 mm.                                                                      |
|  | <b>07650 BL-M L112 03</b><br>7219500       | Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour silver gray (similar to RAL 9006). Length 1105,5 mm.                                                   |
|  | <b>07650 BL-M L37 03</b><br>7219800        | Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour silver gray (similar to RAL 9006). Length 368 mm.                                                      |

|                                                                                     |                                              |                                                                                                                                                       |
|-------------------------------------------------------------------------------------|----------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|
|    | <b>07650 BL-M L75 03</b><br>7220100          | Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour silver gray (similar to RAL 9006). Length 737 mm.                     |
|    | <b>07650 BL-M L187 03</b><br>7220400         | Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour silver gray (similar to RAL 9006). Length 1842,5 mm.                  |
|    | <b>07650 BL-M L150 03</b><br>7223000         | Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour silver gray (similar to RAL 9006). Length 1474 mm.                    |
|    | <b>07650 BL-M L225 03</b><br>7223100         | Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour silver gray (similar to RAL 9006). Length 2211 mm.                    |
|    | <b>07650 BL-M 5-pol L37 03</b><br>7225600    | Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour silver gray (similar to RAL 9006). Length 368 mm.                     |
|    | <b>07650 BL-M 5-pol L75 03</b><br>7225700    | Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour silver gray (similar to RAL 9006). Length 737 mm.                     |
|    | <b>07650 BL-M 5-pol L112 03</b><br>7225800   | Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour silver gray (similar to RAL 9006). Length 1105,5 mm.                  |
|    | <b>07650 BL-M 5-pol L150 03</b><br>7225900   | Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour silver gray (similar to RAL 9006). Length 1474 mm.                    |
|   | <b>07650 BL-M 5-pol L187 03</b><br>7226000   | Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour silver gray (similar to RAL 9006). Length 1842,5 mm.                  |
|  | <b>07650 BL-M 5-pol L225 03</b><br>7226100   | Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour silver gray (similar to RAL 9006). Length 2211 mm.                    |
|  | <b>07650 L-Connector 03</b><br>7508700       | Connector for L-shaped continuous line applications. Colour silver gray (similar to RAL 9006). Dimensions (L x W): 362 mm x 362 mm.                   |
|  | <b>07650 T-Connector 03</b><br>7509000       | Connector for T-shaped continuous line applications. Colour silver gray (similar to RAL 9006). Dimensions (L x W): 659 mm x 362 mm.                   |
|  | <b>07650 X-Connector 03</b><br>7509300       | Connector for X-shaped continuous line applications. Colour silver gray (similar to RAL 9006). Dimensions (L x W): 659 mm x 659 mm.                   |
|  | <b>07650 BL L5 03</b><br>7688400             | Blank cover for E-Line 7651 continuous line system. PVC. Colour silver gray (similar to RAL 9006). Length 55 mm.                                      |
|  | <b>A01DSXOE/1500</b><br>7694900              | Decorative wire suspension with stainless steel suspension clip, galvanised steel wire (Ø 1.5 mm) and eyelet. For E-Line 7651 continuous line system. |
|  | <b>A01DSXOE/3000</b><br>7695000              | Decorative wire suspension with stainless steel suspension clip, galvanised steel wire (Ø 1.5 mm) and eyelet. For E-Line 7651 continuous line system. |
|  | <b>A01DSXOE/6000</b><br>7695100              | Decorative wire suspension with stainless steel suspension clip, galvanised steel wire (Ø 1.5 mm) and eyelet. For E-Line 7651 continuous line system. |
|  | <b>07650IP BL-M 5-pol L37 03</b><br>7786400  | Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour silver gray (similar to RAL 9006). Length 368 mm.                     |
|  | <b>07650IP BL-M 5-pol L75 03</b><br>7786500  | Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour silver gray (similar to RAL 9006). Length 737 mm.                     |
|  | <b>07650IP BL-M 5-pol L112 03</b><br>7786600 | Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour silver gray (similar to RAL 9006). Length 1106 mm.                    |

|                                                                                     |                                              |                                                                                                                                    |
|-------------------------------------------------------------------------------------|----------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------|
|    | <b>07650IP BL-M 5-pol L150 03</b><br>7786700 | Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour silver gray (similar to RAL 9006). Length 1474 mm. |
|    | <b>07650IP BL-M 5-pol L187 03</b><br>7786800 | Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour silver gray (similar to RAL 9006). Length 1843 mm. |
|    | <b>07650IP BL-M 5-pol L225 03</b><br>7786900 | Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour silver gray (similar to RAL 9006). Length 2211 mm. |
|    | <b>07650IP BL-M L112 03</b><br>7787700       | Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour silver gray (similar to RAL 9006). Length 1106 mm. |
|    | <b>07650IP BL-M L37 03</b><br>7788000        | Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour silver gray (similar to RAL 9006). Length 368 mm.  |
|    | <b>07650IP BL-M L75 03</b><br>7788300        | Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour silver gray (similar to RAL 9006). Length 737 mm.  |
|    | <b>07650IP BL-M L187 03</b><br>7788600       | Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour silver gray (similar to RAL 9006). Length 1843 mm. |
|    | <b>07650IP BL-M L150 03</b><br>7789000       | Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour silver gray (similar to RAL 9006). Length 1474 mm. |
|   | <b>07650IP BL-M L225 03</b><br>7789100       | Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour silver gray (similar to RAL 9006). Length 2211 mm. |
|  | <b>07650IP Ks 03</b><br>7789700              | End cap for terminating an E-Line 7651 continuous line application IP50.                                                           |
|  | <b>07650IP BL L112 03</b><br>7712100         | Blank cover for E-Line 7651 continuous line system. PVC. Colour silver gray (similar to RAL 9006). Length 1105,4 mm.               |
|  | <b>07650IP BL L150 03</b><br>7712400         | Blank cover for E-Line 7651 continuous line system. PVC. Colour silver gray (similar to RAL 9006). Length 1474 mm.                 |
|  | <b>07650IP BL L187 03</b><br>7712700         | Blank cover for E-Line 7651 continuous line system. PVC. Colour silver gray (similar to RAL 9006). Length 1842,8 mm.               |
|  | <b>07650IP BL L225 03</b><br>7713000         | Blank cover for E-Line 7651 continuous line system. PVC. Colour silver gray (similar to RAL 9006). Length 2211,2 mm.               |
|  | <b>07650IP BL L37 03</b><br>7713300          | Blank cover for E-Line 7651 continuous line system. PVC. Colour silver gray (similar to RAL 9006). Length 368 mm.                  |
|  | <b>07650IP BL L75 03</b><br>7713600          | Blank cover for E-Line 7651 continuous line system. PVC. Colour silver gray (similar to RAL 9006). Length 736,5 mm.                |
|  | <b>07650IP BL L5 03</b><br>8362600           | Blank cover for E-Line 7651 continuous line system. PVC. Colour silver gray (similar to RAL 9006). Length 54,5 mm.                 |
|  | <b>07650IP BL L153 03</b><br>8362900         | Blank cover for E-Line 7651 continuous line system. PVC. Colour silver gray (similar to RAL 9006). Length 1530 mm.                 |
|  | <b>07650 BL L153 03</b><br>8363100           | Blank cover for E-Line 7651 continuous line system. PVC. Colour silver gray (similar to RAL 9006). Length 1529 mm.                 |
|  | <b>A01SX/3000</b><br>3664499                 | 1 piece. Wire suspension with fixing clip, 3000 mm                                                                                 |



**D01X m Caddy-Clip 01**  
4068899

Fixing clamp with caddy clip for quick mounting on suitable profile steel without drilling. The quantity and mounting positions depend on the system ceiling, luminaire load and luminaire arrangement. Observe the specifications of the ceiling manufacturer.



**D01X m Caddy-Clip**  
4068999

Fixing clamp with caddy clip for quick mounting on suitable profile steel without drilling. The quantity and mounting positions depend on the system ceiling, luminaire load and luminaire arrangement. Observe the specifications of the ceiling manufacturer.



**07690VS 2,5² L100**  
6822100

Connection cable with 7-pole plug, 100 mm.



**07690/1LV 2.5² L300**  
6822200

Connection cable for central infeed of the E-Line trunking profiles.



**07690VS**  
6822300

Plug for power feed, 7-pole, fixed.

#### Offer text

Trunking for E-Line 7651 continuous line applications. To simplify installation, a pre-assembled continuous line coupler is included in the scope of delivery for connection to a further trunking unit. Length of the trunking: 4425 mm. With 7-conductor through-wiring. Cable cross-section 2.5 mm<sup>2</sup>. With 12 female connectors for tool-free, electrical connection of the gear trays at 370 mm intervals. With 7-pole plug/socket pair for rapid electrical connection and termination at ends with protection against accidental contact. The heat-resistant through-wiring is factory-completed with all necessary components. All connections are designed for fast connection and are with reverse polarity protection. The electrical feed can be made without accessories through an upper knockout (M20/PG13.5). The trunking body is made of hot-dip galvanised sheet steel. Surface coated silver-grey.