

UK 16 N BU - Feed-through terminal block



3006056

<https://www.phoenixcontact.com/ro/produse/3006056>

Vă rugăm să țineți cont de faptul că datele afișate în acest document PDF au fost generate din catalogul nostru online. Datele complete sunt disponibile în documentația pentru utilizator. În cazul descărcărilor, se aplică Termenii și condițiile generale de utilizare ale companiei noastre.



Feed-through terminal block, nom. voltage: 800 V, nominal current: 76 A, number of connections: 2, connection method: Screw connection, Rated cross section: 16 mm², cross section: 2.5 mm² - 25 mm², mounting type: NS 35/7,5, NS 35/15, NS 32, color: blue

Avantajele dumneavoastră

- All universal terminal blocks in the UK... series can also be used in the Ex e area according to IEC/EN 60079 as standard
- The corresponding EC-type examination numbers for Ex approval can be found in the technical connection data

Date comerciale

Număr articol	3006056
Unitate de ambalare	50 Bucată
Cantitate minimă pentru comandă	1 Bucată
Cod produs	BE1211
Pagina de catalog	Pagina 461 (C-1-2019)
GTIN	4017918091316
Greutate pe bucată (inclusiv ambalajul)	23,3 g
Greutate pe bucată (fără ambalaj)	22,3 g
Cod tarifar vamal	85369010
Țara de origine	IN

UK 16 N BU - Feed-through terminal block



3006056

<https://www.phoenixcontact.com/ro/produse/3006056>

Date tehnice

Product properties

Product type	Feed-through terminal block
Number of connections	2
Number of rows	1
Potentials	1

Data management status

Article revision	09
------------------	----

Insulation characteristics

Overvoltage category	III
Degree of pollution	3

Electrical properties

Rated surge voltage	8 kV
Maximum power dissipation for nominal condition	2.43 W

Connection data

Number of connections per level	2
Nominal cross section	16 mm ²

Level 1 above 1 below 1

Screw thread	M4
Tightening torque	1.5 ... 1.8 Nm
Stripping length	11 mm
Internal cylindrical gage	B7
Connection in acc. with standard	IEC 60947-7-1
Conductor cross section rigid	2.5 mm ² ... 25 mm ²
Cross section AWG	12 ... 4 (converted acc. to IEC)
Conductor cross section flexible	4 mm ² ... 16 mm ²
Conductor cross section, flexible [AWG]	10 ... 6 (converted acc. to IEC)
Conductor cross-section flexible (ferrule without plastic sleeve)	1.5 mm ² ... 16 mm ²
Flexible conductor cross section (ferrule with plastic sleeve)	1.5 mm ² ... 16 mm ²
2 conductors with same cross section, solid	1.5 mm ² ... 6 mm ²
2 conductors with same cross section, flexible	1.5 mm ² ... 4 mm ²
2 conductors with same cross section, flexible, with ferrule without plastic sleeve	1.5 mm ² ... 6 mm ²
2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve	0.75 mm ² ... 10 mm ²
Nominal current	76 A
Maximum load current	101 A (with 25 mm ² conductor cross section)
Nominal voltage	800 V
Nominal cross section	16 mm ²

UK 16 N BU - Feed-through terminal block



3006056

<https://www.phoenixcontact.com/ro/produse/3006056>

Ex data

Rated data (ATEX/IECEx)

Identification	Ex II 2 GD Ex eb IIC Gb
Operating temperature range	-60 °C ... 110 °C
Ex-certified accessories	3006027 D-UK 16
	1205066 SZS 1,0X4,0 VDE
	1201442 E/UK
List of bridges	Fixed bridge / FBI 2-12 / 0200075
	Fixed bridge / FBI 10-12 / 0203454
Bridge data	66 A / 16 mm ²
Ex temperature increase	40 K (75.1 A / 16 mm ²)
Rated voltage	690 V
for bridging with bridge	690 V
Rated insulation voltage	630 V
output	(Permanent)

Ex level General

Rated current	68 A
Maximum load current	91 A
Contact resistance	0.17 mΩ

Ex connection data General

Torque range	1.5 Nm ... 1.8 Nm
Nominal cross section	16 mm ²
Rated cross section AWG	6
Connection capacity rigid	2.5 mm ² ... 25 mm ²
Connection capacity AWG	14 ... 4
Connection capacity flexible	4 mm ² ... 16 mm ²
Connection capacity AWG	12 ... 6
2 conductors with same cross section, solid	1.5 mm ² ... 6 mm ²
2 conductors with the same cross-section AWG rigid	16 ... 10
2 conductors with same cross section, stranded	1.5 mm ² ... 4 mm ²
2 conductors with the same cross-section AWG flexible	16 ... 12

Dimensions

Width	12.2 mm
End cover width	1.5 mm
Height	42.5 mm
Depth on NS 32	59 mm
Depth on NS 35/7,5	54 mm
Depth on NS 35/15	61.5 mm

Material specifications

Color	blue
-------	------

UK 16 N BU - Feed-through terminal block



3006056

<https://www.phoenixcontact.com/ro/produse/3006056>

Flammability rating according to UL 94	V0
Insulating material group	I
Insulating material	PA
Static insulating material application in cold	-60 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21))	130 °C
Relative insulation material temperature index (Elec., UL 746 B)	130 °C
Fire protection for rail vehicles (DIN EN 45545-2) R22	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26	HL 1 - HL 3
Calorimetric heat release NFPA 130 (ASTM E 1354)	28 MJ/kg
Surface flammability NFPA 130 (ASTM E 162)	passed
Specific optical density of smoke NFPA 130 (ASTM E 662)	passed
Smoke gas toxicity NFPA 130 (SMP 800C)	passed

Electrical tests

Surge voltage test

Test voltage setpoint	9.8 kV
Result	Test passed

Temperature-rise test

Requirement temperature-rise test	Increase in temperature ≤ 45 K
Result	Test passed
Short-time withstand current 16 mm ²	1.92 kA
Result	Test passed

Power-frequency withstand voltage

Test voltage setpoint	2 kV
Result	Test passed

Mechanical properties

Mechanical data

Open side panel	Yes
-----------------	-----

Mechanical tests

Mechanical strength

Result	Test passed
--------	-------------

Attachment on the carrier

DIN rail/fixing support	NS 32/NS 35
Test force setpoint	10 N
Result	Test passed

Test for conductor damage and slackening

UK 16 N BU - Feed-through terminal block



3006056

<https://www.phoenixcontact.com/ro/produse/3006056>

Rotation speed	10 rpm
Revolutions	135
Conductor cross section/weight	2.5 mm ² / 0.7 kg
	16 mm ² / 2.9 kg
	25 mm ² / 4.5 kg
Result	Test passed

Environmental and real-life conditions

Needle-flame test

Time of exposure	30 s
Result	Test passed

Ambient conditions

Ambient temperature (operation)	-60 °C ... 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.)
Ambient temperature (storage/transport)	-25 °C ... 60 °C (for a short time, no longer than 24 h, -60°C to +70°C)
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C
Permissible humidity (operation)	20 % ... 90 %
Permissible humidity (storage/transport)	30 % ... 70 %

Standards and regulations

Connection in acc. with standard	IEC 60947-7-1
----------------------------------	---------------

Mounting

Mounting type	NS 35/7,5
	NS 35/15
	NS 32

UK 16 N BU - Feed-through terminal block

3006056

<https://www.phoenixcontact.com/ro/produse/3006056>



Desene

Circuit diagram



UK 16 N BU - Feed-through terminal block



3006056

<https://www.phoenixcontact.com/ro/produse/3006056>

Aprobări

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/ro/produse/3006056>

DNV

ID de înregistrare: TAE00001CT



CSA

ID de înregistrare: 13631

	Tensiune nominală U_N	Curent nominal I_N	Secțiune transversală AWG	Secțiune transversală mm^2
	600 V	85 A	22 - 4	-



IECEE CB Scheme

ID de înregistrare: NL-83812

	Tensiune nominală U_N	Curent nominal I_N	Secțiune transversală AWG	Secțiune transversală mm^2
	800 V	76 A	-	4 - 16



cULus Recognized

ID de înregistrare: E60425

	Tensiune nominală U_N	Curent nominal I_N	Secțiune transversală AWG	Secțiune transversală mm^2
Use group B				
	600 V	85 A	22 - 4	-
Use group C				
	600 V	85 A	22 - 4	-
Use group F				
	800 V	85 A	22 - 4	-

CCA

ID de înregistrare: NTR-NL 3072

	Tensiune nominală U_N	Curent nominal I_N	Secțiune transversală AWG	Secțiune transversală mm^2
	800 V	-	-	- 16



KEMA-KEUR

ID de înregistrare: 71-125614

	Tensiune nominală U_N	Curent nominal I_N	Secțiune transversală AWG	Secțiune transversală mm^2
	800 V	-	-	4 - 16

UK 16 N BU - Feed-through terminal block



3006056

<https://www.phoenixcontact.com/ro/produse/3006056>



ATEX

ID de înregistrare: KEMA98ATEX1786U



cUL Recognized

ID de înregistrare: E192998

	Tensiune nominală U_N	Curent nominal I_N	Secțiune transversală AWG	Secțiune transversală mm^2
	600 V	85 A	22 - 4	-



EAC Ex

ID de înregistrare: RU C-DE.HA91.B.00066



GL

ID de înregistrare: 98876-96 HH

	Tensiune nominală U_N	Curent nominal I_N	Secțiune transversală AWG	Secțiune transversală mm^2
EEx e II part certificate	690 V	74 A	-	- 16



IECEx

ID de înregistrare: IECEx KEM 06.0029U



UL Recognized

ID de înregistrare: E192998

	Tensiune nominală U_N	Curent nominal I_N	Secțiune transversală AWG	Secțiune transversală mm^2
	600 V	85 A	22 - 4	-



CCC

ID de înregistrare: 2020322313000623



DNV GL-EX

ID de înregistrare: TAE00003K6

	Tensiune nominală U_N	Curent nominal I_N	Secțiune transversală AWG	Secțiune transversală mm^2
EEx e II part certificate	440 V	32 A	-	- 2.5

cULus Recognized

UK 16 N BU - Feed-through terminal block



3006056

<https://www.phoenixcontact.com/ro/produse/3006056>

Clasificări

ECLASS

ECLASS-11.0	27141120
ECLASS-13.0	27250101

ETIM

ETIM 8.0	EC000897
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

UK 16 N BU - Feed-through terminal block



3006056

<https://www.phoenixcontact.com/ro/produse/3006056>

Environmental product compliance

EU RoHS

Îndeplinește cerințele conform directivei RoHS	Da, Nicio reglementare privind excepțiile
--	---

China RoHS

Environment friendly use period (EFUP)	EFUP-E
	Nu există substanțe periculoase peste valorile limită

EU REACH SVHC

Trimitere la substanța candidată REACH (nr. CAS)	Nicio substanță cu un procentaj masic mai mare de 0,1 %
--	---

UK 16 N BU - Feed-through terminal block



3006056

<https://www.phoenixcontact.com/ro/produse/3006056>

Accesorii



Indicație: Funcționarea produsului poate fi restricționată în cazul utilizării împreună cu unul din accesorii prezentate mai jos.

FBI 2-12 - Fixed bridge

0200075

<https://www.phoenixcontact.com/ro/produse/0200075>



Fixed bridge, pitch: 12 mm, number of positions: 2, length: 8 mm, color: silver

FBI 10-12 - Fixed bridge

0203454

<https://www.phoenixcontact.com/ro/produse/0203454>



Fixed bridge, pitch: 12 mm, number of positions: 10, length: 8 mm, color: silver



Max. current carrying capacity: 101 A

UK 16 N BU - Feed-through terminal block

3006056


<https://www.phoenixcontact.com/ro/produse/3006056>



EB 10-12 - Insertion bridge

3006137

<https://www.phoenixcontact.com/ro/produse/3006137>



Insertion bridge, pitch: 12 mm, number of positions: 10, color: gray

 Max. current carrying capacity: 70 A

D-UK 16 - End cover

3006027

<https://www.phoenixcontact.com/ro/produse/3006027>



End cover, depth: 42.7 mm, width: 1.5 mm, height: 42.5 mm, color: gray

UK 16 N BU - Feed-through terminal block

3006056

<https://www.phoenixcontact.com/ro/produse/3006056>



EA 7-WS - Cover

0800747

<https://www.phoenixcontact.com/ro/produse/0800747>

Single covers, for covering one terminal block, with black symbol (lightning flash)
snap fit, color: transparent/yellow



EA 7 - Cover

1024250

<https://www.phoenixcontact.com/ro/produse/1024250>

Cover, material: ABS, color: transparent



UK 16 N BU - Feed-through terminal block

3006056

<https://www.phoenixcontact.com/ro/produse/3006056>



TS-K - Separating plate

1302215

<https://www.phoenixcontact.com/ro/produse/1302215>



Separating plate, depth: 22 mm, width: 0.5 mm, height: 22 mm, color: gray

ATP-UK - Partition plate

3003224

<https://www.phoenixcontact.com/ro/produse/3003224>



Partition plate, depth: 45.7 mm, width: 1.5 mm, height: 56 mm, color: gray

UK 16 N BU - Feed-through terminal block

3006056

<https://www.phoenixcontact.com/ro/produse/3006056>

WS 4-12 - Warning label

0805328

<https://www.phoenixcontact.com/ro/produse/0805328>

Warning plate, with 2 plastic screws, across 4 terminal blocks, pitch 12 mm



WS 5-12 - Warning label

0805315

<https://www.phoenixcontact.com/ro/produse/0805315>

Warning plate, with 2 plastic screws, across 5 terminal blocks, pitch 12 mm



UK 16 N BU - Feed-through terminal block

3006056

<https://www.phoenixcontact.com/ro/produse/3006056>



NS 32 PERF 2000MM-VPE 10 - DIN rail perforated

1201002

<https://www.phoenixcontact.com/ro/produse/1201002>



DIN rail perforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, G profile, color: silver

NS 32 UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201015

<https://www.phoenixcontact.com/ro/produse/1201015>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, G profile, color: silver

UK 16 N BU - Feed-through terminal block

3006056

<https://www.phoenixcontact.com/ro/produse/3006056>



NS 35/ 7,5 PERF 2000MM - DIN rail perforated

0801733

<https://www.phoenixcontact.com/ro/produse/0801733>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

NS 35/ 7,5 UNPERF 2000MM - DIN rail, unperforated

0801681

<https://www.phoenixcontact.com/ro/produse/0801681>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

UK 16 N BU - Feed-through terminal block

3006056

<https://www.phoenixcontact.com/ro/produse/3006056>



NS 35/ 7,5 WH PERF 2000MM - DIN rail perforated

1204119

<https://www.phoenixcontact.com/ro/produse/1204119>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver

NS 35/ 7,5 WH UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1204122

<https://www.phoenixcontact.com/ro/produse/1204122>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver

UK 16 N BU - Feed-through terminal block

3006056

<https://www.phoenixcontact.com/ro/produse/3006056>



NS 35/ 7,5 AL UNPERF 2000MM - DIN rail, unperforated

0801704

<https://www.phoenixcontact.com/ro/produse/0801704>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Aluminum, uncoated, Standard profile, color: silver

NS 35/ 7,5 ZN PERF 2000MM - DIN rail perforated

1206421

<https://www.phoenixcontact.com/ro/produse/1206421>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, Standard profile, color: silver

UK 16 N BU - Feed-through terminal block

3006056

<https://www.phoenixcontact.com/ro/produse/3006056>



NS 35/ 7,5 ZN UNPERF 2000MM - DIN rail, unperforated

1206434

<https://www.phoenixcontact.com/ro/produse/1206434>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, Standard profile, color: silver

NS 35/ 7,5 CU UNPERF 2000MM-VPE 10 - DIN rail, unperforated

0801762

<https://www.phoenixcontact.com/ro/produse/0801762>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Copper, uncoated, Standard profile, color: copper-colored

UK 16 N BU - Feed-through terminal block

3006056

<https://www.phoenixcontact.com/ro/produse/3006056>



NS 35/ 7,5 CAP - End cap

1206560

<https://www.phoenixcontact.com/ro/produse/1206560>

DIN rail end piece, for DIN rail NS 35/7.5



NS 35/15 PERF 2000MM - DIN rail perforated

1201730

<https://www.phoenixcontact.com/ro/produse/1201730>



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

UK 16 N BU - Feed-through terminal block

3006056

<https://www.phoenixcontact.com/ro/produse/3006056>



NS 35/15 UNPERF 2000MM - DIN rail, unperforated

1201714

<https://www.phoenixcontact.com/ro/produse/1201714>



DIN rail, unperforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

NS 35/15 WH PERF 2000MM - DIN rail perforated

0806602

<https://www.phoenixcontact.com/ro/produse/0806602>



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: white

UK 16 N BU - Feed-through terminal block

3006056

<https://www.phoenixcontact.com/ro/produse/3006056>



NS 35/15 WH UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1204135

<https://www.phoenixcontact.com/ro/produse/1204135>



DIN rail, unperforated, Pack of 10 (20 m), similar to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver

NS 35/15 AL UNPERF 2000MM - DIN rail, unperforated

1201756

<https://www.phoenixcontact.com/ro/produse/1201756>



DIN rail, unperforated, similar to EN 60715, material: Aluminum, uncoated, Standard profile, color: silver

UK 16 N BU - Feed-through terminal block

3006056

<https://www.phoenixcontact.com/ro/produse/3006056>



NS 35/15 ZN PERF 2000MM - DIN rail perforated

1206599

<https://www.phoenixcontact.com/ro/produse/1206599>



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, Standard profile, color: silver

NS 35/15 ZN UNPERF 2000MM - DIN rail, unperforated

1206586

<https://www.phoenixcontact.com/ro/produse/1206586>



DIN rail, unperforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, Standard profile, color: silver

UK 16 N BU - Feed-through terminal block

3006056

<https://www.phoenixcontact.com/ro/produse/3006056>



NS 35/15 CU UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201895

<https://www.phoenixcontact.com/ro/produse/1201895>



DIN rail, unperforated, Pack of 10 (20 m), similar to EN 60715, material: Copper, uncoated, Standard profile, color: copper-colored

NS 35/15 CAP - End cap

1206573

<https://www.phoenixcontact.com/ro/produse/1206573>

DIN rail end piece, for DIN rail NS 35/15



UK 16 N BU - Feed-through terminal block

3006056

<https://www.phoenixcontact.com/ro/produse/3006056>



NS 35/15-2,3 UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201798

<https://www.phoenixcontact.com/ro/produse/1201798>




DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile 2.3 mm, color: silver

ZB 12:UNPRINTED - Zack marker strip

0812120

<https://www.phoenixcontact.com/ro/produse/0812120>



Zack marker strip, Strip, white, unlabeled, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 12.2 mm, lettering field size: 12 x 10.5 mm, Number of individual labels: 5

UK 16 N BU - Feed-through terminal block

3006056


<https://www.phoenixcontact.com/ro/produse/3006056>



ZB 12 CUS - Zack marker strip

0824942

<https://www.phoenixcontact.com/ro/produse/0824942>



Zack marker strip, can be ordered: Strip, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 12.2 mm, lettering field size: 10.5 x 12.15 mm, Number of individual labels: 5

ZB 12,LGS:L1-N,PE - Zack marker strip

0812146

<https://www.phoenixcontact.com/ro/produse/0812146>



Zack marker strip, Strip, white, labeled, printed horizontally: L1, L2, L3, N, PE, mounting type: snapped, for terminal block width: 12.2 mm, lettering field size: 10.5 x 12.15 mm, Number of individual labels: 5

UK 16 N BU - Feed-through terminal block



3006056

<https://www.phoenixcontact.com/ro/produse/3006056>

UC-TM 12 - Marker for terminal blocks

0819194

<https://www.phoenixcontact.com/ro/produse/0819194>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 12 mm, lettering field size: 11.45 x 10.5 mm, Number of individual labels: 40

UC-TM 12 CUS - Marker for terminal blocks

0824613

<https://www.phoenixcontact.com/ro/produse/0824613>



Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 12 mm, lettering field size: 11.45 x 10.5 mm, Number of individual labels: 40

UK 16 N BU - Feed-through terminal block

3006056

<https://www.phoenixcontact.com/ro/produse/3006056>



UCT-TM 12 - Marker for terminal blocks

0829144

<https://www.phoenixcontact.com/ro/produse/0829144>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: snapped, for terminal block width: 12 mm, lettering field size: 10.8 x 9.6 mm, Number of individual labels: 30

UCT-TM 12 CUS - Marker for terminal blocks

0829630

<https://www.phoenixcontact.com/ro/produse/0829630>



Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 12 mm, lettering field size: 10.8 x 9.6 mm, Number of individual labels: 30

UK 16 N BU - Feed-through terminal block

3006056

<https://www.phoenixcontact.com/ro/produse/3006056>



PS-MT - Test plug

0311647

<https://www.phoenixcontact.com/ro/produse/0311647>

Test plug, number of positions: 1, color: silver



PS-IH WH - Insulating sleeve

0311566

<https://www.phoenixcontact.com/ro/produse/0311566>

Insulating sleeve, number of positions: 1, color: white



UK 16 N BU - Feed-through terminal block

3006056

<https://www.phoenixcontact.com/ro/produse/3006056>



PS-IH RD - Insulating sleeve

0311579

<https://www.phoenixcontact.com/ro/produse/0311579>

Insulating sleeve, number of positions: 1, color: red



PS-IH BU - Insulating sleeve

0311582

<https://www.phoenixcontact.com/ro/produse/0311582>

Insulating sleeve, number of positions: 1, color: blue



UK 16 N BU - Feed-through terminal block

3006056

<https://www.phoenixcontact.com/ro/produse/3006056>



PS-IH YE - Insulating sleeve

0311595

<https://www.phoenixcontact.com/ro/produse/0311595>

Insulating sleeve, number of positions: 1, color: yellow



PS-IH GN - Insulating sleeve

0311605

<https://www.phoenixcontact.com/ro/produse/0311605>

Insulating sleeve, number of positions: 1, color: green



UK 16 N BU - Feed-through terminal block

3006056

<https://www.phoenixcontact.com/ro/produse/3006056>



PS-IH GY - Insulating sleeve

0311621

<https://www.phoenixcontact.com/ro/produse/0311621>

Insulating sleeve, number of positions: 1, color: gray



PS-IH BK - Insulating sleeve

0311634

<https://www.phoenixcontact.com/ro/produse/0311634>

Insulating sleeve, number of positions: 1, color: black



UK 16 N BU - Feed-through terminal block

3006056

<https://www.phoenixcontact.com/ro/produse/3006056>



PS-IH VT - Insulating sleeve

0311618

<https://www.phoenixcontact.com/ro/produse/0311618>

Insulating sleeve, number of positions: 1, color: violet



CLIPFIX 35 - End bracket

3022218

<https://www.phoenixcontact.com/ro/produse/3022218>

Quick mounting end clamp for NS 35/7,5 DIN rail or NS 35/15 DIN rail, with marking option, width: 9.5 mm, color: gray



UK 16 N BU - Feed-through terminal block

3006056

<https://www.phoenixcontact.com/ro/produse/3006056>



CLIPFIX 35-5 - End bracket

3022276

<https://www.phoenixcontact.com/ro/produse/3022276>




Quick mounting end clamp for NS 35/7,5 DIN rail or NS 35/15 DIN rail, with marking option, with parking option for FBS...5, FBS...6, KSS 5, KSS 6, width: 5.15 mm, color: gray

E/NS 35 N - End bracket

0800886

<https://www.phoenixcontact.com/ro/produse/0800886>



End clamp, width: 9.5 mm, color: gray

UK 16 N BU - Feed-through terminal block



3006056

<https://www.phoenixcontact.com/ro/produse/3006056>

E/UK - End bracket

1201442

<https://www.phoenixcontact.com/ro/produse/1201442>

End bracket, Mounting on a DIN rail NS 32 or NS 35, material: PA, color: gray



E/UK 1 - End bracket

1201413

<https://www.phoenixcontact.com/ro/produse/1201413>

End clamps, for supporting the ends of double-level and three-level terminal blocks, width: 10 mm, color: gray



UK 16 N BU - Feed-through terminal block

3006056

<https://www.phoenixcontact.com/ro/produse/3006056>



PSBJ 4/15/6 FARBLOS - Test plug strip

0303419

<https://www.phoenixcontact.com/ro/produse/0303419>

Test plug strip, number of positions: 1, color: transparent



PSBJ 4/15/6 WH - Test plug strip

0303312

<https://www.phoenixcontact.com/ro/produse/0303312>

Test plug strip, number of positions: 1, color: white



UK 16 N BU - Feed-through terminal block

3006056

<https://www.phoenixcontact.com/ro/produse/3006056>



PSBJ 4/15/6 RD - Test plug strip

0303325

<https://www.phoenixcontact.com/ro/produse/0303325>



Test plug strip, number of positions: 1, color: red

PSBJ 4/15/6 BU - Test plug strip

0303354

<https://www.phoenixcontact.com/ro/produse/0303354>



Test plug strip, number of positions: 1, color: blue

UK 16 N BU - Feed-through terminal block

3006056

<https://www.phoenixcontact.com/ro/produse/3006056>



PSBJ 4/15/6 YE - Test plug strip

0303367

<https://www.phoenixcontact.com/ro/produse/0303367>



Test plug strip, number of positions: 1, color: yellow

PSBJ 4/15/6 GN - Test plug strip

0303370

<https://www.phoenixcontact.com/ro/produse/0303370>



Test plug strip, number of positions: 1, color: green

UK 16 N BU - Feed-through terminal block

3006056

<https://www.phoenixcontact.com/ro/produse/3006056>



PSBJ 4/15/6 VT - Test plug strip

0303383

<https://www.phoenixcontact.com/ro/produse/0303383>



Test plug strip, number of positions: 1, color: violet

PSBJ 4/15/6 GY - Test plug strip

0303396

<https://www.phoenixcontact.com/ro/produse/0303396>



Test plug strip, number of positions: 1, color: gray

UK 16 N BU - Feed-through terminal block

3006056

<https://www.phoenixcontact.com/ro/produse/3006056>



PSBJ 4/15/6 BK - Test plug strip

0303406

<https://www.phoenixcontact.com/ro/produse/0303406>



Test plug strip, number of positions: 1, color: black

PSB 4/7/6 - Test plug strip

0303299

<https://www.phoenixcontact.com/ro/produse/0303299>



Test plug strip, number of positions: 1, color: silver

UK 16 N BU - Feed-through terminal block

3006056

<https://www.phoenixcontact.com/ro/produse/3006056>



SZS 1,0X4,0 VDE - Screwdriver

1205066

<https://www.phoenixcontact.com/ro/produse/1205066>



Screwdriver, slot-headed, VDE insulated, size: 1.0 x 4.0 x 100 mm, 2-component grip, with non-slip grip

Phoenix Contact 2024 © - Toate drepturile rezervate
<https://www.phoenixcontact.com>

PHOENIX CONTACT România
Splaiul Unirii 165 Timpuri Noi Square TNO1, Etaj 1
Bucuresti 030133
+40 21 350 88 12 - 3
sales.ro@phoenixcontact.com