



Filtru iesire dv/dt pentru unitate viteza variabila, IP20

VW3A5304

Principale

Tip produs sau componenta	Dv/dt filter
Compatibilitate gama	Altivar Process ATV900 Altivar Process ATV600 Easy Altivar 610 Altivar Machine ATV340
aplicatie specifica produsului	Filtru de iesire
[In] calibru	50 A
compatibilitate produs	ATV630 variable speed drive wall mount - 11 kW, 200...240 V ATV630 variable speed drive wall mount - 15 kW, 380...480 V ATV630 variable speed drive wall mount - 18,5 kW, 380...480 V ATV630 variable speed drive wall mount - 22 kW, 380...480 V ATV650 variable speed drive wall mount - 15 kW, 380...480 V ATV650 variable speed drive wall mount - 18,5 kW, 380...480 V ATV650 variable speed drive wall mount - 22 kW, 380...480 V ATV610 variable speed drive - 18,5 kW, 380...415 V ATV610 variable speed drive - 22 kW, 380...415 V ATV630 variable speed drive wall mount - 5,5 kW, 200...240 V ATV630 variable speed drive wall mount - 7,5 kW, 200...240 V ATV930 variable speed drive wall mount - 11 kW, 200...240 V ATV930 variable speed drive wall mount - 15 kW, 380...480 V ATV930 variable speed drive wall mount - 18,5 kW, 380...480 V ATV930 variable speed drive wall mount - 22 kW, 380...480 V ATV950 variable speed drive wall mount - 15 kW, 380...480 V ATV950 variable speed drive wall mount - 18,5 kW, 380...480 V ATV950 variable speed drive wall mount - 22 kW, 380...480 V
cantitate Incorporata	1
conexiune electrica	Bloc de conexiuni, capacitate conexiune: 16 mm² / AWG 6

Suplimentare

lungimea maxima a cablului motorului	500 m cablu neecranat 300 m cablu ecranat
dv/dt	3000 V/μs maxim la 200...240 V 3000 V/μs maxim la 380...480 V
pierderi termice	65 W la 4 kHz
maximum drive output frequency	100 Hz
temperatura ambientala de utilizare	-10...50 °C (fără declasarea curentului) 50...60 °C (cu diminuarea curentului cu 1.5% par °C)
altitudinea de functionare	0...1000 m fără declasarea curentului 1000...4000 m cu declasarea curentului cu 1 % pe 100 m
latime	300 mm
inaltime	560 mm
adancime	245 mm
greutate produs	18 kg

Declinare de responsabilitate: Această documentație nu se substituie și nu trebuie utilizată pentru stabilirea adecvării sau fiabilității acestor produse pentru aplicații utilizator

Mediu

grad de protectie IP	IP20 IP21 (with kit VW3A53903)
temperatura ambietala pentru depozitare	-40...70 °C

Unitati de ambalare

Unitate de masura pentru prima forma de impachetare	PCE
Numar unitati in prima forma de impachetare	1
Inaltime prima forma de impachetare	38,0 cm
Latime prima forma de impachetare	38,0 cm
Lungime prima forma de impachetare	60,0 cm
Greutate prima forma de impachetare	25,4 kg

Garanție contractuală

Garantie	18 months
----------	-----------



Environmental Data

Schneider Electric isi propune sa atinga nivelul Net Zero pana in 2050 prin parteneriate la nivelul lantului de aprovizionare, materiale cu impact mai redus si circularitate, prin campania „Use Better, Use Longer, Use Again” pentru a extinde durata de viata a produselor si reciclabilitatea.

[Environmental Data explicate >](#)

[Cum evaluam sustenabilitatea produselor >](#)

Use Better


Materiale si ambalare	
Pachet cu carton reciclabil	Nu
Ambalaj fara plastic	Nu
Directiva RoHS UE	Conformitate proactiva (Produs in afara domeniului de aplicare a EU RoHS)
Regulamentul REACH	Declaratia REACH

Use Again

Reambalare si refabricare	
Preluare la sfarsitul duratei de viata	No

Dimensions Drawings

Dimensions



Dimensions in mm

A	B	C	A1	B1	Ø
300	545	245	210	411	7

Dimensions in in.


A	B	C	A1	B1	Ø
11.8	21.5	9.6	8.3	16.2	0.28

Mounting and Clearance

Mounting and Clearance



(1) Filter



Connections and Schema

Recommended Schema



- (1) Drive
- (2) Filter