

EMT (15X4)R - Insert label

0817329

<https://www.phoenixcontact.com/ro/produse/0817329>



Vă rugăm să țineți cont de faptul că datele afișate în acest document PDF au fost generate din catalogul nostru online. Datele complete sunt disponibile în documentația pentru utilizator. În cazul descărcărilor, se aplică Termenii și condițiile generale de utilizare ale companiei noastre.



Insert label, Roll, white, unlabeled, can be labeled with: THERMOMARK E.300 (D)/600 (D), THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMaster 300/600, THERMOMARK X1.2, mounting type: insert, cable diameter range: 0.6 ... 50 mm, lettering field size: 15 x 4 mm, Number of individual labels: 7500

Avantajele dumneavoastră

- EMT ... insert labels for marking PATG and PATO marking sleeves for wire and cable identification
- Thanks to their special shape, EMT ... insert labels remain securely inside the collar once inserted
- Quick and inexpensive marking with THERMOMARK ... roll printers from Phoenix Contact
- When combined with the right ink ribbon, the marking is highly resistant to solvents and mechanical influences
- Marking service: Phoenix Contact can custom-mark all EMT ... markers according to your requirements

Date comerciale

Număr articol	0817329
Unitate de ambalare	1 Bucată
Cantitate minimă pentru comandă	1 Bucată
Cod produs	BG2211
Pagina de catalog	Pagina 229 (C-3-2019)
GTIN	4046356123419
Greutate pe bucată (inclusiv ambalajul)	473,08 g
Greutate pe bucată (fără ambalaj)	387,1 g
Cod tarifar vamal	39202021
Țara de origine	DE

EMT (15X4)R - Insert label

0817329

<https://www.phoenixcontact.com/ro/produse/0817329>



Date tehnice

Product properties

Product type	Conductor marking
Type	Roll

Data management status

Article revision	04
------------------	----

Marking

Number of individual labels	7500
Number of individual labels per row	6
Identification technology	Thermal transfer for rolls

Dimensions

Width	15 mm
Text field width	15.00 mm
Text field height	4.00 mm
Length	4 mm

Material specifications

RoHS compliant	yes
Foil strength	175 µm
Color	white
Material	Polyester
Components	free from silicone and halogen

Cable/line

External cable diameter	0.6 mm ... 50 mm
-------------------------	------------------

Environmental and real-life conditions

Test for substances that would hinder coating with paint or varnish

Result	Test passed
--------	-------------

Scratch test for the determining scratch resistance

Specification	DIN EN ISO 1518-1:2019-10 (following)
Requirements	≥ 5 N
Result	Test passed

Tesafilm test

Specification	DIN EN ISO 2409:2013 (following)
Result	Test passed

UV resistance

Specification	ISO 4892-2:2013-03 (following)
---------------	--------------------------------

EMT (15X4)R - Insert label



0817329

<https://www.phoenixcontact.com/ro/produse/0817329>

Result	Test passed
Test duration	96 h

Temperature resistance

Specification	ANSI/UL 969-2018:03 (following)
Test duration	240 h
Rating 200 °C (230 °C)	Test passed

Wipe resistance of inscriptions

Specification	DIN EN 61010-1 (VDE 0411-1):2011-07 DIN EN 62208 (VDE 0660-511):2012-06 (in parts)
Isopropyl [CAS No. 67-63-0]	Test passed
n-Hexane [CAS No. 110-54-3]	Test passed
Water + Petroleum ether [CAS No. 64742-82-1]	Test passed
Sodium hydroxide 0.1 mol/l [CAS No. 1310-73-2]	Test passed
Ethanol (99 %) [CAS No. 64-17-5]	Test passed
Specification	ISO 175:2010 (following)
Test duration	168 h
Sodium hydroxide 0.1 mol/l [CAS No. 1310-73-2]	Test passed
Diesel [CAS No. 68476-34-6]	Test passed
IRM 901	Test passed
IRM 902	Test passed

Testing in a condensation changing climate in the presence of sulfur dioxide

Specification	DIN 50018:2013-05
Result	Test passed
Climate level	AHT 1.0 S
Cycles	2

Salt spray test

Specification	DIN EN 60068-2-11:2000-02
Result	Test passed
Test duration	96 h

Ambient conditions

Ambient temperature (operation)	-40 °C ... 120 °C
Recommended storage conditions	23 °C / 50 % relative humidity
Recommended ambient temperature (storage/transport)	23 °C
Recommended humidity (storage/transport)	50 %
Shelf life	2 years

EMT (15X4)R - Insert label

0817329

<https://www.phoenixcontact.com/ro/produse/0817329>



Standards and regulations

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
-----------------	-----------------------------

Mounting

Mounting type	insert
---------------	--------

EMT (15X4)R - Insert label

0817329

<https://www.phoenixcontact.com/ro/produse/0817329>



Clasificări

ECLASS

ECLASS-11.0	27281106
ECLASS-12.0	27281106
ECLASS-13.0	27281106

ETIM

ETIM 9.0	EC001530
----------	----------

UNSPSC

UNSPSC 21.0	39131700
-------------	----------

EMT (15X4)R - Insert label

0817329

<https://www.phoenixcontact.com/ro/produse/0817329>



Environmental product compliance

EU RoHS

Îndeplinește cerințele conform directivei RoHS	Da, Nicio reglementare privind excepțiile
--	---

EU REACH SVHC

Trimitere la substanța candidată REACH (nr. CAS)	Nicio substanță cu un procentaj masic mai mare de 0,1 %
--	---

EMT (15X4)R - Insert label

0817329

<https://www.phoenixcontact.com/ro/produse/0817329>



Accesorii

THERMOMARK E.300 - Thermal transfer printer

1285306

<https://www.phoenixcontact.com/ro/produse/1285306>



Thermal transfer printer for printing all materials in roll format with a print resolution of 300 dpi. Suitable for long-term use in production and for large print volumes, as large rolls can also be processed.

THERMOMARK E.300 D - Thermal transfer printer

1004303

<https://www.phoenixcontact.com/ro/produse/1004303>



Thermal transfer printer with internal rewinder for printing all materials in roll format with a print resolution of 300 dpi. Suitable for long-term use in production and for large print volumes, as large rolls can also be processed.

EMT (15X4)R - Insert label

0817329

<https://www.phoenixcontact.com/ro/produse/0817329>



THERMOMARK E.600 - Thermal transfer printer

1285310

<https://www.phoenixcontact.com/ro/produse/1285310>



Thermal transfer printer for printing all materials in roll format with a print resolution of 600 dpi. Suitable for long-term use in production and for large print volumes, as large rolls can also be processed.

THERMOMARK E.600 D - Thermal transfer printer

1004304

<https://www.phoenixcontact.com/ro/produse/1004304>



Thermal transfer printer with internal rewinder for printing all materials in roll format with a print resolution of 600 dpi. Suitable for long-term use in production and for large print volumes, as large rolls can also be processed.

EMT (15X4)R - Insert label

0817329

<https://www.phoenixcontact.com/ro/produse/0817329>



THERMOMARK ROLL 2.0 - Thermal transfer printer

1085260

<https://www.phoenixcontact.com/ro/produse/1085260>



Thermal transfer printer for material off the roll, incl. Euro/US power cable and USB cable. Operating instructions printed in German and English. 1 roll of labels EML (20x8)R white = 1000 labels, ink ribbon = 50 m

THERMOMARK-RIBBON 110-WMTB HF - Ink ribbon

5148007

<https://www.phoenixcontact.com/ro/produse/5148007>



Ink ribbon, for roll printer for printing product groups WMTB HF..., WMS-2 HF..., TMT..., EMT..., EMLF..., PML-..., length: 300 m, roll length: 300 m, width: 110 mm, color: black

EMT (15X4)R - Insert label

0817329

<https://www.phoenixcontact.com/ro/produse/0817329>



PAB-SK 15 - Marker carriers

1013287

<https://www.phoenixcontact.com/ro/produse/1013287>

Marker carriers, transparent, unlabeled, mounting type: adhesive, lettering field size: 15 x 4 mm



PATG 0/15 - Conductor marker carrier

1013740

<https://www.phoenixcontact.com/ro/produse/1013740>

Conductor marker carrier, transparent, unlabeled, mounting type: slide-on, cable diameter range: 0.6 ... 1.2 mm, lettering field size: 15 x 4 mm



EMT (15X4)R - Insert label

0817329

<https://www.phoenixcontact.com/ro/produse/0817329>



PATG 1/15 - Conductor marker carrier

1013025

<https://www.phoenixcontact.com/ro/produse/1013025>



Conductor marker carrier, transparent, unlabeled, mounting type: slide-on, cable diameter range: 1.5 ... 2.5 mm, lettering field size: 15 x 4 mm

PATG 2/15 - Conductor marker carrier

1013038

<https://www.phoenixcontact.com/ro/produse/1013038>



Conductor marker carrier, transparent, unlabeled, mounting type: slide-on, cable diameter range: 2 ... 4 mm, lettering field size: 15 x 4 mm

EMT (15X4)R - Insert label

0817329

<https://www.phoenixcontact.com/ro/produse/0817329>



PATG 3/15 - Conductor marker carrier

1013041

<https://www.phoenixcontact.com/ro/produse/1013041>



Conductor marker carrier, transparent, unlabeled, mounting type: slide-on, cable diameter range: 4 ... 7 mm, lettering field size: 15 x 4 mm

PATG 4/15 - Conductor marker carrier

1013054

<https://www.phoenixcontact.com/ro/produse/1013054>



Conductor marker carrier, transparent, unlabeled, mounting type: slide-on, cable diameter range: 6 ... 10 mm, lettering field size: 15 x 4 mm

EMT (15X4)R - Insert label

0817329

<https://www.phoenixcontact.com/ro/produse/0817329>



PATG 5/15 - Conductor marker carrier

1013067

<https://www.phoenixcontact.com/ro/produse/1013067>



Conductor marker carrier, transparent, unlabeled, mounting type: slide-on, cable diameter range: 10 ... 14 mm, lettering field size: 15 x 4 mm

PATG 6/15 - Conductor marker carrier

1013070

<https://www.phoenixcontact.com/ro/produse/1013070>



Conductor marker carrier, transparent, unlabeled, mounting type: slide-on, cable diameter range: 14 ... 22 mm, lettering field size: 15 x 4 mm

EMT (15X4)R - Insert label

0817329

<https://www.phoenixcontact.com/ro/produse/0817329>



PATG 7/15 - Conductor marker carrier

1013083

<https://www.phoenixcontact.com/ro/produse/1013083>



Conductor marker carrier, transparent, unlabeled, mounting type: slide-on, cable diameter range: 22 ... 30 mm, lettering field size: 15 x 4 mm

PATG 8/15 - Conductor marker carrier

1013096

<https://www.phoenixcontact.com/ro/produse/1013096>



Conductor marker carrier, transparent, unlabeled, mounting type: slide-on, cable diameter range: 30 ... 35 mm, lettering field size: 15 x 4 mm

EMT (15X4)R - Insert label

0817329

<https://www.phoenixcontact.com/ro/produse/0817329>



PATG 9/15 - Conductor marker carrier

1013106

<https://www.phoenixcontact.com/ro/produse/1013106>

Conductor marker carrier, transparent, unlabeled, mounting type: slide-on, cable diameter range: 35 ... 45 mm, lettering field size: 15 x 4 mm



PATO 1/15 - Conductor marker carrier

1013119

<https://www.phoenixcontact.com/ro/produse/1013119>

Conductor marker carrier, transparent, unlabeled, mounting type: clip on, cable diameter range: 2 ... 3.5 mm, lettering field size: 4 x 15 mm



EMT (15X4)R - Insert label

0817329

<https://www.phoenixcontact.com/ro/produse/0817329>



PATO 2/15 - Conductor marker carrier

1013122

<https://www.phoenixcontact.com/ro/produse/1013122>



Conductor marker carrier, transparent, unlabeled, mounting type: clip on, cable diameter range: 2.8 ... 4.4 mm, lettering field size: 4 x 15 mm

PATO 3/15 - Conductor marker carrier

1013135

<https://www.phoenixcontact.com/ro/produse/1013135>



Conductor marker carrier, transparent, unlabeled, mounting type: clip on, cable diameter range: 4.4 ... 6.7 mm, lettering field size: 4 x 15 mm

EMT (15X4)R - Insert label

0817329

<https://www.phoenixcontact.com/ro/produse/0817329>



PATO 4/15 - Conductor marker carrier

1013148

<https://www.phoenixcontact.com/ro/produse/1013148>



Conductor marker carrier, transparent, unlabeled, mounting type: clip on, cable diameter range: 6.7 ... 10 mm, lettering field size: 4 x 15 mm

THERMOMARK ROLLMASTER 300 - Thermal transfer printer

0804501

<https://www.phoenixcontact.com/ro/produse/0804501>



Thermal transfer printer for material off the roll, incl. Euro/US power cable and USB cable. Support CD includes user manuals in several languages, links to firmware, drivers, and planning and marking software. Operating instructions printed in German and English. 1 roll of labels EML (20x8)R white = 1000 labels, ink ribbon = 50 m

EMT (15X4)R - Insert label

0817329

<https://www.phoenixcontact.com/ro/produse/0817329>



THERMOMARK ROLLMASTER 600 - Thermal transfer printer

0804663

<https://www.phoenixcontact.com/ro/produse/0804663>



Thermal transfer printer for material off the roll, incl. Euro/US power cable and USB cable. Support CD includes user manuals in several languages, links to firmware, drivers, and planning and marking software. Operating instructions printed in German and English. 1 roll of labels EML (20x8)R white = 1000 labels, ink ribbon = 50 m

THERMOMARK ROLL - Thermal transfer printer

5146477

<https://www.phoenixcontact.com/ro/produse/5146477>



Thermal transfer printer, 300 dpi, incl. European power cable, US power cable, and USB cable. DVD with CLIP PROJECT advanced planning and marking software, user manuals in various languages, Windows® printer driver, and firmware. German/English user manual in DIN A5 format, EML (20x8)R roll of labels, white, with 1000 labels, and ink ribbon: 50 m

EMT (15X4)R - Insert label

0817329

<https://www.phoenixcontact.com/ro/produse/0817329>



THERMOMARK X1.2 - Thermal transfer printer

5146231

<https://www.phoenixcontact.com/ro/produse/5146231>



Thermal transfer printer, weight: 10 kg, length: 0.446 m, width: 242 mm, height: 274 mm, color: gray

Phoenix Contact 2024 © - Toate drepturile rezervate

<https://www.phoenixcontact.com>

PHOENIX CONTACT România

Splaiul Unirii 165 Timpuri Noi Square TNO1, Etaj 1

Bucuresti 030133

+40 21 350 88 12 - 3

sales.ro@phoenixcontact.com