

# Product data sheet

Specifications



## APC NetShelter Basic Rack PDU, 1U, 20A, 120V, 10 NEMA 5-20 outlets, 5-20P inlet

AP9563

### Overview

Lead time Usually in Stock

### Main

Colour	Black
Product or component type	PDU
PDU type	Basic
Cord length	3.65 m
Number of cables	1
Provided equipment	Installation guide Rack mounting brackets

### Complementary

Input Voltage	100 V 120 V
Height	44 mm
Width	447 mm
Output Voltage	120 V
Depth	57 mm
Product weight	2.5 kg
Mounting location	Front Rear
Mounting preference	No preference
Input Plug Type	NEMA 5-20P
Mounting mode	Rack-mounted
Rack units	1U
Mounting position	Horizontal
[In] rated current	16 A
Input current limits	20 A
Load capacity	1920 VA
Network frequency	50/60 Hz
Outlet type and quantity	10 NEMA 5-20R

### Environment

<b>Product certifications</b>	cUL listed UL listed
<b>Ambient air temperature for operation</b>	-5...45 °C
<b>Relative humidity</b>	0...95 %
<b>Operating altitude</b>	0...10000 ft
<b>Ambient air temperature for storage</b>	-25...65 °C
<b>Storage Relative Humidity</b>	0...95 %
<b>Storage altitude</b>	0...15240 m

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	7 cm
<b>Package 1 Width</b>	22.9 cm
<b>Package 1 Length</b>	46.4 cm
<b>Package 1 Weight</b>	3.64 kg

## Contractual warranty

<b>Warranty (in months)</b>	24
-----------------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

Total lifecycle Carbon footprint	3 740 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	0.3 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.3 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	3 726 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.2 kg CO2 eq.
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

## Use Better



### Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	<a href="#">Compliant</a>
REACH Regulation	<a href="#">Free of Substances of Very High Concern above the threshold</a>
Halogen-free status	Product contains halogen above thresholds

## Use Longer



### Lifetime extension

Repair	No
--------	----

## Use Again



### Repack and remanufacture

Recyclability potential, in %	45
End of life manual availability	<a href="#">End of Life Information</a>
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins