



shunt release 110-415 V AC, for miniature circuit breaker 5SL4, 5SY, 5SP, RCBO 5SU1, FI 5SV (for 5SU1 handle coupler 5ST3805-1 is required)

Model	
product brand name	SENTRON
product designation	Shunt trip
design of the product	Mountable
design of the product factory mounted	No
electrical endurance (operating cycles) typical	10 000
Current	
operational current at DC rated value	0.05 A
Supply voltage	
operating voltage	
<ul style="list-style-type: none"> • rated value • at AC rated value minimum • at AC rated value maximum • at DC rated value minimum • at DC rated value maximum 	<ul style="list-style-type: none"> 230 V 110 V 415 V 110 V 220 V
protection class IP	IP20
Control current	
type of voltage of control voltage	AC/DC
Product details	
number of fault signal contacts	0
number of NC contacts	0
number of NO contacts	2
number of CO contacts	0
product extension can be mounted	Universal
product extension	shunt trip
Connections	
connectable conductor cross-section	
<ul style="list-style-type: none"> • minimum • maximum 	<ul style="list-style-type: none"> 0.5 mm² 2.5 mm²
AWG number as coded connectable conductor cross section	
<ul style="list-style-type: none"> • minimum • maximum 	<ul style="list-style-type: none"> 24 12
tightening torque with screw-type terminals	
<ul style="list-style-type: none"> • maximum 	0.8 N·m
Mechanical Design	
height	90 mm
width	18 mm
depth	70 mm

number of modular width units	1
Net Weight	98 g
Environmental conditions	
standard	IEC/EN60947-1
ambient temperature during operation	
• minimum	-25 °C
• maximum	55 °C
ambient temperature during storage minimum	-40 °C

Approvals Certificates

Environment	General Product Approval
-------------	--------------------------

[Environmental Con-
firmations](#)

[Environmental Con-
firmations](#)



[Confirmation](#)

[Miscellaneous](#)

General Product Ap- proval	other	Railway
-------------------------------	-------	---------



[Miscellaneous](#)

[Confirmation](#)

[Special Test Certifi-
cate](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5ST3030>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5ST3030>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5ST3030

CAX-Online-Generator




<https://www.siemens.com/cax>


Tender specifications

<https://www.siemens.com/specifications>

Characteristic curves

[https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP="HAUPT"></mmp_prod_no>](https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP=)





last modified:

11/24/2025 

