

# Fișă tehnică produs

Specificatii



## Intreruptor ComPacT NSX400F, 36 kA la 415 VAC, unitate de declansare MicroLogic 1.3 M 320A, 3 poli 3d

C40F31M320

### Principale

Gama	ComPacT noua generatie
nume produs	ComPacT NSX noua generatie
nume scurt al dispozitivului	NSX400F
Tip produs sau componenta	Disjunctori
aplicatie a dispozitivului	Motor protection
descriere poli	3P
descriere poli protejati	3d
[In] curent nominal	320 A la 65 °C
[Ue] tensiune nominala de functionare	690 V c.a. 50/60 Hz
Tip retea electrica	C.a.
frecventa retea electrica	50/60 Hz
adevare pentru izotatie	Da conformitate cu SR EN 60947-2
categorie de utilizare	Categoria A
[Icu] capacitate nominala limita de rupere la scurtcircuit	40 kA Icu la 220/240 V c.a. 50/60 Hz conformitate cu SR EN 60947-2 36 kA Icu la 380/415 V c.a. 50/60 Hz conformitate cu SR EN 60947-2 30 kA Icu la 440 V c.a. 50/60 Hz conformitate cu SR EN 60947-2 25 kA Icu la 500 V c.a. 50/60 Hz conformitate cu SR EN 60947-2 20 kA Icu la 525 V c.a. 50/60 Hz conformitate cu SR EN 60947-2 10 kA Icu la 660/690 V c.a. 50/60 Hz conformitate cu SR EN 60947-2 85 kA Icu la 240 V c.a. 50/60 Hz conformitate cu UL 60947-4-1 35 kA Icu la 480 V c.a. 50/60 Hz conformitate cu UL 60947-4-1 20 kA Icu la 600 V c.a. 50/60 Hz conformitate cu UL 60947-4-1
Nivel de performanta	F 36 kA 415 V c.a.
nume unitate de declansare	Micrologic 1.3 M
tehnologie unitate de declansare	Electronic
functii de protectie a unitatii de declansare	SI
tip de control	Comutare
Modul de montare a intreruptorului	Fix

### Suplimentare

[Ui] tensiune nominala de izotatie	800 V c.a. 50/60 Hz
[Uimp] tensiune nominala de tinere la impuls	8 kV

<b>[Ics] capacitate nominala de serviciu de rupere la scurtcircuit</b>	40 kA la 220/240 V c.a. 50/60 Hz conformitate cu SR EN 60947-2 36 kA la 380/415 V c.a. 50/60 Hz conformitate cu SR EN 60947-2 30 kA la 440 V c.a. 50/60 Hz conformitate cu SR EN 60947-2 25 kA la 500 V c.a. 50/60 Hz conformitate cu SR EN 60947-2 10 kA la 525 V c.a. 50/60 Hz conformitate cu SR EN 60947-2 10 kA la 660/690 V c.a. 50/60 Hz conformitate cu SR EN 60947-2
<b>durabilitate mecanica</b>	15000 cic
<b>durabilitate electrica</b>	12000 cic la 440 V In/2 6000 cic la 440 V In 6000 cic la 690 V In/2 3000 cic la 690 V In
<b>puterea disipata pe pol</b>	12,29 W
<b>suport de montare</b>	Placa dorsala
<b>pozitie de montare</b>	Orizantal si vertical Flat on the back
<b>conexiune superioara</b>	Fata
<b>conexiune inferioara</b>	Fata
<b>pasul de conectare</b>	45 mm
<b>tip de protectie</b>	S : for protectie la scurtcircuit pe perioada scurta I : for protectie instantanee la scurtcircuit
<b>gama uitatii de declansare</b>	320 A la 65 °C
<b>Reglarea preluarii protectiei de scurta durata tip Isd</b>	9 setari reglabile
<b>[Isd] interval de reglare a restabilirii pe termen scurt</b>	1600 A 1920 A 2440 A 2560 A 2880 A 3200 A 3520 A 3840 A 4160 A
<b>Reglarea intarzierii protectiei de scurta durata tip tsd</b>	Fix
<b>Ajustarea protectiei instantanee tip Ii</b>	Fix
<b>[Ii] interval de reglare a restabilirii instantanee</b>	4800 A
<b>protectie de scurgere la pamant</b>	Fara
<b>blocare ZSI cu selectare a zonei</b>	Fara
<b>Numar de sloturi pentru auxiliare electrice</b>	6 sloturi
<b>semnalizare locala</b>	LED intermitent (verde) for gata de functionare
<b>Latime</b>	140 mm
<b>Inaltime</b>	255 mm
<b>Adancime</b>	110 mm
<b>greutate produs</b>	6,05 kg
<b>Mediu</b>	
<b>standarde</b>	SR EN 60947-2
<b>categorie de supratensiune</b>	III
<b>clasa de protectie la electrocutare</b>	Clasa II pornit parte frontala
<b>grad de poluare</b>	3 conformitate cu SR EN 60664-1
<b>grad de protectie IP</b>	IP40 conforming to SR EN 60529

grad de protectie IK	IK07 conformitate cu IEC 62262
temperatura ambientala de functionare	-25...70 °C
temperatura ambietala pentru depozitare	-50...85 °C
umiditate relativa	0...95 %
altitudinea de functionare	0...2000 m fără declasare 2000 m...5000 m cu declasare

## Unitati de ambalare

Unitate de masura pentru prima forma de impachetare	PCE
Număr de produse în pachet	1
Inaltime prima forma de impachetare	15,0 cm
Latime prima forma de impachetare	15,5 cm
Lungime prima forma de impachetare	29,0 cm
Greutate colet(Lbs)	5,624 kg
Unitate de masura pentru a doua forma de impachetare	S04
Numar unitati in a doua forma de impachetare	2
Inaltime a doua forma de impachetare	30,0 cm
Latime a doua forma de impachetare	40,0 cm
Lungime a doua forma de impachetare	60,0 cm
Greutate a doua forma de impachetare	12,089 kg

## Garanție contractuală

Garantie (in luni)	18
--------------------	----

Schneider Electric isi propune sa atinga nivelul Net Zero pana in 2050 prin parteneriate la nivelul lantului de aprovizionare, materiale cu impact mai redus si circularitate, prin campania „Use Better, Use Longer, Use Again” pentru a extinde durata de viata a produselor si reciclabilitatea.

[Environmental Data explicate >](#)

[Cum evaluam sustenabilitatea produselor >](#)

### **Amprenta de mediu**

Amprenta de carbon totala pe durata de viata	247 kg CO2 eq.
Amprenta de carbon a fazei de fabricație [A1–A3]	35 kg CO2 eq.
Amprenta de carbon a fazei de distribuție [A4]	0.9 kg CO2 eq.
Amprenta de carbon a fazei de instalare [A5]	0.6 kg CO2 eq.
Amprenta de carbon a fazei de utilizare [B2, B3, B4, B6]	199 kg CO2 eq.
Amprenta de carbon a fazei de sfârșit de viață [C1–C4]	11 kg CO2 eq.
Raport de mediu	<a href="#">Profilul ambiental al produsului</a>

### **Use Better**

#### **Materiale si ambalare**

Pachet cu carton reciclabil	Da
Ambalaj fara plastic	Da
Numar SCIP	25ca3248-85d0-423a-a9d8-5b7aeb52e7b6
Directiva RoHS a UE	<a href="#">Conform Prin Scutire</a>
Regulamentul REACH	<a href="#">Referința conține SVHC peste prag</a>
Statut de indemn de halogen	Produsul conține halogeni peste pragurile admise
Nu contine PVC	Da
Nu contine silicon	Nu

### **Use Longer**

#### **Prelungire durata de viata**

Reparare	Nu
----------	----

### **Use Again**

#### **Reambalare si refabricare**

Potentialul de reciclabilitate, in %	56
Profil circularitate	<a href="#">Informatii privind sfarsitul duratei de viata</a>
Preluare la sfarsitul duratei de viata	Da
Eticheta WEEE	 În Uniunea Europeana, produsele trebuie reciclate respectand sistemul specific de colectare a deseurilor si nu trebuie sa ajunga in pubelele de colectare a deseurilor menajere.



Offer Marketing Illustration

Product benefits / Features

---



**ComPacT NSX**  
Range Accessories

Wireless auxiliary contact

Short terminal shield

Interphase barriers

Long terminal shield

Rotary handles

Standard auxiliary contact

MN undervoltage release

MX shunt release

Standard motor mechanism module

The image displays a collection of accessories for the ComPacT NSX circuit breaker range. At the top left, a green circular graphic partially overlaps a photograph of the main circuit breaker unit. Below this, the title 'ComPacT NSX Range Accessories' is presented in a bold, sans-serif font. The accessories are arranged in a 3x3 grid, each accompanied by a small product photograph and a descriptive label. The labels are: 'Wireless auxiliary contact' (a small green and white module), 'Short terminal shield' (a black rectangular shield), 'Interphase barriers' (a black vertical barrier), 'Long terminal shield' (a larger black rectangular shield), 'Rotary handles' (a black handle with a green knob), 'Standard auxiliary contact' (a white module with two terminals), 'MN undervoltage release' (a black module with a white label), 'MX shunt release' (a yellow and black module), and 'Standard motor mechanism module' (a black module with a silver handle).

Offer Marketing Illustration

Product benefits / Features

---



Offer Marketing Illustration

Product benefits / Features

---



### ComPacT NSX

#### Technical Benefits

- Nominal current: 16 to 630 A and 9 breaking capacities for the 2 sizes of circuit breakers
- 1, 2, 3, and 4 pole versions available
- Large range of electronic and thermal-magnetic protections
- Plug and ready wiring system and communicating accessories
- Integrated earth leakage protection via MicroLogic Vigi (earth leakage circuit breaker - ELCB)
- Advanced trip unit with integrated power metering: I, U, P, E, THD, f, CosPhi

Offer Marketing Illustration

Product benefits / Features

---

## ComPacT NSX Moulded Case Circuit Breaker



### Protection begins with prevention

Designed to prevent an electrical fire through integrated earth leakage protection with preventive maintenance thanks to its Everlink power connections.



### Maximize power availability

By providing corrective, preventive, and predictive maintenance for asset management thanks to our advanced MicroLogic trip units.



### Connectivity

Designed to connect to EcoStruxure Power, an IoT-connected architecture for improving every aspect of your power distribution system.

