

Pin busbar, 2-phase 10 mm<sup>2</sup>, 990mm, gray insulation can be cut for FI/LS 2P (3 MW)+AFDD



Figure similar

|  |                          |
|--|--------------------------|
| <b>product brand name</b>  | SENTRON                  |
| <b>product designation</b>                                       | Pin busbar               |
| <b>design of the product</b>                                     | 28x (1PH+HS)             |
| <b>design of the phase tap</b>                                   | L1/L2                    |
| <b>General technical data</b>                                    |                          |
| <b>compatibility</b>   | for MCBs 1P with UR/ST   |
| <b>design of pole</b>  | 2 poles                  |
| <b>phase number</b>  | 2                        |
| <b>operational current rated value</b>                           | 63 A                     |
| <b>suitability for interaction devices with auxiliary switch</b> | Yes                      |
| <b>suitability for interaction devices with N conductor</b>      | No                       |
| <b>color</b>   | light grey               |
| <b>Product details</b>   |                          |
| <b>product component with end cap</b>                            | No                       |
| <b>product feature attachable arc fault detection device</b>     | No                       |
| <b>product feature insulated</b>                                 | Yes                      |
| <b>product function</b>  |                          |
| • suitable for compact devices                                   | No                       |
| • can be cut   | Yes                      |
| <b>number of devices suitable for fitting</b>                    | 28                       |
| <b>type of electrical connection</b>                             | Pin                      |
| <b>Mechanical Design</b>   |                          |
| <b>module width</b>  | 18 mm                    |
| <b>height</b>  | 17 mm                    |
| <b>width</b>   | 14 mm                    |
| <b>length</b>  | 1 016 mm                 |
| <b>number of modular width units</b>                             | 56                       |
| <b>cross-section</b>   | 10 mm <sup>2</sup>       |
| <b>angle of the pin of busbar</b>                                | 0°                       |
| <b>Net Weight</b>  | 304 g                    |
| <b>Approvals Certificates</b>                                    |                          |
| <b>Environment</b>   | General Product Approval |

[Environmental Con-  
firmations](#)

[Environmental Con-  
firmations](#)

[Miscellaneous](#)



## Further information

### Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

### Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

### Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/lowvoltage/catalogs>

### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5ST3735-2>

### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5ST3735-2>

### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[https://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5ST3735-2](https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5ST3735-2)

### CAX-Online-Generator


<https://www.siemens.com/cax>


### Tender specifications

<https://www.siemens.com/specifications>

### Characteristic curves

[https://curves.simaris.siemens.com/curves/<mmp\\_prod\\_noCOMP="HAUPT"></mmp\\_prod\\_no>](https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP=)





---

last modified:

4/6/2026 

