

3-phase busbar with infeed left for 2 circuit breakers Size S00 and S0

<b>product brand name</b>	SIRIUS
<b>product category</b>	Infeed systems
<b>product designation</b>	3-phase busbar
<b>design of the product</b>	for 2 switches with infeed on the left
<b>product type designation</b>	3RV29
<b>suitability for use</b>	circuit-breakers 3RV2
<b>General technical data</b>	
<b>certificate of suitability</b>	CE / UL / CSA / CCC
<b>size of the circuit-breaker</b>	S00, S0
power loss [W] for rated value of the current at AC in hot operating state per pole	4.52 W
<b>type of calculation of power loss current-dependent</b>	quadratic
<b>surge voltage resistance rated value</b>	6 kV
protection class IP on the front according to IEC 60529	IP00
<b>thermal current</b>	63 A
<b>Substance Prohibition (Date)</b>	10/01/2009
<b>Net Weight</b>	427 g
<b>number of poles for main current circuit</b>	3
operating voltage at AC rated value	500 V
<b>operational current rated value</b>	63 A
<b>UL/CSA ratings</b>	
operating voltage at AC according to UL rated value	600 V
<b>Ambient conditions</b>	
ambient temperature during operation	-20 ... +60 °C
<b>Electrical Safety</b>	
<b>protection class IP on the front according to IEC 60529</b>	IP00; IP20 when using finely stranded conductor cross-section 6 mm <sup>2</sup> with end sleeve (with plastic collar) or conductor cross-section ≥ 10 mm <sup>2</sup> at the infeed terminal
<b>touch protection on the front according to IEC 60529</b>	finger-safe when using finely stranded conductor cross-section 6 mm <sup>2</sup> and end sleeve (with plastic collar) or conductor cross-section ≥ 10 mm <sup>2</sup> at the supply terminal
<b>Short-circuit protection</b>	
<b>short-circuit rating</b>	see table in the operating instructions
<b>Installation/ mounting/ dimensions</b>	
<b>mounting position</b>	any
<b>fastening method</b>	snap-on fastening on 35 mm DIN rail
<b>height</b>	129 mm
<b>width</b>	110 mm
<b>depth</b>	87 mm
<b>required spacing</b>	

- with side-by-side mounting
  - backwards 0 mm
  - upwards 10 mm
  - at the side 0 mm
- for grounded parts
  - backwards 0 mm
  - upwards 10 mm
  - at the side 0 mm
- for live parts
  - backwards 0 mm
  - upwards 10 mm
  - at the side 0 mm

#### Connections/ Terminals

type of electrical connection for main current circuit      spring-loaded terminals

#### Approvals Certificates

##### Environmental Product Declaration

- global warming potential [CO2 eq] / during manufacturing 2.47 kg
- global warming potential [CO2 eq] / during operation 68.6 kg
- global warming potential [CO2 eq] / after end of life -0.129 kg
- global warming potential [CO2 eq] / total 70.9 kg

##### Environment

##### General Product Approval

##### Maritime application

[Environmental Con-  
firmations](#)



##### Maritime application

##### other



[Confirmation](#)



##### other

[Miscellaneous](#)

#### Further information

##### Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

##### Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

##### Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

##### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RV2917-1A>

##### Cax online generator




<https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RV2917-1A>

##### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RV2917-1A>

##### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[https://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RV2917-1A&lang=en](https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RV2917-1A&lang=en)



last modified:

6/30/2025 