

Infeed terminal 25 mm² short for pin busbars



Model		
product brand name	SENTRON	
product designation	Busbar systems	
design of the product	Accessories	
Supply voltage		
operating voltage at AC rated value	690 V	
Connections		
tightening torque		
• minimum	1 N·m	
• maximum	2 N·m	
type of connectable conductor cross-sections for copper conductor stranded	6 - 25 mm ²	
Mechanical Design		
height	17.7 mm	
width	17 mm	
depth	16.8 mm	
length	38.2 mm	
Net Weight	12 g	
Approvals Certificates		
Environment	General Product Approval	other

[Environmental Confirmations](#)

[Environmental Confirmations](#)

[Confirmation](#)

[Miscellaneous](#)



other

[Confirmation](#)

Further information

Information on the packaging
<https://support.industry.siemens.com/cs/ww/en/view/109813875>
 Information for data generation and storage
<https://support.industry.siemens.com/cs/ww/en/view/109995012>
 Information- and Downloadcenter (Catalogs, Brochures,...)
<https://www.siemens.com/lowvoltage/catalogs>
 Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5ST3768>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5ST3768>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5ST3768

CAX-Online-Generator

<https://www.siemens.com/cax>

Tender specifications

<https://www.siemens.com/specifications>

Characteristic curves

[https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP="HAUPT"></mmp_prod_no>](https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP=)

last modified:

4/11/2025 

