



Product features and key data

Luminaire colour	RAL9016 Traffic white
Wiring	7LV
Ingress Protection (IP) rating	IP20
Protection class	I
Net length	2.212,50 mm
Net width	63 mm
Net height	41,40 mm
Weight	3,0 kg

Available accessories

Material	Description
 07690TL Luminaire Support Bracket 2196600	Luminaire support bracket (1 pair), sheet steel, galvanised.
 E04 Kette glzvz (20m) 2343400	Chain bright zinc-plated (20 m).
 A01SX/1500 2230700	Wire suspension with fixing clip.
 A01KX/1500 2230100	Chain suspension consisting of link chain, bright zinc-plated, length 1500 mm, with turnbuckle and suspension clamp E03KX.
 A01DSX/1500 2229600	Decorative wire suspension with suspension clip.
 E03KX 2342800	Suspension clamp for chain mounting.
 E03SX 2343200	Suspension clamp for fixing to steel wire.
 07690LHI Cable Holder 10pcs 2195300	Cable restraint for cable routing in trunking with through-wiring.
 D01X 2321200	Fixing clip for direct ceiling surface-mounting.
 07690LHA Cable Holder 2195200	Outer cable restraint.

	07690SK Female Connector 2195900	Female connector for ribbon cable wiring. 7-pole, for electrical contact of ribbon cables 07690/5LV/46m and 07690/7LV/46m.
	07690VV Wiring Connector 2197300	Wiring connector, 7-pole plug socket pair
	07690TO 2196700	Female connectors, for electrical contact of single wires. 5-pole, for tool-free electrical connection between single-core cables subsequently integrated into trunking and gear trays
	E03SKX 6188900	Suspension clamp for chain mounting. Height-adjustable, flexible version.
	A01SXVA 6817000	1 piece. Wire suspension with fixing clip
	07650 Flex con-cab 3pol 6912100	Flexible connection cable for E-Line LED gear tray.
	07650 Flex con-cab 5pol 6912200	Flexible connection cable for E-Line LED gear tray.
	07650 Ks 01 7260500	End cap for terminating an E-Line 7651 continuous line application IP20.
	A01DSX/3000 7234300	1 piece. Decorative wire suspension with suspension clip. 3000 mm
	A01DSX/5000 7234400	1 piece. Decorative wire suspension with suspension clip, 5000 mm
	A01SKX/1500 7234500	1 piece. {Reference (Object) not found: tb1848822583891}
	A01SX/5000 7234600	1 piece. Wire suspension with fixing clip, 5000 mm
	07650 BL L225 01 7258700	Blank cover for E-Line 7651 continuous line system. PVC. Colour white (similar to RAL 9016). Length 2211,5 mm.
	07650 BL L187 01 7258800	Blank cover for E-Line 7651 continuous line system. PVC. Colour white (similar to RAL 9016). Length 1843 mm.
	07650 BL L150 01 7258900	Blank cover for E-Line 7651 continuous line system. PVC. Colour white (similar to RAL 9016). Length 1474 mm.
	07650 BL L112 01 7259000	Blank cover for E-Line 7651 continuous line system. PVC. Colour white (similar to RAL 9016). Length 1105,5 mm.
	07650 BL L75 01 7259100	Blank cover for E-Line 7651 continuous line system. PVC. Colour white (similar to RAL 9016). Length 736,5 mm.
	07650 BL L37 01 7259200	Blank cover for E-Line 7651 continuous line system. PVC. Colour white (similar to RAL 9016). Length 368 mm.
	07650 BL-M L112 01 7219400	Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour white (similar to RAL 9016). Length 1105,5 mm.
	07650 BL-M L37 01 7219700	Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour white (similar to RAL 9016). Length 368 mm.

	07650 BL-M L75 01 7220000	Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour white (similar to RAL 9016). Length 737 mm.
	07650 BL-M L187 01 7220300	Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour white (similar to RAL 9016). Length 1842,5 mm.
	07650 BL-M L150 01 7220600	Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour white (similar to RAL 9016). Length 1474 mm.
	07650 BL-M L225 01 7223200	Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour white (similar to RAL 9016). Length 2211 mm.
	07650 BL-M 5-pol L37 01 7225000	Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour white (similar to RAL 9016). Length 368 mm.
	07650 BL-M 5-pol L75 01 7225100	Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour white (similar to RAL 9016). Length 737 mm.
	07650 BL-M 5-pol L112 01 7225200	Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour white (similar to RAL 9016). Length 1105,5 mm.
	07650 BL-M 5-pol L150 01 7225300	Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour white (similar to RAL 9016). Length 1474 mm.
	07650 BL-M 5-pol L187 01 7225400	Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour white (similar to RAL 9016). Length 1842,5 mm.
	07650 BL-M 5-pol L225 01 7225500	Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour white (similar to RAL 9016). Length 2211 mm.
	07650 L150 7+7LV E 150 01 7274200	Trunking for E-Line 7651 continuous line single luminaires or continuous line terminations. Length of the trunking: 1475 mm. Surface coated white. With 7-core through-wiring for segmenting circuits and supplementary 7-core through-wiring for additional emergency light or light management uses.
	07650 L-Connector 01 7508600	Connector for L-shaped continuous line applications. Colour white (similar to RAL 9016). Dimensions (L x W): 362 mm x 362 mm.
	07650 T-Connector 01 7508900	Connector for T-shaped continuous line applications. Colour white (similar to RAL 9016). Dimensions (L x W): 659 mm x 362 mm.
	07650 X-Connector 01 7509200	Connector for X-shaped continuous line applications. Colour white (similar to RAL 9016). Dimensions (L x W): 659 mm x 659 mm.
	07650 Connector 1-pol 7688200	Plug, 1-pole as spare or for expansion. Colour white.
	07650 BL L5 01 7688300	Blank cover for E-Line 7651 continuous line system. PVC. Colour white (similar to RAL 9016). Length 55 mm.
	A01DSXOE/1500 7694900	Decorative wire suspension with stainless steel suspension clip, galvanised steel wire (Ø 1.5 mm) and eyelet. For E-Line 7651 continuous line system.
	A01DSXOE/3000 7695000	Decorative wire suspension with stainless steel suspension clip, galvanised steel wire (Ø 1.5 mm) and eyelet. For E-Line 7651 continuous line system.
	A01DSXOE/6000 7695100	Decorative wire suspension with stainless steel suspension clip, galvanised steel wire (Ø 1.5 mm) and eyelet. For E-Line 7651 continuous line system.
	07650IP BL-M 5-pol L37 01 7784600	Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour white (similar to RAL 9016). Length 368 mm.

	07650IP BL-M 5-pol L75 01 7785900	Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour white (similar to RAL 9016). Length 737 mm.
	07650IP BL-M 5-pol L112 01 7786000	Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour white (similar to RAL 9016). Length 1106 mm.
	07650IP BL-M 5-pol L150 01 7786100	Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour white (similar to RAL 9016). Length 1474 mm.
	07650IP BL-M 5-pol L187 01 7786200	Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour white (similar to RAL 9016). Length 1843 mm.
	07650IP BL-M 5-pol L225 01 7786300	Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour white (similar to RAL 9016). Length 2211 mm.
	07650IP BL-M L112 01 7787600	Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour white (similar to RAL 9016). Length 1106 mm.
	07650IP BL-M L37 01 7787900	Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour white (similar to RAL 9016). Length 368 mm.
	07650IP BL-M L75 01 7788200	Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour white (similar to RAL 9016). Length 737 mm.
	07650IP BL-M L187 01 7788500	Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour white (similar to RAL 9016). Length 1843 mm.
	07650IP BL-M L150 01 7788800	Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour white (similar to RAL 9016). Length 1474 mm.
	07650IP BL-M L225 01 7789200	Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour white (similar to RAL 9016). Length 2211 mm.
	07650IP Ks 01 7789600	End cap for terminating an E-Line 7651 continuous line application IP50.
	07650IP BL L112 01 7712000	Blank cover for E-Line 7651 continuous line system. PVC. Colour white (similar to RAL 9016). Length 1105,4 mm.
	07650IP BL L112 03 7712100	Blank cover for E-Line 7651 continuous line system. PVC. Colour silver gray (similar to RAL 9006). Length 1105,4 mm.
	07650IP BL L150 01 7712300	Blank cover for E-Line 7651 continuous line system. PVC. Colour white (similar to RAL 9016). Length 1474 mm.
	07650IP BL L187 01 7712600	Blank cover for E-Line 7651 continuous line system. PVC. Colour white (similar to RAL 9016). Length 1842,8 mm.
	07650IP BL L225 01 7712900	Blank cover for E-Line 7651 continuous line system. PVC. Colour white (similar to RAL 9016). Length 2211,2 mm.
	07650IP BL L37 01 7713200	Blank cover for E-Line 7651 continuous line system. PVC. Colour white (similar to RAL 9016). Length 368 mm.
	07650IP BL L75 01 7713500	Blank cover for E-Line 7651 continuous line system. PVC. Colour white (similar to RAL 9016). Length 736,5 mm.
	07650IP BL L5 01 8362500	Blank cover for E-Line 7651 continuous line system. PVC. Colour white (similar to RAL 9016). Length 54,5 mm.


07650IP BL L153 01
 8362800

Blank cover for E-Line 7651 continuous line system. PVC. Colour white (similar to RAL 9016). Length 1530 mm.


A01SX/3000
 3664499

1 piece. Wire suspension with fixing clip, 3000 mm


D01X m Caddy-Clip 01
 4068899

Fixing clamp with caddy clip for quick mounting on suitable profile steel without drilling. The quantity and mounting positions depend on the system ceiling, luminaire load and luminaire arrangement. Observe the specifications of the ceiling manufacturer.


D01X m Caddy-Clip
 4068999

Fixing clamp with caddy clip for quick mounting on suitable profile steel without drilling. The quantity and mounting positions depend on the system ceiling, luminaire load and luminaire arrangement. Observe the specifications of the ceiling manufacturer.


07690VS 2,5² L100
 6822100

Connection cable with 7-pole plug, 100 mm.


07690/1LV 2.5² L300
 6822200

Connection cable for central infeed of the E-Line trunking profiles.


07690VS
 6822300

Plug for power feed, 7-pole, fixed.

Offer text

Trunking for E-Line 7651 continuous line applications. To simplify installation, a pre-assembled continuous line coupler is included in the scope of delivery for connection to a further trunking unit. Length of the trunking: 2212,5 mm. With 7-conductor through-wiring. Cable cross-section 2.5 mm². With 1 female connector for tool-free, electrical connection of the gear trays. With 7-pole plug/socket pair for rapid electrical connection and termination at ends with protection against accidental contact. The heat-resistant through-wiring is factory-completed with all necessary components. All connections are designed for fast connection and are with reverse polarity protection. The electrical feed can be made without accessories through an upper knockout (M20/PG13.5). The trunking body is made of hot-dip galvanised sheet steel. Surface coated white.