



DELTA connection socket Universal connection unit 2x 8-pole RJ45 Cat. 6 E  
Compact technology FLEX LSA-plus terminals Screw mounting shielded

| Model                           |                          |       |
|---------------------------------|--------------------------|-------|
| product brand name              | DELTA                    |       |
| product designation             | Connection socket        |       |
| design of the product           | Communication            |       |
| type of composition             | basic element            |       |
| General technical data          |                          |       |
| mounting type                   | flush mounting           |       |
| surface processing              | others                   |       |
| product feature printed marking | No                       |       |
| material                        | others                   |       |
| Protection class                |                          |       |
| protection class IP             | IP20                     |       |
| Suitability                     |                          |       |
| suitability for use             | UAE/IAE                  |       |
| Appearance                      |                          |       |
| appearance                      | not applicable           |       |
| color                           | miscellaneous            |       |
| Product details                 |                          |       |
| product feature luster terminal | No                       |       |
| product feature dust cover      | No                       |       |
| product component               |                          |       |
| • labeling field                | No                       |       |
| • hinged lid                    | No                       |       |
| • strain relief                 | No                       |       |
| product feature halogen-free    | Yes                      |       |
| product feature transparent     | No                       |       |
| Mechanical Design               |                          |       |
| height                          | 70 mm                    |       |
| depth                           | 40 mm                    |       |
| fastening method                | screw mounting           |       |
| Net Weight                      | 152 g                    |       |
| material                        | metal                    |       |
| Approvals Certificates          |                          |       |
| Environment                     | General Product Approval | other |

[Environmental Conformations](#)

[Confirmation](#)



[Confirmation](#)

## Further information

### Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

### Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

### Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/lowvoltage/catalogs>

### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5TG2026-2>

### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5TG2026-2>

### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[https://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5TG2026-2](https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5TG2026-2)

### CAX-Online-Generator

<https://www.siemens.com/cax>

### Tender specifications

<https://www.siemens.com/specifications>

### Characteristic curves

[https://curves.simaris.siemens.com/curves/<mmp\\_prod\\_noCOMP="HAUPT"></mmp\\_prod\\_no>](https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP=)

---

last modified:

8/15/2025 

