


UK 4 - Feed-through terminal block



3003017

<https://www.phoenixcontact.com/ro/produse/3003017>

Vă rugăm să țineți cont de faptul că datele afișate în acest document PDF au fost generate din catalogul nostru online. Datele complete sunt disponibile în documentația pentru utilizator. În cazul descărcărilor, se aplică Termenii și condițiile generale de utilizare ale companiei noastre.



Feed-through terminal block, nom. voltage: 800 V, nominal current: 32 A, number of connections: 2, number of positions: 1, connection method: Screw connection, cross section: 0.2 mm² - 4 mm², mounting type: NS 35/7,5, NS 35/15, NS 32, color: gray

Date comerciale

Număr articol	3003017
Unitate de ambalare	50 Bucată
Cantitate minimă pentru comandă	1 Bucată
Cod produs	BE1211
GTIN	4017918090418
Greutate pe bucată (inclusiv ambalajul)	10,395 g
Greutate pe bucată (fără ambalaj)	10,001 g
Cod tarifar vamal	85369010
Țara de origine	DE

UK 4 - Feed-through terminal block



3003017

<https://www.phoenixcontact.com/ro/produse/3003017>

Date tehnice

Product properties

Product type	Feed-through terminal block
Number of positions	1
Number of connections	2
Number of rows	1
Potentials	1

Data management status

Article revision	01
------------------	----

Insulation characteristics

Overvoltage category	III
Degree of pollution	3

Electrical properties

Rated surge voltage	8 kV
Maximum power dissipation for nominal condition	0 W

Connection data

Number of connections per level	2
---------------------------------	---

Level 1 above 1 below 1

Screw thread	M3
Tightening torque	0.6 ... 0.8 Nm
Stripping length	8 mm
Connection in acc. with standard	IEC / EN
Conductor cross section rigid	0.2 mm ² ... 4 mm ²
Cross section AWG	24 ... 12 (converted acc. to IEC)
Conductor cross section flexible	0.2 mm ² ... 4 mm ²
Conductor cross section, flexible [AWG]	24 ... 12 (converted acc. to IEC)
Conductor cross-section flexible (ferrule without plastic sleeve)	0.25 mm ² ... 4 mm ²
Flexible conductor cross section (ferrule with plastic sleeve)	0.25 mm ² ... 2.5 mm ²
2 conductors with same cross section, solid	0.2 mm ² ... 1.5 mm ²
2 conductors with same cross section, flexible	0.2 mm ² ... 1.5 mm ²
2 conductors with same cross section, flexible, with ferrule without plastic sleeve	0.25 mm ² ... 1.5 mm ²
2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve	0.5 mm ² ... 1.5 mm ²
Nominal current	32 A
Nominal voltage	800 V
Connection in acc. with standard	UL
Cross section AWG	28 ... 12 (converted acc. to IEC)
Nominal current	20 A

UK 4 - Feed-through terminal block



3003017

<https://www.phoenixcontact.com/ro/produse/3003017>

Nominal voltage	600 V
Connection in acc. with standard	CSA
Cross section AWG	28 ... 12 (converted acc. to IEC)
Nominal current	25 A
Nominal voltage	600 V

Dimensions

Width	6.2 mm
End cover width	1.8 mm
Height	42.5 mm
Depth on NS 32	52 mm
Depth on NS 35/7,5	47 mm
Depth on NS 35/15	54.5 mm

Material specifications

Color	gray
Flammability rating according to UL 94	V2
Insulating material group	I
Insulating material	PA
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21))	125 °C
Relative insulation material temperature index (Elec., UL 746 B)	125 °C

Electrical tests

Surge voltage test

Test voltage setpoint	9.8 kV
Result	Test passed

Temperature-rise test

Requirement temperature-rise test	Increase in temperature ≤ 45 K
Result	Test passed
Short-time withstand current 4 mm ²	0.48 kA
Result	Test passed

Power-frequency withstand voltage

Test voltage setpoint	2 kV
Result	Test passed

Mechanical properties

Mechanical data

Open side panel	Yes
-----------------	-----

Mechanical tests

Mechanical strength

UK 4 - Feed-through terminal block



3003017

<https://www.phoenixcontact.com/ro/produse/3003017>

Result	Test passed
--------	-------------

Attachment on the carrier

DIN rail/fixing support	NS 32/NS 35
Test force setpoint	1 N
Result	Test passed

Test for conductor damage and slackening

Rotation speed	10 rpm
Revolutions	135
Conductor cross section/weight	0.2 mm ² / 0.2 kg
	4 mm ² / 0.9 kg
Result	Test passed

Environmental and real-life conditions

Needle-flame test

Time of exposure	30 s
Result	Test passed

Ambient conditions

Ambient temperature (operation)	-60 °C ... 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.)
Ambient temperature (storage/transport)	-25 °C ... 60 °C (for a short time, no longer than 24 h, -60°C to +70°C)
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C
Permissible humidity (operation)	20 % ... 90 %
Permissible humidity (storage/transport)	30 % ... 70 %

Standards and regulations

Connection in acc. with standard	IEC / EN
	UL
	CSA

Mounting

Mounting type	NS 35/7,5
	NS 35/15
	NS 32

UK 4 - Feed-through terminal block

3003017

<https://www.phoenixcontact.com/ro/produse/3003017>



Desene

Circuit diagram



UK 4 - Feed-through terminal block



3003017

<https://www.phoenixcontact.com/ro/produse/3003017>

Aprobări

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/ro/produse/3003017>

DNV

ID de înregistrare: TAE00001CT



CSA

ID de înregistrare: 13631

	Tensiune nominală U_N	Curent nominal I_N	Secțiune transversală AWG	Secțiune transversală mm^2
	600 V	25 A	28 - 12	-



EAC

ID de înregistrare: RU C-DE.BL08.B.00534



cULus Recognized

ID de înregistrare: E60425

	Tensiune nominală U_N	Curent nominal I_N	Secțiune transversală AWG	Secțiune transversală mm^2
Use group B				
	600 V	20 A	28 - 12	-
Multi-conductor connection	600 V	20 A	- 14	-
Use group C				
	600 V	20 A	28 - 12	-
Multi-conductor connection	600 V	20 A	- 14	-

ClassNK

NK

ID de înregistrare: 09 ME 142

UK 4 - Feed-through terminal block



3003017

<https://www.phoenixcontact.com/ro/produse/3003017>

Clasificări

ECLASS

ECLASS-11.0	27141120
ECLASS-13.0	27250101

ETIM

ETIM 8.0	EC000897
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

UK 4 - Feed-through terminal block



3003017

<https://www.phoenixcontact.com/ro/produse/3003017>

Environmental product compliance

EU RoHS

Îndeplinește cerințele conform directivei RoHS	Da, Nicio reglementare privind excepțiile
--	---

China RoHS

Environment friendly use period (EFUP)	EFUP-E
	Nu există substanțe periculoase peste valorile limită

EU REACH SVHC

Trimitere la substanța candidată REACH (nr. CAS)	Nicio substanță cu un procentaj masic mai mare de 0,1 %
--	---

UK 4 - Feed-through terminal block

3003017

<https://www.phoenixcontact.com/ro/produse/3003017>



Accesorii

IS-K 4 - Bridge bar isolator

1302338

<https://www.phoenixcontact.com/ro/produse/1302338>



Bridge bar isolator, color: gray

ISSBI 10- 6 - Bridge

0301505

<https://www.phoenixcontact.com/ro/produse/0301505>



Bridge, pitch: 6 mm, number of positions: 10, color: silver

UK 4 - Feed-through terminal block

3003017

<https://www.phoenixcontact.com/ro/produse/3003017>



LB 10-6 GY - Bridge

0202358

<https://www.phoenixcontact.com/ro/produse/0202358>

Bridge, pitch: 6 mm, number of positions: 10, color: gray



LB 100-6 GY - Bridge

0202345

<https://www.phoenixcontact.com/ro/produse/0202345>

Bridge, pitch: 6 mm, number of positions: 100, color: gray



UK 4 - Feed-through terminal block

3003017

<https://www.phoenixcontact.com/ro/produse/3003017>



KB- 6 - Chain bridge

0201472

<https://www.phoenixcontact.com/ro/produse/0201472>



Chain bridge, pitch: 6 mm, number of positions: 1, color: silver

FBI 10- 6 - Fixed bridge

0203250

<https://www.phoenixcontact.com/ro/produse/0203250>



Fixed bridge, pitch: 6.2 mm, number of positions: 10, color: silver

UK 4 - Feed-through terminal block

3003017

<https://www.phoenixcontact.com/ro/produse/3003017>



FBI 100- 6 - Fixed bridge

0201650

<https://www.phoenixcontact.com/ro/produse/0201650>



Fixed bridge, pitch: 6.2 mm, number of positions: 100, color: silver

FBI 20- 6 - Fixed bridge

0201867

<https://www.phoenixcontact.com/ro/produse/0201867>



Fixed bridge, pitch: 6.2 mm, number of positions: 20, color: silver

UK 4 - Feed-through terminal block

3003017

<https://www.phoenixcontact.com/ro/produse/3003017>



EB 3- 6/ST - Insertion bridge

5020807

<https://www.phoenixcontact.com/ro/produse/5020807>

Insertion bridge, pitch: 6 mm, number of positions: 3, color: gray



EB 6- 6/DR - Insertion bridge

5020755

<https://www.phoenixcontact.com/ro/produse/5020755>

Insertion bridge, pitch: 6.2 mm, number of positions: 6, color: gray



UK 4 - Feed-through terminal block

3003017

<https://www.phoenixcontact.com/ro/produse/3003017>



EB 2- 6 - Insertion bridge

0201155

<https://www.phoenixcontact.com/ro/produse/0201155>

Insertion bridge, pitch: 6.2 mm, number of positions: 2, color: gray



EB 3- 6 - Insertion bridge

0201142

<https://www.phoenixcontact.com/ro/produse/0201142>

Insertion bridge, pitch: 6.2 mm, number of positions: 3, color: gray



UK 4 - Feed-through terminal block

3003017


<https://www.phoenixcontact.com/ro/produse/3003017>



EB 10- 6 - Insertion bridge

0201139

<https://www.phoenixcontact.com/ro/produse/0201139>



Insertion bridge, pitch: 6.2 mm, number of positions: 10, color: gray

USBR 2-7 - Switching jumper

2303239

<https://www.phoenixcontact.com/ro/produse/2303239>



Switching jumper, pitch: 7 mm, number of positions: 2, color: silver

UK 4 - Feed-through terminal block

3003017

<https://www.phoenixcontact.com/ro/produse/3003017>



USBRJ 2-7 - Switching jumper

2305538

<https://www.phoenixcontact.com/ro/produse/2305538>

Switching jumper, number of positions: 2, color: silver



WS 5- 6 - Warning label

1004403

<https://www.phoenixcontact.com/ro/produse/1004403>

Warning plate, with 2 plastic screws, across 5 terminal blocks, pitch 6 mm



UK 4 - Feed-through terminal block

3003017

<https://www.phoenixcontact.com/ro/produse/3003017>



WS 4- 6 - Warning label

1004209

<https://www.phoenixcontact.com/ro/produse/1004209>

Warning plate, with 2 plastic screws, across 4 terminal blocks, pitch 6 mm



WS 3- 6 - Warning label

1004115

<https://www.phoenixcontact.com/ro/produse/1004115>

Warning plate, with 2 plastic screws, across 3 terminal blocks, pitch 6 mm



UK 4 - Feed-through terminal block

3003017

<https://www.phoenixcontact.com/ro/produse/3003017>



FB-150 METER - Fixed bridge

0201595

<https://www.phoenixcontact.com/ro/produse/0201595>



Cross connection rail, for fixed bridging of identical inputs and outputs, made of Cu, nickel-plated, 1 m long

KSS 3- 6 - Short-circuit connector

0309523

<https://www.phoenixcontact.com/ro/produse/0309523>



Short-circuit connector, pitch: 6 mm, number of positions: 3, color: black

UK 4 - Feed-through terminal block

3003017

<https://www.phoenixcontact.com/ro/produse/3003017>



KSS 6 - Short-circuit connector

0301547

<https://www.phoenixcontact.com/ro/produse/0301547>



Short-circuit connector, pitch: 6 mm, number of positions: 2, color: black

RPS - Reducing plug

0201647

<https://www.phoenixcontact.com/ro/produse/0201647>



Reducing plug, number of positions: 1, color: gray

UK 4 - Feed-through terminal block

3003017

<https://www.phoenixcontact.com/ro/produse/3003017>



TS-K - Separating plate

1302215

<https://www.phoenixcontact.com/ro/produse/1302215>



Separating plate, depth: 22 mm, width: 0.5 mm, height: 22 mm, color: gray

ATP-UK - Partition plate

3003224

<https://www.phoenixcontact.com/ro/produse/3003224>



Partition plate, depth: 45.7 mm, width: 1.5 mm, height: 56 mm, color: gray

UK 4 - Feed-through terminal block

3003017

<https://www.phoenixcontact.com/ro/produse/3003017>



SBS 6:UNBEDRUCKT - Marker card

1007222

<https://www.phoenixcontact.com/ro/produse/1007222>




Marker card, Card, white, unlabeled, can be labeled with: Marker pen, mounting type: snapped, snap into flat marker groove, for terminal block width: 6 mm, lettering field size: 6 x 6.1 mm, Number of individual labels: 250

PS-UK 2,5 B/Z-6 - Test plug

3001239

<https://www.phoenixcontact.com/ro/produse/3001239>



Test plug, number of positions: 1, color: red

UK 4 - Feed-through terminal block

3003017

<https://www.phoenixcontact.com/ro/produse/3003017>



PS-UK 2,5 B/E - Test plug

3001132

<https://www.phoenixcontact.com/ro/produse/3001132>



Test plug, number of positions: 1, color: red

NS 32 PERF 2000MM-VPE 10 - DIN rail perforated

1201002

<https://www.phoenixcontact.com/ro/produse/1201002>



DIN rail perforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, G profile, color: silver

UK 4 - Feed-through terminal block

3003017

<https://www.phoenixcontact.com/ro/produse/3003017>



NS 32 UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201015

<https://www.phoenixcontact.com/ro/produse/1201015>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, G profile, color: silver

NS 35/ 7,5 PERF 2000MM - DIN rail perforated

0801733

<https://www.phoenixcontact.com/ro/produse/0801733>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

UK 4 - Feed-through terminal block

3003017

<https://www.phoenixcontact.com/ro/produse/3003017>



NS 35/ 7,5 UNPERF 2000MM - DIN rail, unperforated

0801681

<https://www.phoenixcontact.com/ro/produse/0801681>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

NS 35/ 7,5 WH PERF 2000MM - DIN rail perforated

1204119

<https://www.phoenixcontact.com/ro/produse/1204119>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver

UK 4 - Feed-through terminal block

3003017

<https://www.phoenixcontact.com/ro/produse/3003017>



NS 35/ 7,5 WH UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1204122

<https://www.phoenixcontact.com/ro/produse/1204122>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver

NS 35/ 7,5 AL UNPERF 2000MM - DIN rail, unperforated

0801704

<https://www.phoenixcontact.com/ro/produse/0801704>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Aluminum, uncoated, Standard profile, color: silver

UK 4 - Feed-through terminal block

3003017

<https://www.phoenixcontact.com/ro/produse/3003017>



NS 35/ 7,5 ZN PERF 2000MM - DIN rail perforated

1206421

<https://www.phoenixcontact.com/ro/produse/1206421>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, Standard profile, color: silver

NS 35/ 7,5 ZN UNPERF 2000MM - DIN rail, unperforated

1206434

<https://www.phoenixcontact.com/ro/produse/1206434>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, Standard profile, color: silver

UK 4 - Feed-through terminal block

3003017

<https://www.phoenixcontact.com/ro/produse/3003017>



NS 35/ 7,5 CU UNPERF 2000MM-VPE 10 - DIN rail, unperforated

0801762

<https://www.phoenixcontact.com/ro/produse/0801762>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Copper, uncoated, Standard profile, color: copper-colored

NS 35/ 7,5 CAP - End cap

1206560

<https://www.phoenixcontact.com/ro/produse/1206560>

DIN rail end piece, for DIN rail NS 35/7.5



UK 4 - Feed-through terminal block

3003017

<https://www.phoenixcontact.com/ro/produse/3003017>



NS 35/15 PERF 2000MM - DIN rail perforated

1201730

<https://www.phoenixcontact.com/ro/produse/1201730>



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

NS 35/15 UNPERF 2000MM - DIN rail, unperforated

1201714

<https://www.phoenixcontact.com/ro/produse/1201714>



DIN rail, unperforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

UK 4 - Feed-through terminal block

3003017

<https://www.phoenixcontact.com/ro/produse/3003017>



NS 35/15 WH PERF 2000MM - DIN rail perforated

0806602

<https://www.phoenixcontact.com/ro/produse/0806602>



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: white

NS 35/15 WH UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1204135

<https://www.phoenixcontact.com/ro/produse/1204135>



DIN rail, unperforated, Pack of 10 (20 m), similar to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver

UK 4 - Feed-through terminal block

3003017

<https://www.phoenixcontact.com/ro/produse/3003017>



NS 35/15 AL UNPERF 2000MM - DIN rail, unperforated

1201756

<https://www.phoenixcontact.com/ro/produse/1201756>



DIN rail, unperforated, similar to EN 60715, material: Aluminum, uncoated, Standard profile, color: silver

NS 35/15 ZN PERF 2000MM - DIN rail perforated

1206599

<https://www.phoenixcontact.com/ro/produse/1206599>



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, Standard profile, color: silver

UK 4 - Feed-through terminal block

3003017

<https://www.phoenixcontact.com/ro/produse/3003017>



NS 35/15 ZN UNPERF 2000MM - DIN rail, unperforated

1206586

<https://www.phoenixcontact.com/ro/produse/1206586>



DIN rail, unperforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, Standard profile, color: silver

NS 35/15 CU UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201895

<https://www.phoenixcontact.com/ro/produse/1201895>



DIN rail, unperforated, Pack of 10 (20 m), similar to EN 60715, material: Copper, uncoated, Standard profile, color: copper-colored

UK 4 - Feed-through terminal block

3003017

<https://www.phoenixcontact.com/ro/produse/3003017>



NS 35/15 CAP - End cap

1206573

<https://www.phoenixcontact.com/ro/produse/1206573>

DIN rail end piece, for DIN rail NS 35/15



NS 35/15-2,3 UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201798

<https://www.phoenixcontact.com/ro/produse/1201798>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile 2.3 mm, color: silver

UK 4 - Feed-through terminal block

3003017

<https://www.phoenixcontact.com/ro/produse/3003017>



ZB 6:UNBEDRUCKT - Zack marker strip

1051003

<https://www.phoenixcontact.com/ro/produse/1051003>



Zack marker strip, Strip, white, unlabeled, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 6.15 x 10.5 mm, Number of individual labels: 10

ZB 6 CUS - Zack marker strip

0824992

<https://www.phoenixcontact.com/ro/produse/0824992>



Zack marker strip, can be ordered: Strip, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 6.2 mm, lettering field size: 6.15 x 10.5 mm, Number of individual labels: 10

UK 4 - Feed-through terminal block

3003017

<https://www.phoenixcontact.com/ro/produse/3003017>



ZB 6,LGS:FORTL.ZAHLEN - Zack marker strip

1051016

<https://www.phoenixcontact.com/ro/produse/1051016>



Zack marker strip, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, printed horizontally: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 491 ... 500, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 6. 15 x 10.5 mm, Number of individual labels: 10

ZB 6,QR:FORTL.ZAHLEN - Zack marker strip

1051029

<https://www.phoenixcontact.com/ro/produse/1051029>



Zack marker strip, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, Printed vertically: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 491 ... 500, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 6. 15 x 10.5 mm, Number of individual labels: 10

UK 4 - Feed-through terminal block

3003017

<https://www.phoenixcontact.com/ro/produse/3003017>



ZB 6,LGS:GLEICHE ZAHLEN - Zack marker strip

1051032

<https://www.phoenixcontact.com/ro/produse/1051032>



Zack marker strip, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, printed horizontally: Identical numbers 1 or 2, etc. up to 100, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 6.15 x 10.5 mm, Number of individual labels: 10

ZB 6,LGS:L1-N,PE - Marker for terminal blocks

1051414

<https://www.phoenixcontact.com/ro/produse/1051414>



Marker for terminal blocks, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, horizontal: L1, L2, L3, N, PE, L1, L2, L3, N, PE, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 6.15 x 10.5 mm, Number of individual labels: 10

UK 4 - Feed-through terminal block

3003017

<https://www.phoenixcontact.com/ro/produse/3003017>



ZB 6,LGS:U-N - Marker for terminal blocks

1051430

<https://www.phoenixcontact.com/ro/produse/1051430>



Marker for terminal blocks, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, printed horizontally: U, V, W, N, GND, U, V, W, N, GND, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 6.15 x 10.5 mm, Number of individual labels: 10

UC-TM 6 - Marker for terminal blocks

0818085

<https://www.phoenixcontact.com/ro/produse/0818085>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 5.6 x 10.5 mm, Number of individual labels: 80

UK 4 - Feed-through terminal block

3003017

<https://www.phoenixcontact.com/ro/produse/3003017>



UC-TM 6 CUS - Marker for terminal blocks

0824589

<https://www.phoenixcontact.com/ro/produse/0824589>



Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 6.2 mm, lettering field size: 5.6 x 10.5 mm, Number of individual labels: 80

UCT-TM 6 - Marker for terminal blocks

0828736

<https://www.phoenixcontact.com/ro/produse/0828736>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 5.6 x 10.5 mm, Number of individual labels: 60

UK 4 - Feed-through terminal block

3003017

<https://www.phoenixcontact.com/ro/produse/3003017>



UCT-TM 6 CUS - Marker for terminal blocks

0829602

<https://www.phoenixcontact.com/ro/produse/0829602>



Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 6.2 mm, lettering field size: 5.6 x 10.5 mm, Number of individual labels: 60

MPS-MT - Test plug

0201744

<https://www.phoenixcontact.com/ro/produse/0201744>



Test plug, with solder connection up to 1 mm² conductor cross section, number of positions: 1, color: gray

UK 4 - Feed-through terminal block

3003017

<https://www.phoenixcontact.com/ro/produse/3003017>



MPS-IH WH - Insulating sleeve

0201663

<https://www.phoenixcontact.com/ro/produse/0201663>

Insulating sleeve, color: white



MPS-IH RD - Insulating sleeve

0201676

<https://www.phoenixcontact.com/ro/produse/0201676>

Insulating sleeve, color: red



UK 4 - Feed-through terminal block

3003017

<https://www.phoenixcontact.com/ro/produse/3003017>




MPS-IH BU - Insulating sleeve

0201689

<https://www.phoenixcontact.com/ro/produse/0201689>

Insulating sleeve, color: blue



MPS-IH YE - Insulating sleeve

0201692

<https://www.phoenixcontact.com/ro/produse/0201692>

Insulating sleeve, color: yellow



UK 4 - Feed-through terminal block

3003017

<https://www.phoenixcontact.com/ro/produse/3003017>



MPS-IH GN - Insulating sleeve

0201702

<https://www.phoenixcontact.com/ro/produse/0201702>

Insulating sleeve, color: green



MPS-IH GY - Insulating sleeve

0201728

<https://www.phoenixcontact.com/ro/produse/0201728>

Insulating sleeve, color: gray



UK 4 - Feed-through terminal block

3003017

<https://www.phoenixcontact.com/ro/produse/3003017>



MPS-IH BK - Insulating sleeve

0201731

<https://www.phoenixcontact.com/ro/produse/0201731>

Insulating sleeve, color: black



CLIPFIX 35 - End bracket

3022218

<https://www.phoenixcontact.com/ro/produse/3022218>

Quick mounting end clamp for NS 35/7,5 DIN rail or NS 35/15 DIN rail, with marking option, width: 9.5 mm, color: gray



UK 4 - Feed-through terminal block

3003017

<https://www.phoenixcontact.com/ro/produse/3003017>



CLIPFIX 35-5 - End bracket

3022276

<https://www.phoenixcontact.com/ro/produse/3022276>




Quick mounting end clamp for NS 35/7,5 DIN rail or NS 35/15 DIN rail, with marking option, with parking option for FBS...5, FBS...6, KSS 5, KSS 6, width: 5.15 mm, color: gray

E/NS 35 N - End bracket

0800886

<https://www.phoenixcontact.com/ro/produse/0800886>



End clamp, width: 9.5 mm, color: gray

UK 4 - Feed-through terminal block

3003017

<https://www.phoenixcontact.com/ro/produse/3003017>



E/UK - End bracket

1201442

<https://www.phoenixcontact.com/ro/produse/1201442>

End bracket, Mounting on a DIN rail NS 32 or NS 35, material: PA, color: gray



E/UK 1 - End bracket

1201413

<https://www.phoenixcontact.com/ro/produse/1201413>

End clamps, for supporting the ends of double-level and three-level terminal blocks, width: 10 mm, color: gray



UK 4 - Feed-through terminal block

3003017

<https://www.phoenixcontact.com/ro/produse/3003017>



PSBJ 3/13/4 - Test plug strip

0201304

<https://www.phoenixcontact.com/ro/produse/0201304>



Test plug strip, number of positions: 1, color: silver

PSB 3/10/4 - Test plug strip

0601292

<https://www.phoenixcontact.com/ro/produse/0601292>



Test plug strip, number of positions: 1, color: silver

UK 4 - Feed-through terminal block

3003017

<https://www.phoenixcontact.com/ro/produse/3003017>



D-UK 4/10 - End cover

3003020

<https://www.phoenixcontact.com/ro/produse/3003020>

End cover, depth: 35.9 mm, width: 1.8 mm, height: 42.5 mm, color: gray



EA 5 - Cover

1024014

<https://www.phoenixcontact.com/ro/produse/1024014>

Cover, material: ABS, color: transparent



UK 4 - Feed-through terminal block

3003017

<https://www.phoenixcontact.com/ro/produse/3003017>



EA 5-WS - Cover

1024085

<https://www.phoenixcontact.com/ro/produse/1024085>

Single covers, for covering one terminal block, with black symbol (lightning flash)
snap fit, color: transparent/yellow



SF-SL 0,6X3,5-100 S-VDE - Screwdriver

1212587

<https://www.phoenixcontact.com/ro/produse/1212587>

Actuation tool, for ST terminal blocks, VDE insulated, with slimmer insulation
integrated in the blade, also suitable for use as a bladed screwdriver, size: 0.6 x
3.5 x 100 mm, 2-component grip, with non-slip grip



Phoenix Contact 2024 © - Toate drepturile rezervate
<https://www.phoenixcontact.com>

PHOENIX CONTACT România
Splaiul Unirii 165 Timpuri Noi Square TNO1, Etaj 1
Bucuresti 030133
+40 21 350 88 12 - 3
sales.ro@phoenixcontact.com