

Fișă tehnică produs

Specificatii



Intreruptor ComPacT NSX400N, 50 kA la 415 VAC, unitate de declansare MicroLogic 2.3 250A, 3 poli 3d

C40N32D250

Principale

Gama	ComPacT noua generatie
nume produs	ComPacT NSX noua generatie
nume scurt al dispozitivului	NSX400N
Tip produs sau componenta	Disjunctori
aplicatie a dispozitivului	Distributie
descriere poli	3P
descriere poli protejati	3d
[In] curent nominal	250 A la 40 °C
[Ue] tensiune nominala de functionare	690 V c.a. 50/60 Hz
Tip retea electrica	C.a.
frecventa retea electrica	50/60 Hz
adevare pentru izolatie	Da conformitate cu SR EN 60947-2
categorie de utilizare	Categoria A
[Icu] capacitate nominala limita de rupere la scurtcircuit	85 kA Icu la 220/240 V c.a. 50/60 Hz conformitate cu SR EN 60947-2 50 kA Icu la 380/415 V c.a. 50/60 Hz conformitate cu SR EN 60947-2 42 kA Icu la 440 V c.a. 50/60 Hz conformitate cu SR EN 60947-2 30 kA Icu la 500 V c.a. 50/60 Hz conformitate cu SR EN 60947-2 22 kA Icu la 525 V c.a. 50/60 Hz conformitate cu SR EN 60947-2 10 kA Icu la 660/690 V c.a. 50/60 Hz conformitate cu SR EN 60947-2 85 kA Icu la 240 V c.a. 50/60 Hz conformitate cu UL 60947-4-1 50 kA Icu la 480 V c.a. 50/60 Hz conformitate cu UL 60947-4-1 20 kA Icu la 600 V c.a. 50/60 Hz conformitate cu UL 60947-4-1
Nivel de performanta	N 50 kA 415 V c.a.
nume unitate de declansare	Micrologic 2.3
tehnologie unitate de declansare	Electronic
functii de protectie a unitatii de declansare	LSol
tip de control	Comutare
Modul de montare a intreruptorului	Fix

Suplimentare

[Ui] tensiune nominala de izolatie	800 V c.a. 50/60 Hz
[Uimp] tensiune nominala de tinere la impuls	8 kV

[Ics] capacitate nominala de serviciu de rupere la scurtcircuit	85 kA la 220/240 V c.a. 50/60 Hz conformitate cu SR EN 60947-2 50 kA la 380/415 V c.a. 50/60 Hz conformitate cu SR EN 60947-2 42 kA la 440 V c.a. 50/60 Hz conformitate cu SR EN 60947-2 30 kA la 500 V c.a. 50/60 Hz conformitate cu SR EN 60947-2 11 kA la 525 V c.a. 50/60 Hz conformitate cu SR EN 60947-2 10 kA la 660/690 V c.a. 50/60 Hz conformitate cu SR EN 60947-2
durabilitate mecanica	15000 cic
durabilitate electrica	12000 cic la 440 V In/2 6000 cic la 440 V In 6000 cic la 690 V In/2 3000 cic la 690 V In
puterea disipata pe pol	19,2 W
suport de montare	Placa dorsala
pozitie de montare	Orizantal si vertical Flat on the back
conexiune superioara	Fata
conexiune inferioara	Fata
pasul de conectare	45 mm
tip de protectie	L : for protectie la suprasarcina (timpindelungat) So : for protectie la scurtcircuit de scurta durata cu intarziere fixa I : for protectie instantanee la scurtcircuit
gama uitatii de declansare	250 A la 40 °C
Tip de reglare a preluarii de lunga durata Ir (protectie termica)	9 setari reglabile
[Ir] interval de reglare a restabilirii pe termen lung	70...250 A
Tip de reglare a intarzierii de lunga durata tr	Fix
[tr] reglarea intarzierii de lunga durata	400 s la 1.5 x Ir 16 s la 6 x Ir 11 s la 7.2 x Ir
memorie termica	20 de minute inainte si dupa declansare
Reglarea preluarii protectiei de scurta durata tip Isd	9 setari reglabile
[Isd] interval de reglare a restabilirii pe termen scurt	1,5...10 x Ir
Reglarea intarzierii protectiei de scurta durata tip tsd	Fix
Ajustarea protectiei instantanee tip Ii	Fix
[Ii] interval de reglare a restabilirii instantanee	3000 A
protectie de scurgere la pamant	Fara
blocare ZSI cu selectare a zonei	Fara
Numar de sloturi pentru auxiliare electrice	6 sloturi
semnalizare locala	LED intermitent (verde) for gata de functionare LED 105 % Ir (rosu) for suprasarcina LED 90 % Ir (portocaliu) for suprasarcina
Latime	140 mm
Inaltime	255 mm
Adancime	110 mm
greutate produs	6,05 kg
Mediu	
standarde	SR EN 60947-2

categoria de supratensiune	III
clasa de protectie la electrocutare	Clasa II pornit parte frontala
grad de poluare	3 conformitate cu SR EN 60664-1
grad de protectie IP	IP40 conforming to SR EN 60529
grad de protectie IK	IK07 conformitate cu IEC 62262
temperatura ambiantala de functionare	-25...70 °C
temperatura ambiantala pentru depozitare	-50...85 °C
umiditate relativa	0...95 %
altitudinea de functionare	0..2000 m fără declarare 2000 m...5000 m cu declarare

Unitati de ambalare

Unitate de masura pentru prima forma de impachetare	PCE
Număr de produse în pachet	1
Inaltime prima forma de impachetare	14,8 cm
Latime prima forma de impachetare	15,5 cm
Lungime prima forma de impachetare	29,0 cm
Greutate colet(Lbs)	5,618 kg
Unitate de masura pentru a doua forma de impachetare	S04
Numar unitati in a doua forma de impachetare	2
Inaltime a doua forma de impachetare	30,0 cm
Latime a doua forma de impachetare	40,0 cm
Lungime a doua forma de impachetare	60,0 cm
Greutate a doua forma de impachetare	12,08 kg

Garanție contractuală

Garantie (in luni)	18
--------------------	----

Schneider Electric isi propune sa atinga nivelul Net Zero pana in 2050 prin parteneriate la nivelul lantului de aprovizionare, materiale cu impact mai redus si circularitate, prin campania „Use Better, Use Longer, Use Again” pentru a extinde durata de viata a produselor si reciclabilitatea.

[Environmental Data explicate >](#)

[Cum evaluam sustenabilitatea produselor >](#)

Amprenta de mediu

Amprenta de carbon totala pe durata de viata	169 kg CO2 eq.
Amprenta de carbon a fazei de fabricație [A1–A3]	35 kg CO2 eq.
Amprenta de carbon a fazei de distribuție [A4]	0.9 kg CO2 eq.
Amprenta de carbon a fazei de instalare [A5]	0.6 kg CO2 eq.
Amprenta de carbon a fazei de utilizare [B2, B3, B4, B6]	121 kg CO2 eq.
Amprenta de carbon a fazei de sfârșit de viață [C1–C4]	11 kg CO2 eq.
Raport de mediu	Profilul ambiental al produsului

Use Better

Materiale si ambalare

Pachet cu carton reciclabil	Da
Ambalaj fara plastic	Da
Numar SCIP	25ca3248-85d0-423a-a9d8-5b7aeb52e7b6
Directiva RoHS a UE	Conform Prin Scutire
Regulamentul REACH	Referința conține SVHC peste prag
Statut de indemn de halogen	Produsul conține halogeni peste pragurile admise
Nu contine PVC	Da
Nu contine silicon	Nu

Use Longer

Prelungire durata de viata

Reparare	Nu
Posibilitati de actualizare	Nu

Use Again

Reambalare si refabricare

Potentialul de reciclabilitate, in %	56
Profil circularitate	Informatii privind sfarsitul duratei de viata
Preluare la sfarsitul duratei de viata	Da

Eticheta WEEE

În Uniunea Europeană, produsele trebuie reciclate respectând sistemul specific de colectare a deșeurilor și nu trebuie să ajungă în puștele de colectare a deșeurilor menajere.

Offer Marketing Illustration

Product benefits / Features



ComPacT NSX
Range Accessories

Wireless auxiliary contact

Short terminal shield

Interphase barriers

Long terminal shield

Rotary handles

Standard auxiliary contact

MN undervoltage release

MX shunt release

Standard motor mechanism module

The image displays a collection of accessories for the ComPacT NSX circuit breaker range. At the top left, a green circular graphic partially overlaps a photograph of the main circuit breaker unit. Below this, the title 'ComPacT NSX Range Accessories' is presented in a bold, sans-serif font. The accessories are arranged in a 3x3 grid, each accompanied by a small product photograph and a descriptive label. The labels are: 'Wireless auxiliary contact' (a small green and white component), 'Short terminal shield' (a black rectangular shield), 'Interphase barriers' (a black vertical barrier), 'Long terminal shield' (a larger black rectangular shield), 'Rotary handles' (two black rotary handles with green accents), 'Standard auxiliary contact' (a white rectangular component with two terminals), 'MN undervoltage release' (a black rectangular component with a white label), 'MX shunt release' (a yellow and black component with a white label), and 'Standard motor mechanism module' (a black rectangular component with a white label and a small handle).

Offer Marketing Illustration

Product benefits / Features



Offer Marketing Illustration

Product benefits / Features



ComPacT NSX

Technical Benefits

- Nominal current: 16 to 630 A and 9 breaking capacities for the 2 sizes of circuit breakers
- 1, 2, 3, and 4 pole versions available
- Large range of electronic and thermal-magnetic protections
- Plug and ready wiring system and communicating accessories
- Integrated earth leakage protection via MicroLogic Vigi (earth leakage circuit breaker - ELCB)
- Advanced trip unit with integrated power metering: I, U, P, E, THD, f, CosPhi

Offer Marketing Illustration

Product benefits / Features

ComPacT NSX

Moulded Case Circuit Breaker



Protection begins with prevention
Designed to prevent an electrical fire through integrated earth leakage protection with preventive maintenance thanks to its Everlink power connections.



Maximize power availability
By providing corrective, preventive, and predictive maintenance for asset management thanks to our advanced MicroLogic trip units.



Connectivity
Designed to connect to EcoStruxure Power, an IoT-connected architecture for improving every aspect of your power distribution system.

