

PTRVB 4-FI /BK - Potential distributors



3270158

<https://www.phoenixcontact.com/ro/produse/3270158>

Vă rugăm să țineți cont de faptul că datele afișate în acest document PDF au fost generate din catalogul nostru online. Datele complete sunt disponibile în documentația pentru utilizator. În cazul descărcărilor, se aplică Termenii și condițiile generale de utilizare ale companiei noastre.



Potential distributors, with option to supply up to 6 mm², nom. voltage: 250 V, nominal current: 17.5 A, connection method: Push-in connection, Rated cross section: 1.5 mm², cross section: 0.14 mm² - 2.5 mm², Feed-in stage, Rated cross section: 4 mm², cross section: 0.2 mm² - 6 mm², mounting: NS 35/7,5, NS 35/15, color: gray, color of connection elements: black

Avantajele dumneavoastră

- High contact quality thanks to push-in technology as a replacement for Wire-Wrap®, TERMI-POINT®, etc.
- Tool-free wiring in a confined space thanks to compact size
- Bridgeable potential distributor with option to supply up to 6 mm²

Date comerciale

Număr articol	3270158
Unitate de ambalare	10 Bucată
Cantitate minimă pentru comandă	1 Bucată
Cod produs	BE6211
Pagina de catalog	Pagina 48 (C-1-2019)
GTIN	4046356963404
Greutate pe bucată (inclusiv ambalajul)	20,51 g
Greutate pe bucată (fără ambalaj)	20 g
Cod tarifar vamal	85369010
Țara de origine	PL

Date tehnice

Product properties

Product type	Potential distributor
Number of positions	2
Number of connections	13
Number of rows	4
Potentials	1

Data management status

Article revision	06
------------------	----

Insulation characteristics

Overvoltage category	III
----------------------	-----

Electrical properties

Rated surge voltage	4 kV
Maximum power dissipation for nominal condition	0.56 W

Connection data

Service Entrance	yes
Number of connections per level	4
Nominal cross section	1.5 mm ²

Level 1+2+3 above 1

Stripping length	8 mm ... 10 mm
Connection in acc. with standard	IEC 60947-7-1
Conductor cross section rigid	0.14 mm ² ... 2.5 mm ²
Cross section AWG	26 ... 14 (converted acc. to IEC)
Conductor cross section flexible	0.14 mm ² ... 1.5 mm ²
Conductor cross section, flexible [AWG]	26 ... 16 (converted acc. to IEC)
Conductor cross-section flexible (ferrule without plastic sleeve)	0.14 mm ² ... 1.5 mm ²
Flexible conductor cross section (ferrule with plastic sleeve)	0.14 mm ² ... 1.5 mm ²
Nominal current	17.5 A (with 1.5 mm ² conductor cross section)
Maximum load current	24 A (per chamber with 2.5 mm ² conductor cross section)
Maximum total current	37 A (per potential distributor)
Nominal voltage	250 V
Nominal cross section	1.5 mm ²

Feed-in stage

Note	Only the "CRIMPFOX 6" crimping pliers may be used for crimping with 6 mm ² stranded and ferrule.
Stripping length	10 mm ... 12 mm
Connection in acc. with standard	IEC 60947-7-1
Conductor cross section rigid	0.2 mm ² ... 6 mm ²

PTRVB 4-FI /BK - Potential distributors



3270158

<https://www.phoenixcontact.com/ro/produse/3270158>

Cross section AWG	24 ... 10 (converted acc. to IEC)
Conductor cross section flexible	0.2 mm ² ... 6 mm ²
Conductor cross section, flexible [AWG]	24 ... 10 (converted acc. to IEC)
Conductor cross-section flexible (ferrule without plastic sleeve)	0.2 mm ² ... 6 mm ²
Flexible conductor cross section (ferrule with plastic sleeve)	0.2 mm ² ... 6 mm ²
Nominal current	32 A (Supply, for 4 mm ² conductor cross section)
Maximum load current	37 A (Service Entrance)
Nominal voltage	250 V
Nominal cross section	4 mm ²

Level 1+2+3 above 1 Connection cross sections directly pluggable

Conductor cross section rigid	0.34 mm ² ... 2.5 mm ²
Conductor cross section, rigid [AWG]	20 ... 14 (converted acc. to IEC)
Conductor cross-section flexible (ferrule without plastic sleeve)	0.34 mm ² ... 1.5 mm ²
Flexible conductor cross section (ferrule with plastic sleeve)	0.34 mm ² ... 1.5 mm ²

Feed-in stage Connection cross sections directly pluggable

Conductor cross section rigid	0.34 mm ² ... 6 mm ²
Conductor cross section, rigid [AWG]	24 ... 10 (converted acc. to IEC)
Conductor cross-section flexible (ferrule without plastic sleeve)	0.34 mm ² ... 6 mm ²
Flexible conductor cross section (ferrule with plastic sleeve)	0.34 mm ² ... 6 mm ²

Dimensions

Width	8.3 mm
Height	64 mm
Depth on NS 35/7,5	55.5 mm
Depth on NS 35/15	63 mm

Material specifications

Color	gray
Color of connection elements	black
Flammability rating according to UL 94	V0
Insulating material group	I
Insulating material	PA
Static insulating material application in cold	-60 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21))	125 °C
Relative insulation material temperature index (Elec., UL 746 B)	130 °C
Fire protection for rail vehicles (DIN EN 45545-2) R22	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26	HL 1 - HL 3
Calorimetric heat release NFPA 130 (ASTM E 1354)	27,5 MJ/kg
Surface flammability NFPA 130 (ASTM E 162)	passed
Specific optical density of smoke NFPA 130 (ASTM E 662)	passed

PTRVB 4-FI /BK - Potential distributors



3270158

<https://www.phoenixcontact.com/ro/produse/3270158>

Smoke gas toxicity NFPA 130 (SMP 800C)	passed
--	--------

Electrical tests

Surge voltage test

Test voltage setpoint	4.8 kV
Result	Test passed

Temperature-rise test

Requirement temperature-rise test	Increase in temperature ≤ 45 K
Result	Test passed
Short-time withstand current 1.5 mm ²	0.18 kA
Short-time withstand current 2.5 mm ²	0.3 kA
Short-time withstand current 4 mm ²	0.48 kA
Short-time withstand current 6 mm ²	0.72 kA
Result	Test passed

Power-frequency withstand voltage

Test voltage setpoint	1.5 kV
Result	Test passed

Mechanical properties

Mechanical data

Open side panel	Yes
-----------------	-----

Mechanical tests

Mechanical strength

Result	Test passed
--------	-------------

Attachment on the carrier

DIN rail/fixing support	NS 35
Test force setpoint	1 N
Result	Test passed

Test for conductor damage and slackening

Rotation speed	10 rpm
Revolutions	135
Conductor cross section/weight	0.14 mm ² / 0.2 kg
	1.5 mm ² / 0.4 kg
	2.5 mm ² / 0.7 kg
Result	Test passed

Test for conductor damage and slackening

Rotation speed	10 rpm
Revolutions	135
	0.2 mm ² / 0.2 kg

PTRVB 4-FI /BK - Potential distributors



3270158

<https://www.phoenixcontact.com/ro/produse/3270158>

Conductor cross section/weight	4 mm ² / 0.9 kg
	6 mm ² / 1.4 kg
Result	Test passed

Environmental and real-life conditions

Aging

Temperature cycles	192
Result	Test passed

Needle-flame test

Time of exposure	30 s
Result	Test passed

Oscillation/broadband noise

Specification	DIN EN 50155 (VDE 0115-200):2008-03
Spectrum	Service life test category 2, bogie-mounted
Frequency	$f_1 = 5 \text{ Hz}$ to $f_2 = 250 \text{ Hz}$
ASD level	6.12 (m/s ²) ² /Hz
Acceleration	3.12g
Test duration per axis	5 h
Test directions	X-, Y- and Z-axis
Result	Test passed

Shocks

Specification	DIN EN 50155 (VDE 0115-200):2008-03
Pulse shape	Half-sine
Acceleration	30g
Shock duration	18 ms
Number of shocks per direction	3
Test directions	X-, Y- and Z-axis (pos. and neg.)
Result	Test passed

Ambient conditions

Ambient temperature (operation)	-60 °C ... 105 °C (max. short-term operating temperature RTI Elec.)
Ambient temperature (storage/transport)	-25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C
Permissible humidity (storage/transport)	30 % ... 70 %

Standards and regulations

Connection in acc. with standard	IEC 60947-7-1
	IEC 60947-7-1

Mounting

PTRVB 4-FI /BK - Potential distributors



3270158

<https://www.phoenixcontact.com/ro/produse/3270158>

Mounting type	NS 35/7,5
	NS 35/15

Desene

Circuit diagram



PTRVB 4-FI /BK - Potential distributors



3270158

<https://www.phoenixcontact.com/ro/produse/3270158>

Aprobări

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/ro/produse/3270158>



CSA

ID de înregistrare: 2030668



CSA

ID de înregistrare: 2030668



IECEE CB Scheme

ID de înregistrare: NL-58817

	Tensiune nominală U_N	Curent nominal I_N	Secțiune transversală AWG	Secțiune transversală mm^2
	250 V	17.5 A	-	-



EAC

ID de înregistrare: RU C-DE.BL08.B.00682



cULus Recognized

ID de înregistrare: E60425



KEMA-KEUR

ID de înregistrare: 71-102890

	Tensiune nominală U_N	Curent nominal I_N	Secțiune transversală AWG	Secțiune transversală mm^2
Only flexible conductors	250 V	17.5 A	-	0.14 - 1.5
Only rigid conductors	250 V	17.5 A	-	0.14 - 2.5



cULus Recognized

ID de înregistrare: E60425

DNV

ID de înregistrare: TAE000016Y



cULus Recognized

ID de înregistrare: E60425

PTRVB 4-FI /BK - Potential distributors



3270158

<https://www.phoenixcontact.com/ro/produse/3270158>

Clasificări

ECLASS

ECLASS-11.0	27141120
ECLASS-13.0	27250119

ETIM

ETIM 9.0	EC000897
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

3270158

<https://www.phoenixcontact.com/ro/produse/3270158>

Environmental product compliance

EU RoHS

Îndeplinește cerințele conform directivei RoHS	Da, Nicio reglementare privind excepțiile
--	---

China RoHS

Environment friendly use period (EFUP)	EFUP-E
	Nu există substanțe periculoase peste valorile limită

EU REACH SVHC

Trimitere la substanța candidată REACH (nr. CAS)	Nicio substanță cu un procentaj masic mai mare de 0,1 %
--	---

EF3.0 Climate Change

CO2e kg	0,236 kg CO2e
---------	---------------

PTRVB 4-FI /BK - Potential distributors

3270158

<https://www.phoenixcontact.com/ro/produse/3270158>

Accesorii

i Indicație: Funcționarea produsului poate fi restricționată în cazul utilizării împreună cu unul din accesoriile prezentate mai jos.

FBST 500-PLC RD - Continuous plug-in bridge

2966786

<https://www.phoenixcontact.com/ro/produse/2966786>



Continuous plug-in bridge, length: 500 mm, color: red

i Max. current carrying capacity: 32 A

FBST 500-PLC GY - Continuous plug-in bridge

2966838

<https://www.phoenixcontact.com/ro/produse/2966838>



Continuous plug-in bridge, length: 500 mm, color: gray

i Max. current carrying capacity: 32 A

PTRVB 4-FI /BK - Potential distributors

3270158

<https://www.phoenixcontact.com/ro/produse/3270158>

FBST 500-PLC BN - Continuous plug-in bridge

2967976

<https://www.phoenixcontact.com/ro/produse/2967976>




Continuous plug-in bridge, length: 500 mm, color: brown

 Max. current carrying capacity: 32 A

FBST 500-PLC BU - Continuous plug-in bridge

2966692

<https://www.phoenixcontact.com/ro/produse/2966692>



Continuous plug-in bridge, length: 500 mm, color: blue

 Max. current carrying capacity: 32 A

PTRVB 4-FI /BK - Potential distributors

3270158

<https://www.phoenixcontact.com/ro/produse/3270158>

DP-PTRV 4 - Spacer plate

3270163

<https://www.phoenixcontact.com/ro/produse/3270163>



Spacer plate, depth: 54 mm, width: 8.3 mm, height: 63.6 mm, color: gray

CDC-PTRV - Retaining bracket

3270167

<https://www.phoenixcontact.com/ro/produse/3270167>



Retaining bracket, via four PTRV single modules, pitch: 8.3 mm, depth: 71.5 mm, width: 35.6 mm, height: 71.5 mm, color: gray

PTRVB 4-FI /BK - Potential distributors

3270158

<https://www.phoenixcontact.com/ro/produce/3270158>



RPS - Reducing plug

0201647

<https://www.phoenixcontact.com/ro/produce/0201647>



Reducing plug, number of positions: 1, color: gray

FBST 50-PLC RD - Plug-in bridge

1081050

<https://www.phoenixcontact.com/ro/produce/1081050>



Plug-in bridge, length: 50 mm, color: red

PTRVB 4-FI /BK - Potential distributors

3270158

<https://www.phoenixcontact.com/ro/produce/3270158>

FBST 50-PLC BU - Plug-in bridge

1081051

<https://www.phoenixcontact.com/ro/produce/1081051>



Plug-in bridge, length: 50 mm, color: blue

FBST 50-PLC GY - Plug-in bridge

1081053

<https://www.phoenixcontact.com/ro/produce/1081053>



Plug-in bridge, length: 50 mm, color: gray

PTRVB 4-FI /BK - Potential distributors


3270158

<https://www.phoenixcontact.com/ro/produce/3270158>

ZB 8,3:UNBEDRUCKT - Zack marker strip

0803444

<https://www.phoenixcontact.com/ro/produce/0803444>



Zack marker strip, Strip, white, unlabeled, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 8.3 mm, lettering field size: 10.5 x 8.3 mm

ZB 8,3,LGS:FORTL.ZAHLEN - Zack marker strip

0803480

<https://www.phoenixcontact.com/ro/produce/0803480>



Zack marker strip, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 8.3 mm, lettering field size: 10.5 x 8.3 mm

PTRVB 4-FI /BK - Potential distributors

3270158

<https://www.phoenixcontact.com/ro/produce/3270158>

ZB 8,3,QR:FORTL.ZAHLEN - Zack marker strip

0803479

<https://www.phoenixcontact.com/ro/produce/0803479>




Zack marker strip, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 8.3 mm, lettering field size: 10.5 x 8.3 mm

ZB 8,3 CUS - Zack marker strip

8191573

<https://www.phoenixcontact.com/ro/produce/8191573>



Zack marker strip, Strip, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 8.3 mm, lettering field size: 10.5 x 8.3 mm

PTRVB 4-FI /BK - Potential distributors

3270158

<https://www.phoenixcontact.com/ro/produse/3270158>

TM-PTRV 4,QR:1-4 - Marker for terminal blocks

0803464

<https://www.phoenixcontact.com/ro/produse/0803464>



Marker for terminal blocks, white, labeled, mounting type: snapped, for terminal block width: 4 mm, lettering field size: 2.4 x 9.2 mm

TM-PTRV 4,QR:4-1 - Marker for terminal blocks

0803465

<https://www.phoenixcontact.com/ro/produse/0803465>



Marker for terminal blocks, white, labeled, mounting type: snapped, for terminal block width: 4 mm, lettering field size: 2.4 x 9.2 mm

PTRVB 4-FI /BK - Potential distributors

3270158

<https://www.phoenixcontact.com/ro/produce/3270158>

TM-PTRV 4,QR:A-D - Marker for terminal blocks

0803466

<https://www.phoenixcontact.com/ro/produce/0803466>



Marker for terminal blocks, white, labeled, mounting type: snapped, for terminal block width: 4 mm, lettering field size: 2.4 x 9.2 mm

TM-PTRV 4,QR:D-A - Marker for terminal blocks

0803467

<https://www.phoenixcontact.com/ro/produce/0803467>



Marker for terminal blocks, white, labeled, mounting type: snapped, for terminal block width: 4 mm, lettering field size: 2.4 x 9.2 mm

PTRVB 4-FI /BK - Potential distributors

3270158

<https://www.phoenixcontact.com/ro/produse/3270158>

D-PTRV 4 WH - End cover

3270151

<https://www.phoenixcontact.com/ro/produse/3270151>



End cover, depth: 48.9 mm, width: 3.8 mm, height: 63.6 mm, color: white

D-PTRV 4 WH 1-4 - End cover

3270152

<https://www.phoenixcontact.com/ro/produse/3270152>



End cover, depth: 48.9 mm, width: 2.2 mm, height: 63.6 mm, color: white

PTRVB 4-FI /BK - Potential distributors

3270158

<https://www.phoenixcontact.com/ro/produce/3270158>

D-PTRV 4 WH 1-4 LGS - End cover

3270234

<https://www.phoenixcontact.com/ro/produce/3270234>



End cover, depth: 48.9 mm, width: 2.2 mm, height: 63.6 mm, color: white

D-PTRV 4 WH 4-1 - End cover

3270236

<https://www.phoenixcontact.com/ro/produce/3270236>



End cover, depth: 48.9 mm, width: 2.2 mm, height: 63.6 mm, color: white

PTRVB 4-FI /BK - Potential distributors

3270158

<https://www.phoenixcontact.com/ro/produce/3270158>

D-PTRV 4 WH 4-1 LGS - End cover

3270238

<https://www.phoenixcontact.com/ro/produce/3270238>




End cover, depth: 48.9 mm, width: 2.2 mm, height: 63.6 mm, color: white

D-PTRV 4 WH A-D - End cover

3270153

<https://www.phoenixcontact.com/ro/produce/3270153>



End cover, depth: 48.9 mm, width: 2.2 mm, height: 63.6 mm, color: white

PTRVB 4-FI /BK - Potential distributors

3270158

<https://www.phoenixcontact.com/ro/produse/3270158>

D-PTRV 4 WH A-D LGS - End cover

3270235

<https://www.phoenixcontact.com/ro/produse/3270235>



End cover, depth: 48.9 mm, width: 2.2 mm, height: 63.6 mm, color: white

D-PTRV 4 WH D-A - End cover

3270237

<https://www.phoenixcontact.com/ro/produse/3270237>



End cover, depth: 48.9 mm, width: 2.2 mm, height: 63.6 mm, color: white

PTRVB 4-FI /BK - Potential distributors

3270158

<https://www.phoenixcontact.com/ro/produce/3270158>

D-PTRV 4 WH D-A LGS - End cover

3270239

<https://www.phoenixcontact.com/ro/produce/3270239>



End cover, depth: 48.9 mm, width: 2.2 mm, height: 63.6 mm, color: white

NS 35/ 7,5 PERF 2000MM - DIN rail perforated

0801733

<https://www.phoenixcontact.com/ro/produce/0801733>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

PTRVB 4-FI /BK - Potential distributors

3270158

<https://www.phoenixcontact.com/ro/produce/3270158>



NS 35/ 7,5 UNPERF 2000MM - DIN rail, unperforated

0801681

<https://www.phoenixcontact.com/ro/produce/0801681>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

NS 35/ 7,5 WH PERF 2000MM - DIN rail perforated

1204119

<https://www.phoenixcontact.com/ro/produce/1204119>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver

PTRVB 4-FI /BK - Potential distributors

3270158

<https://www.phoenixcontact.com/ro/produce/3270158>

NS 35/ 7,5 WH UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1204122

<https://www.phoenixcontact.com/ro/produce/1204122>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver

NS 35/ 7,5 AL UNPERF 2000MM - DIN rail, unperforated

0801704

<https://www.phoenixcontact.com/ro/produce/0801704>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Aluminum, uncoated, Standard profile, color: silver

PTRVB 4-FI /BK - Potential distributors

3270158

<https://www.phoenixcontact.com/ro/produce/3270158>

NS 35/ 7,5 ZN PERF 2000MM - DIN rail perforated

1206421

<https://www.phoenixcontact.com/ro/produce/1206421>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, Standard profile, color: silver

NS 35/ 7,5 ZN UNPERF 2000MM - DIN rail, unperforated

1206434

<https://www.phoenixcontact.com/ro/produce/1206434>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, Standard profile, color: silver

PTRVB 4-FI /BK - Potential distributors

3270158

<https://www.phoenixcontact.com/ro/produse/3270158>

NS 35/ 7,5 CU UNPERF 2000MM-VPE 10 - DIN rail, unperforated

0801762

<https://www.phoenixcontact.com/ro/produse/0801762>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Copper, uncoated, Standard profile, color: copper-colored

NS 35/ 7,5 CAP - End cap

1206560

<https://www.phoenixcontact.com/ro/produse/1206560>

DIN rail end piece, for DIN rail NS 35/7.5



PTRVB 4-FI /BK - Potential distributors

3270158

<https://www.phoenixcontact.com/ro/produce/3270158>

CLIPFIX 35 - End bracket

3022218

<https://www.phoenixcontact.com/ro/produce/3022218>



Quick mounting end clamp for NS 35/7,5 DIN rail or NS 35/15 DIN rail, with marking option, width: 9.5 mm, color: gray

CLIPFIX 35-5 - End bracket

3022276

<https://www.phoenixcontact.com/ro/produce/3022276>



Quick mounting end clamp for NS 35/7,5 DIN rail or NS 35/15 DIN rail, with marking option, with parking option for FBS...5, FBS...6, KSS 5, KSS 6, width: 5.15 mm, color: gray

PTRVB 4-FI /BK - Potential distributors

3270158


<https://www.phoenixcontact.com/ro/produce/3270158>

E/NS 35 N - End bracket

0800886

<https://www.phoenixcontact.com/ro/produce/0800886>

End clamp, width: 9.5 mm, color: gray



E/UK - End bracket

1201442

<https://www.phoenixcontact.com/ro/produce/1201442>

End bracket, Mounting on a DIN rail NS 32 or NS 35, material: PA, color: gray



PTRVB 4-FI /BK - Potential distributors

3270158

<https://www.phoenixcontact.com/ro/produce/3270158>

E/UK 1 - End bracket

1201413

<https://www.phoenixcontact.com/ro/produce/1201413>



End clamps, for supporting the ends of double-level and three-level terminal blocks, width: 10 mm, color: gray

MPS-MT - Test plug

0201744

<https://www.phoenixcontact.com/ro/produce/0201744>



Test plug, with solder connection up to 1 mm² conductor cross section, number of positions: 1, color: gray

PTRVB 4-FI /BK - Potential distributors

3270158

<https://www.phoenixcontact.com/ro/produce/3270158>

MPS-IH WH - Insulating sleeve

0201663

<https://www.phoenixcontact.com/ro/produce/0201663>

Insulating sleeve, color: white



MPS-IH RD - Insulating sleeve

0201676

<https://www.phoenixcontact.com/ro/produce/0201676>

Insulating sleeve, color: red



PTRVB 4-FI /BK - Potential distributors

3270158


<https://www.phoenixcontact.com/ro/produse/3270158>

MPS-IH BU - Insulating sleeve

0201689

<https://www.phoenixcontact.com/ro/produse/0201689>

Insulating sleeve, color: blue



MPS-IH YE - Insulating sleeve

0201692

<https://www.phoenixcontact.com/ro/produse/0201692>

Insulating sleeve, color: yellow



PTRVB 4-FI /BK - Potential distributors

3270158

<https://www.phoenixcontact.com/ro/produse/3270158>

MPS-IH GN - Insulating sleeve

0201702

<https://www.phoenixcontact.com/ro/produse/0201702>

Insulating sleeve, color: green



MPS-IH GY - Insulating sleeve

0201728

<https://www.phoenixcontact.com/ro/produse/0201728>

Insulating sleeve, color: gray



PTRVB 4-FI /BK - Potential distributors

3270158

<https://www.phoenixcontact.com/ro/produce/3270158>



MPS-IH BK - Insulating sleeve

0201731

<https://www.phoenixcontact.com/ro/produce/0201731>

Insulating sleeve, color: black



ST-BW 0 - Actuation tool

1200135

<https://www.phoenixcontact.com/ro/produce/1200135>

Actuation tool, for all 1.5 mm² spring cages from PT 1,5/S and FT 1,5/S



Phoenix Contact 2024 © - Toate drepturile rezervate
<https://www.phoenixcontact.com>

PHOENIX CONTACT România
Splaiul Unirii 165 Timpuri Noi Square TNO1, Etaj 1
Bucuresti 030133
+40 21 350 88 12 - 3
sales.ro@phoenixcontact.com