

M12 plug angled 5-pole screw terminal max. 0.75 mm² A-encoded maximal 4 A



General technical data		
ampacity per pin maximum	A	4
operating voltage maximum	V	60
surge voltage resistance rated value	kV	0.8
Mechanical data		
type of connection technology		Screw terminals
connector type		Pin
type of cable outlet		angled
number of poles		5
connectable conductor cross-section for flexible conductor maximum	mm ²	0.75
diameter of inlet opening	mm	4 ... 6
material		
• of connector fixed part		Polyamide
• of the enclosure		Zinc diecast, nickel-plated
depth	mm	20
height	mm	41
width	mm	40
mechanical service life (mating cycles)		100
type of plug interlock		M12 x 1 thread
Ambient conditions		
ambient temperature		
• during storage	°C	-40 ... +85
• during operation	°C	-40 ... +85
protection class IP		IP67
chemical resistance		
• to mineral oil		conditional, must be checked relative to the application
• to water		conditional, must be checked relative to the application
• to grease		conditional, must be checked relative to the application
degree of pollution		3
Certificates/ approvals		
certificate of suitability		
• CSA approval		No
• RoHS conformity		Yes
• UL approval		No
• CCC		No
• IEC approval		Yes
• cUL approval		Yes
• C-Tick		No

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RK1902-4DA00-5AA0>

Cax online generator

<https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RK1902-4DA00-5AA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RK1902-4DA00-5AA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RK1902-4DA00-5AA0&lang=en

last modified:

4/2/2025 