



Product features and key data

Luminaire colour	RAL9006 White aluminium
Wiring	7LV
Ingress Protection (IP) rating	IP20
Protection class	I
Net length	2.212,50 mm
Net width	63 mm
Net height	41,40 mm
Weight	2,6 kg

Available accessories

Material	Description
 07690TL Luminaire Support Bracket 2196600	Luminaire support bracket (1 pair), sheet steel, galvanised.
 E04 Kette glzvz (20m) 2343400	Chain bright zinc-plated (20 m).
 A01SX/1500 2230700	Wire suspension with fixing clip.
 A01KX/1500 2230100	Chain suspension consisting of link chain, bright zinc-plated, length 1500 mm, with turnbuckle and suspension clamp E03KX.
 A01DSX/1500 2229600	Decorative wire suspension with suspension clip.
 E03KX 2342800	Suspension clamp for chain mounting.
 E03SX 2343200	Suspension clamp for fixing to steel wire.
 07690LHI Cable Holder 10pcs 2195300	Cable restraint for cable routing in trunking with through-wiring.
 D01X 2321200	Fixing clip for direct ceiling surface-mounting.
 07690LHA Cable Holder 2195200	Outer cable restraint.

	07690SK Female Connector 2195900	Female connector for ribbon cable wiring. 7-pole, for electrical contact of ribbon cables 07690/5LV/46m and 07690/7LV/46m.
	07690VV Wiring Connector 2197300	Wiring connector, 7-pole plug socket pair
	07690TO 2196700	Female connectors, for electrical contact of single wires. 5-pole, for tool-free electrical connection between single-core cables subsequently integrated into trunking and gear trays
	E03SKX 6188900	Suspension clamp for chain mounting. Height-adjustable, flexible version.
	A01SXVA 6817000	1 piece. Wire suspension with fixing clip
	07650 Flex con-cab 3pol 6912100	Flexible connection cable for E-Line LED gear tray.
	07650 Flex con-cab 5pol 6912200	Flexible connection cable for E-Line LED gear tray.
	07650 Ks 03 7260600	End cap for terminating an E-Line 7651 continuous line application IP20.
	A01DSX/3000 7234300	1 piece. Decorative wire suspension with suspension clip. 3000 mm
	A01DSX/5000 7234400	1 piece. Decorative wire suspension with suspension clip, 5000 mm
	A01SKX/1500 7234500	1 piece. {Reference (Object) not found: tb1848822583891}
	A01SX/5000 7234600	1 piece. Wire suspension with fixing clip, 5000 mm
	07650 BL L225 03 7259300	Blank cover for E-Line 7651 continuous line system. PVC. Colour silver gray (similar to RAL 9006). Length 2211,5 mm.
	07650 BL L187 03 7259400	Blank cover for E-Line 7651 continuous line system. PVC. Colour silver gray (similar to RAL 9006). Length 1843 mm.
	07650 BL L150 03 7259500	Blank cover for E-Line 7651 continuous line system. PVC. Colour silver gray (similar to RAL 9006). Length 1474 mm.
	07650 BL L112 03 7259600	Blank cover for E-Line 7651 continuous line system. PVC. Colour silver gray (similar to RAL 9006). Length 1105,5 mm.
	07650 BL L75 03 7259700	Blank cover for E-Line 7651 continuous line system. PVC. Colour silver gray (similar to RAL 9006). Length 736,5 mm.
	07650 BL L37 03 7259800	Blank cover for E-Line 7651 continuous line system. PVC. Colour silver gray (similar to RAL 9006). Length 368 mm.
	07650 BL-M L112 03 7219500	Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour silver gray (similar to RAL 9006). Length 1105,5 mm.
	07650 BL-M L37 03 7219800	Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour silver gray (similar to RAL 9006). Length 368 mm.

	07650 BL-M L75 03 7220100	Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour silver gray (similar to RAL 9006). Length 737 mm.
	07650 BL-M L187 03 7220400	Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour silver gray (similar to RAL 9006). Length 1842,5 mm.
	07650 BL-M L150 03 7223000	Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour silver gray (similar to RAL 9006). Length 1474 mm.
	07650 BL-M L225 03 7223100	Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour silver gray (similar to RAL 9006). Length 2211 mm.
	07650 BL-M 5-pol L37 03 7225600	Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour silver gray (similar to RAL 9006). Length 368 mm.
	07650 BL-M 5-pol L75 03 7225700	Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour silver gray (similar to RAL 9006). Length 737 mm.
	07650 BL-M 5-pol L112 03 7225800	Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour silver gray (similar to RAL 9006). Length 1105,5 mm.
	07650 BL-M 5-pol L150 03 7225900	Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour silver gray (similar to RAL 9006). Length 1474 mm.
	07650 BL-M 5-pol L187 03 7226000	Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour silver gray (similar to RAL 9006). Length 1842,5 mm.
	07650 BL-M 5-pol L225 03 7226100	Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour silver gray (similar to RAL 9006). Length 2211 mm.
	07650 L150 7+7LV E 150 01 7274200	Trunking for E-Line 7651 continuous line single luminaires or continuous line terminations. Length of the trunking: 1475 mm. Surface coated white. With 7-core through-wiring for segmenting circuits and supplementary 7-core through-wiring for additional emergency light or light management uses.
	07650 L-Connector 03 7508700	Connector for L-shaped continuous line applications. Colour silver gray (similar to RAL 9006). Dimensions (L x W): 362 mm x 362 mm.
	07650 T-Connector 03 7509000	Connector for T-shaped continuous line applications. Colour silver gray (similar to RAL 9006). Dimensions (L x W): 659 mm x 362 mm.
	07650 X-Connector 03 7509300	Connector for X-shaped continuous line applications. Colour silver gray (similar to RAL 9006). Dimensions (L x W): 659 mm x 659 mm.
	07650 BL L5 03 7688400	Blank cover for E-Line 7651 continuous line system. PVC. Colour silver gray (similar to RAL 9006). Length 55 mm.
	A01DSXOE/1500 7694900	Decorative wire suspension with stainless steel suspension clip, galvanised steel wire (Ø 1.5 mm) and eyelet. For E-Line 7651 continuous line system.
	A01DSXOE/3000 7695000	Decorative wire suspension with stainless steel suspension clip, galvanised steel wire (Ø 1.5 mm) and eyelet. For E-Line 7651 continuous line system.
	A01DSXOE/6000 7695100	Decorative wire suspension with stainless steel suspension clip, galvanised steel wire (Ø 1.5 mm) and eyelet. For E-Line 7651 continuous line system.
	07650IP BL-M 5-pol L37 03 7786400	Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour silver gray (similar to RAL 9006). Length 368 mm.
	07650IP BL-M 5-pol L75 03 7786500	Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour silver gray (similar to RAL 9006). Length 737 mm.

	07650IP BL-M 5-pol L112 03 7786600	Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour silver gray (similar to RAL 9006). Length 1106 mm.
	07650IP BL-M 5-pol L150 03 7786700	Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour silver gray (similar to RAL 9006). Length 1474 mm.
	07650IP BL-M 5-pol L187 03 7786800	Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour silver gray (similar to RAL 9006). Length 1843 mm.
	07650IP BL-M 5-pol L225 03 7786900	Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour silver gray (similar to RAL 9006). Length 2211 mm.
	07650IP BL-M L112 03 7787700	Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour silver gray (similar to RAL 9006). Length 1106 mm.
	07650IP BL-M L37 03 7788000	Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour silver gray (similar to RAL 9006). Length 368 mm.
	07650IP BL-M L75 03 7788300	Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour silver gray (similar to RAL 9006). Length 737 mm.
	07650IP BL-M L187 03 7788600	Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour silver gray (similar to RAL 9006). Length 1843 mm.
	07650IP BL-M L150 03 7789000	Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour silver gray (similar to RAL 9006). Length 1474 mm.
	07650IP BL-M L225 03 7789100	Blank cover for E-Line 7651 continuous line system. Made of sheet steel. Colour silver gray (similar to RAL 9006). Length 2211 mm.
	07650IP Ks 03 7789700	End cap for terminating an E-Line 7651 continuous line application IP50.
	07650IP BL L112 03 7712100	Blank cover for E-Line 7651 continuous line system. PVC. Colour silver gray (similar to RAL 9006). Length 1105,4 mm.
	07650IP BL L150 03 7712400	Blank cover for E-Line 7651 continuous line system. PVC. Colour silver gray (similar to RAL 9006). Length 1474 mm.
	07650IP BL L187 03 7712700	Blank cover for E-Line 7651 continuous line system. PVC. Colour silver gray (similar to RAL 9006). Length 1842,8 mm.
	07650IP BL L225 03 7713000	Blank cover for E-Line 7651 continuous line system. PVC. Colour silver gray (similar to RAL 9006). Length 2211,2 mm.
	07650IP BL L37 03 7713300	Blank cover for E-Line 7651 continuous line system. PVC. Colour silver gray (similar to RAL 9006). Length 368 mm.
	07650IP BL L75 03 7713600	Blank cover for E-Line 7651 continuous line system. PVC. Colour silver gray (similar to RAL 9006). Length 736,5 mm.
	07650IP BL L5 03 8362600	Blank cover for E-Line 7651 continuous line system. PVC. Colour silver gray (similar to RAL 9006). Length 54,5 mm.
	07650IP BL L153 03 8362900	Blank cover for E-Line 7651 continuous line system. PVC. Colour silver gray (similar to RAL 9006). Length 1530 mm.
	07650 BL L153 03 8363100	Blank cover for E-Line 7651 continuous line system. PVC. Colour silver gray (similar to RAL 9006). Length 1529 mm.


A01SX/3000
 3664499

1 piece. Wire suspension with fixing clip, 3000 mm


D01X m Caddy-Clip 01
 4068899

Fixing clamp with caddy clip for quick mounting on suitable profile steel without drilling. The quantity and mounting positions depend on the system ceiling, luminaire load and luminaire arrangement. Observe the specifications of the ceiling manufacturer.


D01X m Caddy-Clip
 4068999

Fixing clamp with caddy clip for quick mounting on suitable profile steel without drilling. The quantity and mounting positions depend on the system ceiling, luminaire load and luminaire arrangement. Observe the specifications of the ceiling manufacturer.


07690VS 2,5² L100
 6822100

Connection cable with 7-pole plug, 100 mm.


07690/1LV 2.5² L300
 6822200

Connection cable for central infeed of the E-Line trunking profiles.


07690VS
 6822300

Plug for power feed, 7-pole, fixed.

Offer text

Trunking for E-Line 7651 continuous line single luminaires or continuous line terminations. Also suitable for continuous line applications in combination with a separately ordered continuous line coupler. Length of the trunking: 2212,5 mm. With 7-conductor through-wiring. Cable cross-section 2.5 mm². With 6 female connectors for tool-free, electrical connection of the gear trays at 370 mm intervals. With 7-pole plug/socket pair for rapid electrical connection and termination at ends with protection against accidental contact. The heat-resistant through-wiring is factory-completed with all necessary components. All connections are designed for fast connection and are with reverse polarity protection. The electrical feed can be made without accessories through an upper knockout (M20/PG13.5). The trunking body is made of hot-dip galvanised sheet steel. Surface coated silver-grey.