



DELTA i-system NEMA socket outlet with spring flap titanium white 2-pole+E  
NEMA 5-20 R 125V 20 A

Model	
product brand name	DELTA
product designation	Socket outlet
design of the product	NEMA
cover version	central plate
design of the special power supply unit	without special current supply
design of the socket according to VDE 0620 for severe conditions	No
design of the phase tap	No
General technical data	
marking of socket outlet	without imprint
mounting type	fixing with screw
surface processing	others
material	thermoplastic
Supply voltage	
operating voltage rated value	125 V
supply voltage frequency rated value	50 Hz
Protection class	
protection class IP	IP20
Main circuit	
operational current rated value	20 A
Appearance	
RAL color number (similar)	9 010
color	titanium white
Product details	
product component	
• ejection equipment	No
• labeling field	No
• increased touch protection	No
• residual current device	No
• miniature fuse	No
• integrated functional lighting	No
• integrated light source	No
• integrated orientation lighting	No
• hinged lid	Yes
product feature lockable	No
product feature halogen-free	Yes
product feature transparent	No
Product function	

<b>product function</b>	
• socket selectable	No
• overvoltage protection	No
<b>Number</b>	
number of units	1
number of sockets switchable	0
<b>Connections</b>	
arrangement of contacts diagonal	No
type of electrical connection	plug terminal
<b>Mechanical Design</b>	
height	70 mm
width	70 mm
depth	45 mm
fastening method	flush mounting
<b>Net Weight</b>	96 g
material of the enclosure	plastic
<b>Approvals Certificates</b>	
Environmental Product Declaration	
• global warming potential [CO2 eq] / during manufacturing	0.284 kg
• global warming potential [CO2 eq] / during operation	4.48 kg
• global warming potential [CO2 eq] / after end of life	0.0001 kg
• global warming potential [CO2 eq] / total	4.77 kg
<b>Environment</b>	<b>General Product Approval</b>
	<b>other</b>



[Environmental Con-  
firmations](#)



EG-Konf.



VDE



[Confirmation](#)

#### Further information

##### Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

##### Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

##### Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/lowvoltage/catalogs>

##### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5UB1535>

##### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5UB1535>

##### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[https://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5UB1535](https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5UB1535)

##### CAX-Online-Generator


<https://www.siemens.com/cax>

##### Tender specifications

<https://www.siemens.com/specifications>

##### Characteristic curves

[https://curves.simaris.siemens.com/curves/<mmp\\_prod\\_noCOMP="HAUPT"></mmp\\_prod\\_no>](https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP=)



last modified:

8/19/2025 

