



Unitate De Franare Rezistiva - 16 Ohmi - 1.1 Kw - Ip20

VW3A7733

Principale

gama de produse	Altivar
Compatibilitate gama	Altivar Machine ATV320 Altivar Process ATV900 Altivar Machine ATV340
Tip produs sau componenta	Rezistenta de rupere
valoare ohmica	16 Ohm
[Ue] tensiune nominala de functionare	24 V c.c. 250 V c.a.

Suplimentare

compatibilitate produs	Variable speed drive ATV930 wall mount 18,5 kW 380...480 V light cycle Variable speed drive ATV930 wall mount 22 kW 380...480 V light cycle Variable speed drive ATV930 wall mount 30 kW 380...480 V light cycle Variable speed drive ATV930 wall mount 5,5 kW 200...240 V light cycle Variable speed drive ATV930 wall mount 7,5 kW 200...240 V light cycle Variable speed drive ATV950 wall mount 18,5 kW 380...480 V light cycle Variable speed drive ATV950 wall mount 22 kW 380...480 V light cycle Variable speed drive ATV950 wall mount 30 kW 380...480 V light cycle Variable speed drive ATV930 wall mount 5,5 kW 200...240 V medium cycle Variable speed drive ATV930 wall mount 7,5 kW 200...240 V medium cycle Variable speed drive ATV340 15 kW 380...480 V light cycle Variable speed drive ATV340 18 kW 380...480 V light cycle Variable speed drive ATV340 22 kW 380...480 V light cycle Variable speed drive ATV320 4 kW 200...240 V Variable speed drive ATV320 5,5 kW 200...240 V Variable speed drive ATV320 15 kW 380...480 V Variable speed drive ATV930 22 kW 500...690 V light cycle Variable speed drive ATV930 30 kW 500...690 V light cycle Variable speed drive ATV930 37 kW 500...690 V light cycle Variable speed drive ATV930 30 CP 600 V light cycle Variable speed drive ATV930 40 CP 600 V light cycle Variable speed drive ATV930 50 CP 600 V light cycle
ciclu de utilizare	Light cycle (pentru sarcini grele) <0,8 s braking with 150 % braking torque for a 40 s cycle Light cycle (serviciu normal) <0,8 s braking with 120 % braking torque for a 40 s cycle Medium cycle (serviciu normal) <4 s braking with 135 % braking torque for a 40 s cycle Medium cycle (pentru sarcini grele) <4 s braking with 165 % braking torque for a 40 s cycle
putere medie disponibila	1,1 kW la 50 °C
conexiune electrica	borna, capacitate conexiune: <= 10 mm² / AWG 8 pentru variator borna, capacitate conexiune: <= 2.5 mm² / AWG 12 pentru termostat
tip de protectie	Protectie termica prin comutator de actionare sau control al temperaturii la 120 °C
latime	190 mm
inaltime	570 mm
adancime	180 mm

Declinare de responsabilitate: Această documentație nu se substituie și nu trebuie utilizată pentru stabilirea adecvării sau fiabilității acestor produse pentru aplicații utilizator

greutate produs	3,8 kg
-----------------	--------

Mediu

grad de protectie IP	IP20
temperatura ambietala pentru depozitare	-25...70 °C
temperatura ambientala de functionare	0...50 °C

Unitati de ambalare

Unitate de masura pentru prima forma de impachetare	PCE
Numar unitati in prima forma de impachetare	1
Inaltime prima forma de impachetare	20,600 cm
Latime prima forma de impachetare	25,200 cm
Lungime prima forma de impachetare	58,200 cm
Greutate prima forma de impachetare	4,434 kg
Unitate de masura pentru a doua forma de impachetare	P06
Numar unitati in a doua forma de impachetare	8
Inaltime a doua forma de impachetare	75,000 cm
Latime a doua forma de impachetare	60,000 cm
Lungime a doua forma de impachetare	80,000 cm
Greutate a doua forma de impachetare	44,164 kg

Garanție contractuală

Garantie	18 luni
----------	---------



Environmental Data

Schneider Electric isi propune sa atinga nivelul Net Zero pana in 2050 prin parteneriate la nivelul lantului de aprovizionare, materiale cu impact mai redus si circularitate, prin campania „Use Better, Use Longer, Use Again” pentru a extinde durata de viata a produselor si reciclabilitatea.

[Environmental Data explicate >](#)

[Cum evaluam sustenabilitatea produselor >](#)

Use Better

Materiale si ambalare	
Pachet cu carton reciclabil	Nu
Ambalaj fara plastic	Nu
Directiva RoHS UE	Conformitate proactiva (Produs in afara domeniului de aplicare a EU RoHS)
Regulamentul REACH	Declaratia REACH


Use Again

Reambalare si refabricare	
Preluare la sfarsitul duratei de viata	No

Dimensions Drawings

Dimensions

Right Side and Front View



Dimensions in mm

A	B	C	A1	C1	Ø
190	180	570	170	380	6.6 x 9

Dimensions in in.


A	B	C	A1	C1	Ø
7.48	7.09	22.44	6.69	14.96	0.26 x 0.35

Mounting and Clearance

Mounting and Clearance




(1) Braking resistor



Connections and Schema

Recommended Schema

1 Braking Resistor




A1 : Drive or external braking unit

A2 : Braking resistor

PA, PB : Bus DC

2 Braking Resistors



A1 : Drive or external braking unit

A2 : Braking resistor

PA, PB : Bus DC