

SIMATIC HMI, KTP700 Basic DP, Basic Panel, Key/touch operation, 7" TFT display, 65536 colors, PROFIBUS interface, configurable as of WinCC Basic V13/STEP 7 Basic V13, contains open-source software, which is provided free of charge see enclosed CD



| General information                                                   |                                          |
|-----------------------------------------------------------------------|------------------------------------------|
| Product type designation                                              | KTP700 Basic color DP                    |
| Display                                                               |                                          |
| Design of display                                                     | TFT widescreen display, LED backlighting |
| Screen diagonal                                                       | 7 in                                     |
| Display width                                                         | 154.1 mm                                 |
| Display height                                                        | 85.9 mm                                  |
| Number of colors                                                      | 65 536                                   |
| Resolution (pixels)                                                   |                                          |
| • Horizontal image resolution                                         | 800 pixel                                |
| • Vertical image resolution                                           | 480 pixel                                |
| Backlighting                                                          |                                          |
| • MTBF backlighting (at 25 °C)                                        | 20 000 h                                 |
| • Backlight dimmable                                                  | Yes                                      |
| Control elements                                                      |                                          |
| Keyboard fonts                                                        |                                          |
| • Function keys                                                       |                                          |
| — Number of function keys                                             | 8                                        |
| — Number of function keys with LEDs                                   | 0                                        |
| • Keys with LED                                                       | No                                       |
| • System keys                                                         | No                                       |
| • Numeric keyboard                                                    | Yes; Onscreen keyboard                   |
| • alphanumeric keyboard                                               | Yes; Onscreen keyboard                   |
| Touch operation                                                       |                                          |
| • Design as touch screen                                              | Yes; Analog-resistive                    |
| Installation type/mounting                                            |                                          |
| Mounting position                                                     | vertical                                 |
| Mounting in portrait format possible                                  | Yes                                      |
| Mounting in landscape format possible                                 | Yes                                      |
| maximum permissible angle of inclination without external ventilation | 35°                                      |
| Supply voltage                                                        |                                          |
| Type of supply voltage                                                | DC                                       |
| Rated value (DC)                                                      | 24 V                                     |
| permissible range, lower limit (DC)                                   | 19.2 V                                   |
| permissible range, upper limit (DC)                                   | 28.8 V                                   |
| Input current                                                         |                                          |
| Current consumption (rated value)                                     | 230 mA                                   |
| Starting current inrush I <sub>st</sub>                               | 0.2 A <sup>2</sup> ·s                    |

|                                                  |                                         |
|--------------------------------------------------|-----------------------------------------|
| <b>Power</b>                                     |                                         |
| Active power input, typ.                         | 5.5 W                                   |
| <b>Processor</b>                                 |                                         |
| Processor type                                   | ARM                                     |
| <b>Memory</b>                                    |                                         |
| Flash                                            | Yes                                     |
| RAM                                              | Yes                                     |
| Memory available for user data                   | 10 Mbyte                                |
| <b>Type of output</b>                            |                                         |
| Acoustics                                        |                                         |
| • Buzzer                                         | Yes                                     |
| • Speaker                                        | No                                      |
| <b>Time of day</b>                               |                                         |
| Clock                                            |                                         |
| • Hardware clock (real-time)                     | Yes                                     |
| • Software clock                                 | Yes                                     |
| • retentive                                      | Yes; Back-up duration typically 6 weeks |
| • synchronizable                                 | Yes                                     |
| <b>Interfaces</b>                                |                                         |
| Number of industrial Ethernet interfaces         | 0                                       |
| Number of RS 485 interfaces                      | 1                                       |
| Number of RS 422 interfaces                      | 1; together with RS 485                 |
| Number of RS 232 interfaces                      | 0; with optional adapter                |
| Number of USB interfaces                         | 1; Up to 16 GB                          |
| Number of 20 mA interfaces (TTY)                 | 0                                       |
| Number of parallel interfaces                    | 0                                       |
| Number of other interfaces                       | 0                                       |
| Number of SD card slots                          | 0                                       |
| With software interfaces                         | No                                      |
| <b>Industrial Ethernet</b>                       |                                         |
| • Industrial Ethernet status LED                 | 0                                       |
| <b>Protocols</b>                                 |                                         |
| PROFINET                                         | No                                      |
| Supports protocol for PROFINET IO                | No                                      |
| IRT                                              | No                                      |
| PROFIBUS                                         | Yes                                     |
| EtherNet/IP                                      | No                                      |
| MPI                                              | Yes                                     |
| <b>Protocols (Ethernet)</b>                      |                                         |
| • TCP/IP                                         | No                                      |
| • DHCP                                           | No                                      |
| • SNMP                                           | No                                      |
| • DCP                                            | No                                      |
| • LLDP                                           | No                                      |
| <b>WEB characteristics</b>                       |                                         |
| • HTTP                                           | No                                      |
| • HTML                                           | No                                      |
| <b>Redundancy mode</b>                           |                                         |
| Media redundancy                                 |                                         |
| — MRP                                            | No                                      |
| <b>Further protocols</b>                         |                                         |
| • CAN                                            | No                                      |
| • MODBUS                                         | Yes; Modicon (MODBUS RTU)               |
| <b>Interrupts/diagnostics/status information</b> |                                         |
| <b>Diagnoses</b>                                 |                                         |
| • Diagnostic information readable                | No                                      |
| <b>EMC</b>                                       |                                         |
| Emission of radio interference acc. to EN 55 011 |                                         |

|                                                                |           |
|----------------------------------------------------------------|-----------|
| • Limit class A, for use in industrial areas                   | Yes       |
| • Limit class B, for use in residential areas                  | No        |
| <b>Degree and class of protection</b>                          |           |
| IP (at the front)                                              | IP65      |
| IP (rear)                                                      | IP20      |
| NEMA (front)                                                   |           |
| • Enclosure Type 4 at the front                                | Yes       |
| • Enclosure Type 4x at the front                               | Yes       |
| <b>Standards, approvals, certificates</b>                      |           |
| CE mark                                                        | Yes       |
| cULus                                                          | Yes       |
| RCM (formerly C-TICK)                                          | Yes       |
| KC approval                                                    | Yes       |
| <b>Ecological footprint</b>                                    |           |
| • environmental product declaration                            | Yes       |
| <b>Global warming potential</b>                                |           |
| — global warming potential, (total) [CO2 eq]                   | 85 kg     |
| — global warming potential, (during production) [CO2 eq]       | 26.2 kg   |
| — global warming potential, (during operation) [CO2 eq]        | 59.2 kg   |
| — global warming potential, (after end of life cycle) [CO2 eq] | -0.682 kg |
| <b>Use in hazardous areas</b>                                  |           |
| • ATEX Zone 2                                                  | No        |
| • ATEX Zone 22                                                 | No        |
| • IECEx Zone 2                                                 | No        |
| • IECEx Zone 22                                                | No        |
| • cULus Class I Zone 1                                         | No        |
| • cULus Class I Zone 2, Division 2                             | No        |
| • FM Class I Division 2                                        | No        |
| <b>Marine approval</b>                                         |           |
| • Germanischer Lloyd (GL)                                      | Yes       |
| • American Bureau of Shipping (ABS)                            | Yes       |
| • Bureau Veritas (BV)                                          | Yes       |
| • Det Norske Veritas (DNV)                                     | Yes       |
| • Lloyds Register of Shipping (LRS)                            | Yes       |
| • Nippon Kaiji Kyokai (Class NK)                               | Yes       |
| • Polski Rejestr Statkow (PRS)                                 | No        |
| • Chinese Classification Society (CCS)                         | No        |
| <b>Ambient conditions</b>                                      |           |
| Suited for indoor use                                          | Yes       |
| Suited for outdoor use                                         | No        |
| <b>Ambient temperature during operation</b>                    |           |
| Operation (vertical installation)                              |           |
| — For vertical installation, min.                              | 0 °C      |
| — For vertical installation, max.                              | 50 °C     |
| Operation (max. tilt angle)                                    |           |
| — At maximum tilt angle, min.                                  | 0 °C      |
| — At maximum tilt angle, max.                                  | 40 °C     |
| Operation (vertical installation, portrait format)             |           |
| — For vertical installation, min.                              | 0 °C      |
| — For vertical installation, max.                              | 40 °C     |
| Operation (max. tilt angle, portrait format)                   |           |
| — At maximum tilt angle, min.                                  | 0 °C      |
| — At maximum tilt angle, max.                                  | 35 °C     |
| <b>Ambient temperature during storage/transportation</b>       |           |
| • min.                                                         | -20 °C    |
| • max.                                                         | 60 °C     |
| <b>Relative humidity</b>                                       |           |

|                                                              |                                                               |
|--------------------------------------------------------------|---------------------------------------------------------------|
| • Operation, max.                                            | 90 %; no condensation                                         |
| <b>Operating systems</b>                                     |                                                               |
| proprietary                                                  | Yes                                                           |
| <b>pre-installed operating system</b>                        |                                                               |
| • Windows CE                                                 | No                                                            |
| <b>Configuration</b>                                         |                                                               |
| Message indicator                                            | Yes                                                           |
| Alarm system (incl. buffer and acknowledgment)               | Yes                                                           |
| Process value display (output)                               | Yes                                                           |
| Process value default (input) possible                       | Yes                                                           |
| Recipe management                                            | Yes                                                           |
| <b>Configuration software</b>                                |                                                               |
| • STEP 7 Basic (TIA Portal)                                  | Yes; via integrated WinCC Basic (TIA Portal)                  |
| • STEP 7 Professional (TIA Portal)                           | Yes; via integrated WinCC Basic (TIA Portal)                  |
| • WinCC flexible Compact                                     | No                                                            |
| • WinCC flexible Standard                                    | No                                                            |
| • WinCC flexible Advanced                                    | No                                                            |
| • WinCC Basic (TIA Portal)                                   | Yes                                                           |
| • WinCC Comfort (TIA Portal)                                 | Yes                                                           |
| • WinCC Advanced (TIA Portal)                                | Yes                                                           |
| • WinCC Professional (TIA Portal)                            | Yes                                                           |
| <b>Languages</b>                                             |                                                               |
| <b>Online languages</b>                                      |                                                               |
| • Number of online/runtime languages                         | 10                                                            |
| <b>Project languages</b>                                     |                                                               |
| • Languages per project                                      | 32                                                            |
| <b>Functionality under WinCC (TIA Portal)</b>                |                                                               |
| Libraries                                                    | Yes                                                           |
| <b>Applications/options</b>                                  |                                                               |
| • Web browser                                                | No                                                            |
| • SIMATIC WinCC Sm@rtServer                                  | No                                                            |
| Number of Visual Basic Scripts                               | No                                                            |
| <b>Task planner</b>                                          |                                                               |
| • time-controlled                                            | No                                                            |
| • task-controlled                                            | Yes                                                           |
| <b>Help system</b>                                           |                                                               |
| • Number of characters per info text                         | 500                                                           |
| <b>Message system</b>                                        |                                                               |
| • Number of alarm classes                                    | 32                                                            |
| • Bit messages                                               |                                                               |
| — Number of bit messages                                     | 1 000                                                         |
| • Analog messages                                            |                                                               |
| — Number of analog messages                                  | 25                                                            |
| • S7 alarm number procedure                                  | No                                                            |
| • System messages HMI                                        | Yes                                                           |
| • System event, more (SIMATIC S7, SINUMERIK, SIMOTION, ... ) | Yes; System message buffer of the SIMATIC S7-1200 and S7-1500 |
| • Number of characters per message                           | 80                                                            |
| • Number of process values per message                       | 8                                                             |
| • Acknowledgment groups                                      | Yes                                                           |
| • Message indicator                                          | Yes                                                           |
| • Message buffer                                             |                                                               |
| — Number of entries                                          | 256                                                           |
| — Circulating buffer                                         | Yes                                                           |
| — retentive                                                  | Yes                                                           |
| — maintenance-free                                           | Yes                                                           |
| <b>Recipe management</b>                                     |                                                               |
| • Number of recipes                                          | 50                                                            |
| • Data records per recipe                                    | 100                                                           |

|                                        |                                                               |
|----------------------------------------|---------------------------------------------------------------|
| • Entries per data record              | 100                                                           |
| • Size of internal recipe memory       | 256 kbyte                                                     |
| • Recipe memory expandable             | No                                                            |
| <b>Variables</b>                       |                                                               |
| • Number of variables per device       | 800                                                           |
| • Number of variables per screen       | 100                                                           |
| • Limit values                         | Yes                                                           |
| • Multiplexing                         | Yes                                                           |
| • Structures                           | No                                                            |
| • Arrays                               | Yes                                                           |
| <b>Images</b>                          |                                                               |
| • Number of configurable images        | 250                                                           |
| • Permanent window/default             | Yes                                                           |
| • Global image                         | Yes                                                           |
| • Pop-up images                        | No                                                            |
| • Slide-in images                      | No                                                            |
| • Image selection by PLC               | Yes                                                           |
| • Image number in the PLC              | Yes                                                           |
| <b>Image objects</b>                   |                                                               |
| • Number of objects per image          | 100                                                           |
| • Text fields                          | Yes                                                           |
| • I/O fields                           | Yes                                                           |
| • Graphic I/O fields (graphics list)   | Yes                                                           |
| • Symbolic I/O fields (text list)      | Yes                                                           |
| • Date/time fields                     | Yes                                                           |
| • Switches                             | Yes                                                           |
| • Buttons                              | Yes                                                           |
| • Graphic display                      | Yes                                                           |
| • Icons                                | Yes                                                           |
| • Geometric objects                    | Yes                                                           |
| <b>Complex image objects</b>           |                                                               |
| • Number of complex objects per screen | 10                                                            |
| • Alarm view                           | Yes                                                           |
| • Trend view                           | Yes                                                           |
| • User view                            | Yes                                                           |
| • Status/control                       | No                                                            |
| • Sm@rtClient view                     | No                                                            |
| • Recipe view                          | Yes                                                           |
| • f(x) trend view                      | No                                                            |
| • System diagnostics view              | Yes; System message buffer of the SIMATIC S7-1200 and S7-1500 |
| • Media Player                         | No                                                            |
| • HTML browser                         | No                                                            |
| • PDF display                          | No                                                            |
| • IP camera display                    | No                                                            |
| • Bar graphs                           | Yes                                                           |
| • Sliders                              | No                                                            |
| • Pointer instruments                  | No                                                            |
| • Analog/digital clock                 | No                                                            |
| <b>Lists</b>                           |                                                               |
| • Number of text lists per project     | 300                                                           |
| • Number of entries per text list      | 100                                                           |
| • Number of graphics lists per project | 100                                                           |
| • Number of entries per graphics list  | 100                                                           |
| <b>Archiving</b>                       |                                                               |
| • Number of archives per device        | 2; One message and one process value archive                  |
| • Number of entries per archive        | 10 000                                                        |
| • Message archive                      | Yes                                                           |
| • Process value archive                | Yes                                                           |
| • Archiving methods                    |                                                               |

|                                                        |                            |
|--------------------------------------------------------|----------------------------|
| — Sequential archive                                   | Yes                        |
| — Short-term archive                                   | Yes                        |
| • Memory location                                      |                            |
| — Memory card                                          | No                         |
| — USB memory                                           | Yes                        |
| — Ethernet                                             | No                         |
| • Data storage format                                  |                            |
| — CSV                                                  | No                         |
| — TXT                                                  | Yes                        |
| — RDB                                                  | No                         |
| <b>Security</b>                                        |                            |
| • Number of user groups                                | 50                         |
| • Number of user rights                                | 32                         |
| • Number of users                                      | 50                         |
| • Password export/import                               | Yes                        |
| • SIMATIC Logon                                        | No                         |
| <b>Character sets</b>                                  |                            |
| • Keyboard fonts                                       |                            |
| — US English                                           | Yes                        |
| <b>Transfer (upload/download)</b>                      |                            |
| • MPI/PROFIBUS DP                                      | Yes                        |
| • USB                                                  | No                         |
| • Ethernet                                             | No                         |
| • using external storage medium                        | Yes                        |
| <b>Process coupling</b>                                |                            |
| • S7-1200                                              | Yes                        |
| • S7-1500                                              | Yes                        |
| • S7-200                                               | Yes                        |
| • S7-300/400                                           | Yes                        |
| • LOGO!                                                | Yes                        |
| • WinAC                                                | Yes                        |
| • SINUMERIK                                            | Yes; No access to NCK data |
| • SIMOTION                                             | Yes                        |
| • Allen Bradley (EtherNet/IP)                          | No                         |
| • Allen Bradley (DF1)                                  | Yes                        |
| • Mitsubishi (MC TCP/IP)                               | No                         |
| • Mitsubishi (FX)                                      | Yes                        |
| • OMRON (FINS TCP)                                     | No                         |
| • OMRON (LINK/Multilink)                               | Yes                        |
| • Modicon (Modbus TCP/IP)                              | No                         |
| • Modicon (Modbus)                                     | Yes                        |
| <b>Service tools/configuration aids</b>                |                            |
| • Backup/Restore manually                              | Yes                        |
| • Backup/Restore automatically                         | No                         |
| • Simulation                                           | Yes                        |
| • Device switchover                                    | Yes                        |
| <b>Peripherals/Options</b>                             |                            |
| Printer                                                | No                         |
| SIMATIC HMI MM memory card: Multi Media Card           | No                         |
| SIMATIC HMI SD memory card: Secure Digital memory card | No                         |
| SIMATIC HMI CF memory card Compact Flash Card          | No                         |
| USB memory                                             | Yes                        |
| SIMATIC IPC USB Flashdrive (USB stick)                 | Yes                        |
| SIMATIC HMI USB stick                                  | Yes                        |
| <b>Mechanics/material</b>                              |                            |
| Enclosure material (front)                             |                            |
| • Plastic                                              | Yes                        |
| • Aluminum                                             | No                         |
| • Stainless steel                                      | No                         |

| Dimensions                 |        |
|----------------------------|--------|
| Width of the housing front | 214 mm |
| Height of housing front    | 158 mm |
| Mounting cutout, width     | 198 mm |
| Mounting cutout, height    | 142 mm |
| mounting depth             | 39 mm  |

| Weights                    |       |
|----------------------------|-------|
| Weight (without packaging) | 800 g |
| Weight (with packaging)    | 1 kg  |

| Classifications |        |         |                |
|-----------------|--------|---------|----------------|
|                 |        | Version | Classification |
|                 | eClass | 14      | 27-33-02-01    |
|                 | eClass | 12      | 27-33-02-01    |
|                 | eClass | 9.1     | 27-33-02-01    |
|                 | eClass | 9       | 27-33-02-01    |
|                 | eClass | 8       | 27-24-23-02    |
|                 | eClass | 7.1     | 27-24-23-02    |
|                 | eClass | 6       | 27-24-23-02    |
|                 | ETIM   | 10      | EC001412       |
|                 | ETIM   | 9       | EC001412       |
|                 | ETIM   | 8       | EC001412       |
|                 | ETIM   | 7       | EC001412       |
|                 | IDEA   | 4       | 6607           |
|                 | UNSPSC | 15      | 43-21-15-06    |

| Approvals / Certificates |  |
|--------------------------|--|
| General Product Approval |  |



Miscellaneous

Manufacturer Declaration



|                          |                      |
|--------------------------|----------------------|
| General Product Approval | Maritime application |
|--------------------------|----------------------|



NK / Nippon Kaiji Kyokai

|                      |             |
|----------------------|-------------|
| Maritime application | Environment |
|----------------------|-------------|

CCS (China Classification Society)

KR (Korean Register of Shipping)



last modified:

6/17/2025