

Fișă tehnică produs

Specificatii

Capace Borne Scurte, 4 Poli, Pentru Ins40, 250/Inv100, 250/Nsx100, 250



LV429516

Principale

Tip produs sau componenta	Short terminal shield
Compatibilitate gama	ComPacT noua generatie ComPacT NSX100 noua generatie ComPacT noua generatie ComPacT NSX160 noua generatie ComPacT noua generatie ComPacT NSX250 noua generatie Compact ComPact NSX100 Compact ComPact NSX160 Compact ComPact NSX250 ComPacT noua generatie ComPacT NSX CC noua generatie NSX100 cc ComPacT noua generatie ComPacT NSX CC noua generatie NSX160 cc ComPacT noua generatie ComPacT NSX CC noua generatie NSX250 cc Compact Compact NSX100 DC Compact Compact NSX160 DC Compact Compact NSX250 DC EasyPact EasyPact CVS100 EasyPact EasyPact CVS160 EasyPact EasyPact CVS250
tip de accesorii / piese separate	Accesorii de izolare
descriere poli	4P
Cantitate pe set	1

Suplimentare

pasul conexiunii	35 mm
grad de protectie IP	IP40 conforming to SR EN 60529
Compatibilitate produs	Circuit-breaker Plug-in base

Unitati de ambalare

Unitate de masura pentru prima forma de impachetare	PCE
Număr de produse in pachet	1
Inaltime prima forma de impachetare	3,500 cm
Latime prima forma de impachetare	8,000 cm
Lungime prima forma de impachetare	15,000 cm
Greutate colet(Lbs)	67,000 g
Unitate de masura pentru a doua forma de impachetare	S04
Numar unitati in a doua forma de impachetare	40
Inaltime a doua forma de impachetare	30,000 cm
Latime a doua forma de impachetare	40,000 cm
Lungime a doua forma de impachetare	60,000 cm

Greutate a doua forma de impachetare	3,420 kg
Unitate de masura pentru a treia forma de impachetare	P12
Numar unitati in a treia forma de impachetare	160
Inaltime a treia forma de impachetare	50,000 cm
Latime a treia forma de impachetare	80,000 cm
Lungime a treia forma de impachetare	120,000 cm
Greutate a treia forma de impachetare	24,880 kg

Garanție contractuală

Garantie (in luni)	18
--------------------	----

Schneider Electric isi propune sa atinga nivelul Net Zero pana in 2050 prin parteneriate la nivelul lantului de aprovizionare, materiale cu impact mai redus si circularitate, prin campania „Use Better, Use Longer, Use Again” pentru a extinde durata de viata a produselor si reciclabilitatea.

[Environmental Data explicate >](#)

[Cum evaluam sustenabilitatea produselor >](#)

Amprenta de mediu

Amprenta de carbon totala pe durata de viata	0.5 kg CO2 eq.
Amprenta de carbon a fazei de fabricație [A1–A3]	0.3 kg CO2 eq.
Amprenta de carbon a fazei de distribuție [A4]	0 kg CO2 eq.
Amprenta de carbon a fazei de instalare [A5]	0 kg CO2 eq.
Amprenta de carbon a fazei de utilizare [B2, B3, B4, B6]	0 kg CO2 eq.
Amprenta de carbon a fazei de sfârșit de viață [C1–C4]	0.1 kg CO2 eq.
Raport de mediu	Profilul ambiental al produsului

Use Better

Materiale si ambalare

Pachet cu carton reciclabil	Da
Ambalaj fara plastic	Nu
Directiva RoHS a UE	Conform
Regulamentul REACH	Referinta nu contine SVHC peste prag
Statut de indemn de halogen	Produsul contine halogeni peste pragurile admise
Nu contine PVC	Da
Nu contine silicon	Da

Use Longer

Prelungire durata de viata

Reparare	Nu
----------	----

Use Again

Reambalare si refabricare

Potentialul de reciclabilitate, in %	2
Profil circularitate	Nu sunt necesare operatii de reciclare speciale
Preluare la sfarsitul duratei de viata	Da

Offer Marketing Illustration

Product benefits / Features



ComPacT NSX

Technical Benefits

- Nominal current: 16 to 630 A and 9 breaking capacities for the 2 sizes of circuit breakers
- 1, 2, 3, and 4 pole versions available
- Large range of electronic and thermal-magnetic protections
- Plug and ready wiring system and communicating accessories
- Integrated earth leakage protection via MicroLogic Vigi (earth leakage circuit breaker - ELCB)
- Advanced trip unit with integrated power metering: I, U, P, E, THD, f, CosPhi

Offer Marketing Illustration

Product benefits / Features

ComPacT NSX

Moulded Case Circuit Breaker



Protection begins with prevention

Designed to prevent an electrical fire through integrated earth leakage protection with preventive maintenance thanks to its Everlink power connections.



Maximize power availability

By providing corrective, preventive, and predictive maintenance for asset management thanks to our advanced MicroLogic trip units.



Connectivity

Designed to connect to EcoStruxure Power, an IoT-connected architecture for improving every aspect of your power distribution system.

