


Fișă tehnică produs

Specificatii



Unitate de Franare Rezistiva, 60 Ohmi, 0.16kW, IP20

VW3A7731

Principale

gama de produse	Altivar
Compatibilitate gama	Altivar Machine ATV320 Altivar Machine ATV340 Easy Altivar 310 Altivar Process ATV900 Easy Altivar 310L
Tip produs sau componenta	Rezistenta de rupere
valoare ohmica	60 Ohm

Suplimentare

compatibilitate produs	Variable speed drive ATV930 wall mount 5,5 kW 380...480 V light cycle Variable speed drive ATV930 wall mount 7,5 kW 380...480 V light cycle Variable speed drive ATV930 wall mount 1,5 kW 200...240 V light cycle Variable speed drive ATV930 wall mount 2,2 kW 200...240 V light cycle Variable speed drive ATV950 wall mount 5,5 kW 380...480 V light cycle Variable speed drive ATV950 wall mount 7,5 kW 380...480 V light cycle Variable speed drive ATV930 wall mount 1,5 kW 200...240 V medium cycle Variable speed drive ATV930 wall mount 2,2 kW 200...240 V medium cycle Variable speed drive ATV340 4 kW 380...480 V light cycle Variable speed drive ATV340 5,5 kW 380...480 V light cycle Variable speed drive ATV320 0,55 kW 200...240 V Variable speed drive ATV320 0,75 kW 200...240 V Variable speed drive ATV320 1,1 kW 200...240 V Variable speed drive ATV320 1,5 kW 200...240 V Variable speed drive ATV320 4 kW 380...480 V Variable speed drive ATV320 5,5 kW 380...480 V Variable speed drive ATV310 5,5 kW Variable speed drive ATV310 7,5 kW Variable speed drive ATV930 7,5 kW 500...690 V light cycle Variable speed drive ATV930 11 kW 500...690 V light cycle Variable speed drive ATV930 10 CP 600 V light cycle Variable speed drive ATV930 15 CP 600 V light cycle Variable speed drive ATV320 5,5 kW 525...600 V Variable speed drive ATV310L 0,75 kW Variable speed drive ATV310L 1,5 kW Variable speed drive ATV310L 2,2 kW Variable speed drive ATV310L 3,0 kW Variable speed drive ATV310L 4,0 kW Variable speed drive ATV310L 5,5 kW
ciclu de utilizare	Light cycle (pentru sarcini grele) <0,8 s braking with 150 % braking torque for a 40 s cycle Light cycle (serviciu normal) <0,8 s braking with 120 % braking torque for a 40 s cycle Medium cycle (serviciu normal) <4 s braking with 135 % braking torque for a 40 s cycle Medium cycle (pentru sarcini grele) <4 s braking with 165 % braking torque for a 40 s cycle
putere medie disponibila	0,16 kW la 50 °C
conexiune electrica	borna, capacitate conexiune: <= 10 mm ² / AWG 8 pentru variator
tip de protectie	Thermal protection via drive
latime	105 mm

inaltime	345 mm
adancime	100 mm
greutate produs	1,8 kg

Mediu

grad de protectie IP	IP20
temperatura ambietala pentru depozitare	-25...70 °C
temperatura ambientala de functionare	0...50 °C

Unitati de ambalare

Unitate de masura pentru prima forma de impachetare	PCE
Număr de produse în pachet	1
Inaltime prima forma de impachetare	12,000 cm
Latime prima forma de impachetare	17,000 cm
Lungime prima forma de impachetare	36,000 cm
Greutate colet(Lbs)	2,051 kg
Unitate de masura pentru a doua forma de impachetare	P06
Numar unitati in a doua forma de impachetare	30
Inaltime a doua forma de impachetare	75,000 cm
Latime a doua forma de impachetare	60,000 cm
Lungime a doua forma de impachetare	80,000 cm
Greutate a doua forma de impachetare	70,000 kg

Garanție contractuală

Garantie (in luni)	18
--------------------	----


Environmental Data

Schneider Electric isi propune sa atinga nivelul Net Zero pana in 2050 prin parteneriate la nivelul lantului de aprovizionare, materiale cu impact mai redus si circularitate, prin campania „Use Better, Use Longer, Use Again” pentru a extinde durata de viata a produselor si reciclabilitatea.


[Environmental Data explicate >](#)

[Cum evaluam sustenabilitatea produselor >](#)


Use Better

 Materiale si ambalare	
Pachet cu carton reciclabil	Nu
Ambalaj fara plastic	Nu
Directiva RoHS a UE	Conform
Regulamentul REACH	Referința conține SVHC peste prag

Use Longer

 Prelungire durata de viata	
Reparare	Nu


Use Again

 Reambalare si refabricare	
Preluare la sfarsitul duratei de viata	Da

Dimensions Drawings

Dimensions

Right Side and Front View



Dimensions in mm

A	B	C	A1	C1	Ø
105	100	345	72	316	4.5

Dimensions in in.


A	B	C	A1	C1	Ø
4.13	3.94	13.58	2.83	12.44	0.18

Mounting and Clearance

Mounting and Clearance




(1) Braking resistor



Connections and Schema

Recommended Schema

1 Braking Resistor




A1 : Drive or external braking unit

A2 : Braking resistor

PA, PB : Bus DC

2 Braking Resistors



A1 : Drive or external braking unit

A2 : Braking resistor

PA, PB : Bus DC