

Fișă tehnică produs

Specificatii



Intreruptor ComPacT NSX630N, 50 kA la 415 VAC, unitate de declansare MicroLogic 7.3 E Vigi Vigi 570A, 4 poli 4d

C63N47E570

Principale

Gama	ComPacT noua generatie
nume produs	ComPacT NSX noua generatie
nume scurt al dispozitivului	NSX630N
Tip produs sau componenta	Intreruptor automat diferential
aplicatie a dispozitivului	Distributie
descriere poli	4P
descriere poli protejati	4d 3D + OSN 3d + N/2 3d
pozitie neutrului	Stanga
[In] curent nominal	570 A la 40 °C
[Ue] tensiune nominala de functionare	440 V c.a. 50/60 Hz
Tip retea electrica	C.a.
frecventa retea electrica	50/60 Hz
adeccare pentru izolatie	Da conformitate cu SR EN 60947-2
categorie de utilizare	Categoria A
[Icu] capacitate nominala limita de rupere la scurtcircuit	85 kA Icu la 220/240 V c.a. 50/60 Hz conformitate cu SR EN 60947-2 50 kA Icu la 380/415 V c.a. 50/60 Hz conformitate cu SR EN 60947-2 42 kA Icu la 440 V c.a. 50/60 Hz conformitate cu SR EN 60947-2 30 kA Icu la 500 V c.a. 50/60 Hz conformitate cu SR EN 60947-2 22 kA Icu la 525 V c.a. 50/60 Hz conformitate cu SR EN 60947-2 10 kA Icu la 660/690 V c.a. 50/60 Hz conformitate cu SR EN 60947-2 85 kA Icu la 240 V c.a. 50/60 Hz conformitate cu UL 60947-4-1 50 kA Icu la 480 V c.a. 50/60 Hz conformitate cu UL 60947-4-1 20 kA Icu la 600 V c.a. 50/60 Hz conformitate cu UL 60947-4-1
Nivel de performanta	N 50 kA 415 V c.a.
nume unitate de declansare	Micrologic 7.3 E
tehnologie unitate de declansare	Electronic
functii de protectie a unitatii de declansare	LSIR
tip de control	Comutare
Modul de montare a intreruptorului	Fix

Suplimentare

[Ui] tensiune nominala de izolatie	500 V c.a. 50/60 Hz
[Uimp] tensiune nominala de tinere la impuls	8 kV

[Ics] capacitate nominala de serviciu de rupere la scurtcircuit	85 kA la 220/240 V c.a. 50/60 Hz conformitate cu SR EN 60947-2 50 kA la 380/415 V c.a. 50/60 Hz conformitate cu SR EN 60947-2 42 kA la 440 V c.a. 50/60 Hz conformitate cu SR EN 60947-2 30 kA la 500 V c.a. 50/60 Hz conformitate cu SR EN 60947-2 11 kA la 525 V c.a. 50/60 Hz conformitate cu SR EN 60947-2 10 kA la 660/690 V c.a. 50/60 Hz conformitate cu SR EN 60947-2
durabilitate mecanica	15000 cic
durabilitate electrica	8000 cic la 440 V In/2 4000 cic la 440 V In 6000 cic la 690 V In/2 2000 cic la 690 V In
puterea disipata pe pol	55,6 W N 55,6 W L1 and L3 47,6 W L2
suport de montare	Placa dorsala
pozitie de montare	Orizantal si vertical Flat on the back
conexiune superioara	Fata
conexiune inferioara	Fata
pasul de conectare	45 mm
tip de protectie	L : for protectie la suprasarcina (timpindelungat) S : for protectie la scurtcircuit pe perioada scurta I : for protectie instantanee la scurtcircuit R : for protectie de scurgere la pamant
gama uitatii de declansare	570 A la 40 °C
Tip de reglare a preluarii de lunga durata Ir (protectie termica)	9 setari reglabile
[Ir] interval de reglare a restabilirii pe termen lung	250...570 A
Tip de reglare a intarzierii de lunga durata tr	Reglabil
[tr] reglarea intarzierii de lunga durata	15...400 s la 1.5 x Ir 0,5...16 s la 6 x Ir 0,35...11 s la 7.2 x Ir
Setarea protectiei neutrului	0,5 x Ir (3d + N/2) 1 x Ir (4d) Fara protectie (3d)
memorie termica	20 de minute inainte si dupa declansare
Reglarea preluarii protectiei de scurta durata tip Isd	Reglabil
[Isd] interval de reglare a restabilirii pe termen scurt	1,5...10 x Ir
Reglarea intarzierii protectiei de scurta durata tip tsd	Reglabil
[tsd] interval de reglare a intarzierii de scurta durata	0...0,4 s I ² t=off 0,1...0,4 s I ² t=on
Ajustarea protectiei instantanee tip Ii	Reglabil
[Ii] interval de reglare a restabilirii instantanee	1.5...12 x In
protectie de scurgere la pamant	Inglobat
clasa de protectie pentru scurgeri la pamant	Clasa A
Interval de reglare a curentului rezidual IΔn	Reglabil
[IΔn] interval de reglare a curentului rezidual	300 mA 500 mA 1 A 3 A 5 A 10 A

Mod specific protecției diferențiale	OFF cu ajutorul comutatorului rotativ ION
Interval de reglare a timpului de întârziere Δt	Reglabil
[Δt] interval de reglare a timpului de protecție împotriva curentului rezidual	0 ms 60 ms 150 ms 500 ms 1 s
blocare ZSI cu selectare a zonei	Fara
Numar de sloturi pentru auxiliare electrice	6 sloturi
semnalizare locala	LED intermitent (verde) for gata de funcționare LED 105 % Ir (rosu) for suprasarcină LED 90 % Ir (portocaliu) for suprasarcină
tip afisaj	Ecran LCD
Tip de masurare	Wattmetru
comunicare a datelor	Istoric si tabele de evenimente cu marcaj temporal Indicatoare de mentenanta Valori instantanee si de cerere Maximetre/minimetre Setari de protectie si alarma Calitate energie electrica Masurare a energiei Cerere de curent si putere
Latime	185 mm
Inaltime	255 mm
Adancime	110 mm
greutate produs	8,13 kg

Mediu

standarde	SR EN 60947-2
categorie de supratensiune	Clasa II
clasa de protectie la electrocutare	Clasa II
grad de poluare	3 conformitate cu SR EN 60664-1
grad de protectie IP	IP40 conforming to SR EN 60529
grad de protectie IK	IK07 conforming to IEC 62262
temperatura ambientala de functionare	-25...70 °C
temperatura ambietala pentru depozitare	-40...85 °C
umiditate relativa	0...95 %
altitudinea de functionare	0...2000 m fără declarare 2000 m...5000 m cu declarare

Unitati de ambalare

Unitate de masura pentru prima forma de impachetare	PCE
Numar unitati in prima forma de impachetare	1
Inaltime prima forma de impachetare	16,8 cm
Latime prima forma de impachetare	25,5 cm
Lungime prima forma de impachetare	18,5 cm

Greutate prima forma de impachetare	10,0 kg
--	---------

Garanție contractuală

Garantie	18 luni
----------	---------

Environmental Data

Schneider Electric isi propune sa atinga nivelul Net Zero pana in 2050 prin parteneriate la nivelul lantului de aprovizionare, materiale cu impact mai redus si circularitate, prin campania „Use Better, Use Longer, Use Again” pentru a extinde durata de viata a produselor si reciclabilitatea.

[Environmental Data explicate >](#)

[Cum evaluam sustenabilitatea produselor >](#)

Amprenta de mediu

Amprenta de carbon (kg CO2 eq.) 804

Raport de mediu [Profilul ambiental al produsului](#)

Use Better

Materiale si ambalare

Pachet cu carton reciclabil Da

Ambalaj fara plastic Nu

[Directiva RoHS UE](#) Conform cu scutiile

Numar SCIP C022f0ed-d721-416c-be6b-f13650625ce5

Regulamentul REACH [Declaratia REACH](#)

Performanta continutului de halogen **Produsul contine halogen peste praguri**

Nu contine silicon Nu

Use Longer

Prelungire durata de viata

Posibilitate de modernizare Da

Use Again

Reambalare si refabricare

Profil circularitate [Informatii privind sfarsitul duratei de viata](#)

Preluare la sfarsitul duratei de viata No

DEEE  **Produsul trebuie sa fie eliminat de pe piata din Uniunea Europeana dupa colectarea specifica a deseurilor si sa nu ajunga niciodata in pubele de gunoi**

Offer Marketing Illustration

Product benefits / Features

ComPacT NSX Moulded Case Circuit Breaker



Protection begins with prevention

Designed to prevent an electrical fire through integrated earth leakage protection with preventive maintenance thanks to its Everlink power connections.



Maximize power availability

By providing corrective, preventive, and predictive maintenance for asset management thanks to our advanced MicroLogic trip units.



Connectivity

Designed to connect to EcoStruxure Power, an IoT-connected architecture for improving every aspect of your power distribution system.



Offer Marketing Illustration

Product benefits / Features



Offer Marketing Illustration

Product benefits / Features



ComPacT NSX
Range Accessories

Wireless auxiliary contact

Short terminal shield

Interphase barriers

Long terminal shield

Rotary handles

Standard auxiliary contact

MN undervoltage release

MX shunt release

Standard motor mechanism module

The image displays a collection of accessories for the ComPacT NSX circuit breaker range. At the top left, a green circular graphic partially shows a circuit breaker. Below it, nine individual accessories are arranged in a 3x3 grid, each with a small image and a text label. The accessories include: a wireless auxiliary contact (green and black), a short terminal shield (black), interphase barriers (black), a long terminal shield (black), rotary handles (black and green), a standard auxiliary contact (grey), an MN undervoltage release (black), an MX shunt release (yellow and black), and a standard motor mechanism module (black).

Offer Marketing Illustration

Product benefits / Features



ComPacT NSX

Technical Benefits

- Nominal current: 16 to 630 A and 9 breaking capacities for the 2 sizes of circuit breakers
- 1, 2, 3, and 4 pole versions available
- Large range of electronic and thermal-magnetic protections
- Plug and ready wiring system and communicating accessories
- Integrated earth leakage protection via MicroLogic Vigi (earth leakage circuit breaker - ELCB)
- Advanced trip unit with integrated power metering: I, U, P, E, THD, f, CosPhi

Technical Illustration

Assembly's dimensions

