


Product features and key data

Luminaire colour	RAL9006 White aluminium
Ingress Protection (IP) rating	IP20
Protection class	II
Net length	368 mm
Net width	62 mm
Net height	35 mm
Weight	0,2 kg

Available accessories

Material	Description
 07650 L450 7LV 225 03 IP64 7265700	Trunking for E-Line 7651 IP64 continuous line applications. To simplify installation, a pre-assembled continuous line coupler is included in the scope of delivery for connection to a further trunking unit. Length of the trunking: 4471 mm. Surface coated silver-grey. With 7-conductor through-wiring. Cable cross-section 2.5 mm ² .
 07650 L225 7LV E 225 03 IP64 7265800	Trunking for E-Line 7651 IP64 continuous line single luminaires or continuous line terminations. Length of the trunking: 2258 mm. Surface coated silver-grey. With 7-conductor through-wiring. Cable cross-section 2.5 mm ² .
 07650 L450 7LV 150 03 IP64 7265900	Trunking for E-Line 7651 IP64 continuous line applications. To simplify installation, a pre-assembled continuous line coupler is included in the scope of delivery for connection to a further trunking unit. Length of the trunking: 4471 mm. Surface coated silver-grey. With 7-conductor through-wiring. Cable cross-section 2.5 mm ² .
 07650 L300 7LV 150 03 IP64 7266000	Trunking for E-Line 7651 IP64 continuous line applications. To simplify installation, a pre-assembled continuous line coupler is included in the scope of delivery for connection to a further trunking unit. Length of the trunking: 2996 mm. Surface coated silver-grey. With 7-conductor through-wiring. Cable cross-section 2.5 mm ² .
 07650 L150 7LV E 150 03 IP64 7266100	Trunking for E-Line 7651 IP64 continuous line single luminaires or continuous line terminations. Length of the trunking: 1521 mm. Surface coated silver-grey. With 7-conductor through-wiring. Cable cross-section 2.5 mm ² .
 07650 L450 7+7LV 225 03 IP64 7266200	Trunking for E-Line 7651 IP64 continuous line applications. To simplify installation, a pre-assembled continuous line coupler is included in the scope of delivery for connection to a further trunking unit. Length of the trunking: 4471 mm. Surface coated silver-grey. With 7-core through-wiring for segmenting circuits and supplementary 7-core through-wiring for additional emergency light or light management uses.
 07650 L225 7+7LV E 225 03 IP64 7266300	Trunking for E-Line 7651 IP64 continuous line single luminaires or continuous line terminations. Length of the trunking: 2258 mm. Surface coated silver-grey. With 7-core through-wiring for segmenting circuits and supplementary 7-core through-wiring for additional emergency light or light management uses.
 07650 L450 7+7LV 150 03 IP64 7266400	Trunking for E-Line 7651 IP64 continuous line applications. To simplify installation, a pre-assembled continuous line coupler is included in the scope of delivery for connection to a further trunking unit. Length of the trunking: 4471 mm. Surface coated silver-grey. With 7-core through-wiring for segmenting circuits and supplementary 7-core through-wiring for additional emergency light or light management uses.



07650 L300 7+7LV 150 03 IP64
7266500

Trunking for E-Line 7651 IP64 continuous line applications. To simplify installation, a pre-assembled continuous line coupler is included in the scope of delivery for connection to a further trunking unit. Length of the trunking: 2996 mm. Surface coated silver-grey. With 7-core through-wiring for segmenting circuits and supplementary 7-core through-wiring for additional emergency light or light management uses.



07650 L150 7+7LV E 150 03 IP64
7266600

Trunking for E-Line 7651 IP64 continuous line single luminaires or continuous line terminations. Length of the trunking: 1521 mm. Surface coated silver-grey. With 7-core through-wiring for segmenting circuits and supplementary 7-core through-wiring for additional emergency light or light management uses.



07650 L75 7LV E 75 03
7272800

Trunking for E-Line 7651 continuous line single luminaires or continuous line terminations. Length of the trunking: 737,5 mm. Surface coated silver-grey. With 7-conductor through-wiring. Cable cross-section 2.5 mm².



07650 L150 7LV E 150 03
7272900

Trunking for E-Line 7651 continuous line single luminaires or continuous line terminations. Length of the trunking: 1475 mm. Surface coated silver-grey. With 7-conductor through-wiring. Cable cross-section 2.5 mm².



07650 L300 7LV 150 03
7273000

Trunking for E-Line 7651 continuous line applications. To simplify installation, a pre-assembled continuous line coupler is included in the scope of delivery for connection to a further trunking unit. Length of the trunking: 2950 mm. Surface coated silver-grey. With 7-conductor through-wiring. Cable cross-section 2.5 mm².



07650 L450 7LV 150 03
7273100

Trunking for E-Line 7651 continuous line applications. To simplify installation, a pre-assembled continuous line coupler is included in the scope of delivery for connection to a further trunking unit. Length of the trunking: 4425 mm. Surface coated silver-grey. With 7-conductor through-wiring. Cable cross-section 2.5 mm².



07650 L225 7LV E 225 03
7273700

Trunking for E-Line 7651 continuous line single luminaires or continuous line terminations. Length of the trunking: 2212,5 mm. Surface coated silver-grey. With 7-conductor through-wiring. Cable cross-section 2.5 mm².



07650 L450 7LV 225 03
7274000

Trunking for E-Line 7651 continuous line applications. To simplify installation, a pre-assembled continuous line coupler is included in the scope of delivery for connection to a further trunking unit. Length of the trunking: 4425 mm. Surface coated silver-grey. With 7-conductor through-wiring. Cable cross-section 2.5 mm².



07650 L150 7+7LV E 150 03
7274500

Trunking for E-Line 7651 continuous line single luminaires or continuous line terminations. Length of the trunking: 1475 mm. Surface coated silver-grey. With 7-core through-wiring for segmenting circuits and supplementary 7-core through-wiring for additional emergency light or light management uses.



07650 L300 7+7LV 150 03
7274600

Trunking for E-Line 7651 continuous line applications. To simplify installation, a pre-assembled continuous line coupler is included in the scope of delivery for connection to a further trunking unit. Length of the trunking: 2950 mm. Surface coated silver-grey. With 7-core through-wiring for segmenting circuits and supplementary 7-core through-wiring for additional emergency light or light management uses.



07650 L450 7+7LV 150 03
7274700

Trunking for E-Line 7651 continuous line applications. To simplify installation, a pre-assembled continuous line coupler is included in the scope of delivery for connection to a further trunking unit. Length of the trunking: 4425 mm. Surface coated silver-grey. With 7-core through-wiring for segmenting circuits and supplementary 7-core through-wiring for additional emergency light or light management uses.



07650 L225 7+7LV E 225 03
7275300

Trunking for E-Line 7651 continuous line single luminaires or continuous line terminations. Length of the trunking: 2212,5 mm. Surface coated silver-grey. With 7-core through-wiring for segmenting circuits and supplementary 7-core through-wiring for additional emergency light or light management uses.



07650 L450 7+7LV 225 03
7275400

Trunking for E-Line 7651 continuous line applications. To simplify installation, a pre-assembled continuous line coupler is included in the scope of delivery for connection to a further trunking unit. Length of the trunking: 4425 mm. Surface coated silver-grey. With 7-core through-wiring for segmenting circuits and supplementary 7-core through-wiring for additional emergency light or light management uses.



07650 L75 7LV E 37 03
7276200

Trunking for E-Line 7651 continuous line single luminaires or continuous line terminations. Length of the trunking: 737,5 mm. Surface coated silver-grey. With 7-conductor through-wiring. Cable cross-section 2.5 mm².



07650 L150 7LV E 37 03
7276300

Trunking for E-Line 7651 continuous line single luminaires or continuous line terminations. Length of the trunking: 1475 mm. Surface coated silver-grey. With 7-conductor through-wiring. Cable cross-section 2.5 mm².



07650 L225 7LV E 37 03
7276400

Trunking for E-Line 7651 continuous line single luminaires or continuous line terminations. Length of the trunking: 2212,5 mm. Surface coated silver-grey. With 7-conductor through-wiring. Cable cross-section 2.5 mm².



07650 L300 7LV 37 03
7276500

Trunking for E-Line 7651 continuous line applications. To simplify installation, a pre-assembled continuous line coupler is included in the scope of delivery for connection to a further trunking unit. Length of the trunking: 2950 mm. Surface coated silver-grey. With 7-conductor through-wiring. Cable cross-section 2.5 mm².



07650 L450 7LV 37 03
7276600

Trunking for E-Line 7651 continuous line applications. To simplify installation, a pre-assembled continuous line coupler is included in the scope of delivery for connection to a further trunking unit. Length of the trunking: 4425 mm. Surface coated silver-grey. With 7-conductor through-wiring. Cable cross-section 2.5 mm².

Offer text

Gear tray of sheet steel. For combining with E-Line 07650... trunking. With integrated LiveLink WiFi control unit for daylight-dependent control and presence detection as well as WLAN module for reliable commissioning and operation (WPA2 encryption). Colour silver gray (similar to RAL 9006). Dimensions (L x W x H): 368 mm x 62 mm x 35 mm. Complies with DIN 10500 and is suitable for applications in HACCP, IFS Version 6 and/or BRC Global Standard Food Version 7 certified companies in the food and beverage industry. Further information about LiveLink can be found at www.trilux.com.