

Fișă tehnică produs

Specificatii



Rack PDU, cu switch-uri, 1U, 12 A/ 208 V, 10 A/230 V, (8) C13



AP7920B

Prezentare generala

Prezentare	This APC Switched Rack PDU power distribution unit has a wide range of standardized PDU features that increase network efficiency, manageability and functionality. The output and input connections are (8)C13. Network management capabilities allow you to configure and manage rack PDUs from remote locations. It has has a local current monitoring display that gives a visible warning in case of an overload. The remote individual outlet control provides real-time monitoring of connected loads. It has a multi-tier user access that enables you to restrict unauthorized use of outlets. This rack has a single input power source making it easy to install.
------------	--

Termen de livrare	De obicei în stoc
-------------------	-------------------

Principale

culoare	Negru
Tip produs sau componenta	PDU
Tip PDU	Switched
Cord length	2,0 m
numar de cabluri	1
echipament furnizat	Ghid de instalare Console de montare rack Manual de utilizare

Suplimentare

Input Voltage	200 V 208 V 230 V
inaltime	4,4 cm
latime	44,5 cm
Output Voltage	208 V 230 V
adancime	10,8 cm
greutate produs	2,27 kg
locul de montare	Fata Spate
Mounting preference	No preference
Input Plug Type	IEC 60320 C14
mod de montare	Montaj rack
Rack units	1U
pozitie de montare	Orizontal

Declinare de responsabilitate: Această documentație nu se substituie și nu trebuie utilizată pentru stabilirea adecvării sau fiabilității acestor produse pentru aplicații utilizator

[In] calibru	12 A
Tensiune de intrare acceptabilă	200...240 V
Input current limits	15 A
Capacitate sarcină	2300 VA
curent nominal	10 A - 230 V 12 A - 208 V
frecventa retea	50/60 Hz
Outlet type and quantity	8 IEC 60320 C13

Mediu

certificari produs	Listat cUL UE CSA GOST IRAM listat de UL VDE
standarde	EN 55022 Clasa A EN 55024 EN 61000-3-2 EN 61000-3-3 UL 60950
temperatura ambientala de functionare	0...45 °C
Umiditate relativa	0...95 %
altitudine de functionare	0...10000 ft
temperatura ambietala pentru depozitare	-25...65 °C
Umiditate relativa de depozitare	0...95 %
altitudinea de depozitare	0...15240 m

Unitati de ambalare

Unitate de masura pentru prima forma de impachetare	PCE
Numar unitati in prima forma de impachetare	1
Inaltime prima forma de impachetare	7 cm
Latime prima forma de impachetare	34,3 cm
Lungime prima forma de impachetare	47 cm
Greutate prima forma de impachetare	3,45 kg

Garanție contractuală

Garantie	2 ani reparații sau înlocuire
----------	-------------------------------

Environmental Data

Schneider Electric isi propune sa atinga nivelul Net Zero pana in 2050 prin parteneriate la nivelul lantului de aprovizionare, materiale cu impact mai redus si circularitate, prin campania „Use Better, Use Longer, Use Again” pentru a extinde durata de viata a produselor si reciclabilitatea.

Environmental Data explicate >

Cum evaluam sustenabilitatea produselor >

Amprenta de mediu	
Amprenta de carbon (kg CO2 eq.)	916
Raport de mediu	Profilul ambiental al produsului

Use Better

Materiale si ambalare	
Pachet cu carton reciclabil	Da
Ambalaj fara plastic	Nu
Directiva RoHS UE	Conform cu scutirile
Numar SCIP	1cdb2fed-a06f-4574-913d-8df8e70936b2
Regulamentul REACH	Declaratia REACH

Eficienta energetica	
Eficienta Energetica Optimizata	Produs eficient din punct de vedere energetic

Use Again

Reambalare si refabricare	
Profil circularitate	Informatii privind sfarsitul duratei de viata
Baterie detasabila	Yes
Preluare la sfarsitul duratei de viata	Yes

Image of product / Alternate images

Alternative



