

încercare climatică	conformitate cu IACS E10 exposure to damp heat conformitate cu IEC 60947-1 Annex Q category D exposure to damp heat
temperatura permisă a aerului în jurul aparatului	-40...60 °C 60...70 °C cu declasare
altitudinea de funcționare	0...3000 m
rezistența la foc	850 °C conformitate cu IEC 60695-2-1
întârziere flacăra	V1 conformitate cu UL 94
rezistența mecanică	Vibrații contactor deschis (2 Gn, 5...300 Hz) Vibrații contactor închis (4 Gn, 5...300 Hz) Șocuri contactor închis (15 Gn pentru 11 ms) Șocuri contactor deschis (10 Gn pentru 11 ms)
înălțime	122 mm
lățime	55 mm
adâncime	120 mm
greutate produs	0,93 kg

Unitati de ambalare

Unitate de masura pentru prima forma de impachetare	PCE
Număr de produse în pachet	1
Înălțime prima forma de impachetare	6,2 cm
Lățime prima forma de impachetare	13,7 cm
Lungime prima forma de impachetare	15,3 cm
Greutate colet(Lbs)	995 g
Unitate de masura pentru a doua forma de impachetare	S02
Numar unitati in a doua forma de impachetare	10
Înălțime a doua forma de impachetare	15 cm
Lățime a doua forma de impachetare	30 cm
Lungime a doua forma de impachetare	40 cm
Greutate a doua forma de impachetare	10,288 kg

Garanție contractuală

Garantie (in luni)	18
--------------------	----

Offer Marketing Illustration

Product benefits / Features

TeSys Deca Contactors



Reliable

Multi-standard solutions, high reliability, long mechanical and electrical durability for different sizes, and the most complete accessories.



Energy efficiency

These electronic-coil contactors require up to 80 % less energy than electro-mechanical contactors.



Universal

Multi standards certified (IEC, UL, CSA, CCC, EAC, Marine), Green Premium compliant (RoHS/REACH).



Offer Marketing Illustration

Product benefits / Features



Offer Marketing Illustration

Product benefits / Features

TeSys Deca Contactors

Technical Benefits



- Deca green delivers a consistent low consumption range of contactors from 9 A to 80 A.
- Covers control voltage from 24 to 250 V, with same coils for AC and DC.
- Designed to meet the requirements of industrial and HVAC applications
- With IEC60335-1 compliance, improved fire resistance, and dust-proof auxiliaries
- Suitable for safety applications thanks to mechanically linked contacts and mirror contacts
- Outstanding breaking/making capacity up to 20 In with PLC direct connection

Technical Illustration

Assembly's dimensions

